

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1245902

Luminaire Tested: P3AS02R659024DE010 E3DLP1GPH

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1245902
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-41)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS02R659024DE010 E3DLP1GPH
Description: 3in Adjustable LED luminaire with, R65 optic, 2400K CCT AND, 90CRI , E3DLP1GPH TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 73.0 lumens
Efficiency: N/A
Efficacy: 20.3 lumens/watt
Spacing Criteria (0/90/45): 0.79 / 0.79 / 0.83
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 3.6
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1245902

CATALOG NUMBER: P3AS02R659024DE010 E3DLP1GPH

Luminous Intensity Polar Plot



TEST NUMBER: P1245902

CATALOG NUMBER: P3AS02R659024DE010 E3DLP1GPH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	110	107	105	110	108	105	103	104	102	100		100	98	97		96
2	107	101	97	93	104	100	96	92	96	93	90		93	91	88		91
3	101	94	88	84	99	92	87	83	90	85	82		87	84	81		85
4	95	87	81	77	93	86	80	76	84	79	75		82	78	74		80
5	90	81	75	70	88	80	74	70	78	73	69		77	72	69		75
6	85	76	69	65	84	75	69	65	73	68	64		72	67	64		71
7	81	71	65	60	79	70	64	60	69	64	60		68	63	59		67
8	77	67	60	56	75	66	60	56	65	59	56		64	59	55		63
9	73	63	57	52	72	62	56	52	61	56	52		60	55	52		60
10	69	59	53	49	68	59	53	49	58	53	49		57	52	49		56

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	18551
5°	18094
10°	16856
15°	15097
20°	13044
25°	10839
30°	8558
35°	6344
40°	4380
45°	2698
50°	1467
55°	918
60°	789
65°	726
70°	577
75°	508
80°	505
85°	503

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 2698 cd/sqm

TEST NUMBER: P1245902

CATALOG NUMBER: P3AS02R659024DE010 E3DLP1GPH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	7.6	10.5
10°-20°	18.5	25.3
20°-30°	20.4	28.0
30°-40°	14.9	20.4
40°-50°	7.0	9.5
50°-60°	2.3	3.2
60°-70°	1.4	1.9
70°-80°	0.7	0.9
80°-90°	0.2	0.3
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	46.6	63.8
0°-40°	61.4	84.2
0°-60°	70.7	96.9
0°-90°	73.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	73.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	85	
5°	82	8
15°	66	18
25°	45	20
35°	24	15
45°	9	7
55°	2	2
65°	1	1
75°	1	1
85°	0	0
90°	0	

TEST NUMBER: P1245902

CATALOG NUMBER: P3AS02R659024DE010 E3DLP1GPH

CANDELA DISTRIBUTION (FULL):

	0°
0°	84.6
2.5°	84.1
5°	82.2
7.5°	79.4
10°	75.7
12.5°	71.4
15°	66.5
17.5°	61.3
20°	55.9
22.5°	50.3
25°	44.8
27.5°	39.3
30°	33.8
32.5°	28.5
35°	23.7
37.5°	19.3
40°	15.3
42.5°	11.7
45°	8.7
47.5°	6.3
50°	4.3
52.5°	2.9
55°	2.4
57.5°	2.1
60°	1.8
62.5°	1.6
65°	1.4
67.5°	1.2
70°	0.9
72.5°	0.8
75°	0.6
77.5°	0.5
80°	0.4
82.5°	0.3
85°	0.2
87.5°	0.1
90°	0.0

(END OF REPORT)