

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1246016

Luminaire Tested: P3AS05R159024DE010 E3DLD1GPH

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1246016
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-2)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS05R159024DE010 E3DLD1GPH
Description: 3in Adjustable LED luminaire with, R15 optic, 2400K CCT AND, 90CRI , E3DLD1GPH TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 170.9 lumens
Efficiency: N/A
Efficacy: 23.7 lumens/watt
Spacing Criteria (0/90/45): 0.76 / 0.76 / 0.82
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 7.2
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1246016

CATALOG NUMBER: P3AS05R159024DE010 E3DLD1GPH

Luminous Intensity Polar Plot



TEST NUMBER: P1246016

CATALOG NUMBER: P3AS05R159024DE010 E3DLD1GPH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	109	107	104	110	107	105	102	103	101	99		99	98	96		96
2	106	100	96	92	104	99	95	91	95	92	89		92	90	87		90
3	100	93	87	83	98	91	86	82	89	84	81		86	82	79		84
4	94	86	80	75	92	85	79	74	82	77	73		80	76	73		78
5	89	80	73	68	87	79	73	68	77	72	67		75	71	67		74
6	84	74	68	63	83	73	67	63	72	66	62		70	66	62		69
7	80	70	63	58	78	69	63	58	67	62	58		66	61	58		65
8	76	65	59	54	74	65	58	54	63	58	54		62	57	54		61
9	72	61	55	51	71	61	55	51	60	54	50		59	54	50		58
10	68	58	52	48	67	57	51	47	57	51	47		56	51	47		55

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	43133
5°	41955
10°	38343
15°	33598
20°	28819
25°	24050
30°	19243
35°	14429
40°	10477
45°	6853
50°	4298
55°	2906
60°	2544
65°	2335
70°	2244
75°	2033
80°	1894
85°	1510

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 6853 cd/sqm

TEST NUMBER: P1246016

CATALOG NUMBER: P3AS05R159024DE010 E3DLD1GPH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	17.6	10.3
10°-20°	41.2	24.1
20°-30°	45.4	26.6
30°-40°	34.0	19.9
40°-50°	17.6	10.3
50°-60°	7.3	4.3
60°-70°	4.5	2.6
70°-80°	2.5	1.5
80°-90°	0.7	0.4
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	104.2	61.0
0°-40°	138.2	80.9
0°-60°	163.2	95.5
0°-90°	170.9	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	170.9	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	197	
5°	191	18
15°	148	41
25°	99	45
35°	54	34
45°	22	18
55°	8	7
65°	4	5
75°	2	3
85°	1	1
90°	0	

TEST NUMBER: P1246016

CATALOG NUMBER: P3AS05R159024DE010 E3DLD1GPH

CANDELA DISTRIBUTION (FULL):

0°	
0°	196.7
1°	196.9
2°	196.3
3°	195.0
4°	193.0
5°	190.6
6°	187.6
7°	184.4
8°	180.5
9°	176.3
10°	172.2
12.5°	160.3
15°	148.0
17.5°	135.6
20°	123.5
22.5°	111.1
25°	99.4
27.5°	87.7
30°	76.0
32.5°	64.6
35°	53.9
37.5°	44.8
40°	36.6
42.5°	29.0
45°	22.1
47.5°	16.7
50°	12.6
52.5°	9.3
55°	7.6
57.5°	6.7
60°	5.8
62.5°	5.2
65°	4.5
67.5°	3.9
70°	3.5
72.5°	2.8
75°	2.4
77.5°	1.9
80°	1.5
82.5°	1.1
85°	0.6
87.5°	0.2
90°	0.0

(END OF REPORT)