

Scaled data based on original data using  
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-  
State Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1246252

Luminaire Tested: P3AS05R559024DE010 E3DLD1MW

Issue Date: 1/30/2026

**Test Information**

Test Method: LM-79-2019  
Report Number: P1246252  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-34)  
Test Lab: INNOVATION CENTER  
Issue Date: 1/30/2026  
Manufacturer: COOPER LIGHTING SOLUTIONS  
Product Line: IRiS  
Catalog Number: P3AS05R559024DE010 E3DLD1MW  
Description: 3in Adjustable LED luminaire with, R55 optic, 2400K CCT AND, 90CRI , E3DLD1MW TRIM  
Light Source: -  
Ballast/Driver: -

**Summary**


Lumens per Lamp: N/A  
Luminaire Lumens: 374.0 lumens  
Efficiency: N/A  
Efficacy: 51.9 lumens/watt  
Spacing Criteria (0/90/45): 0.91 / 0.91 / 0.97  
Luminous Opening: Circular (Dia: 0.25' x H: 0')  
CIE Type: Direct

Input Watts (W): 7.2  
Input Voltage (V): NR  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 24 FT

TEST NUMBER: P1246252

CATALOG NUMBER: P3AS05R559024DE010 E3DLD1MW

### Luminous Intensity Polar Plot



TEST NUMBER: P1246252

CATALOG NUMBER: P3AS05R559024DE010 E3DLD1MW

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

|     |     |     |     |     |     |     |     |     |     |     |     |  |     |     |     |  |     |
|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|--|-----|-----|-----|--|-----|
| RF  | 20  |     |     |     | 20  |     |     |     | 20  |     |     |  | 20  |     |     |  | 20  |
| RC  | 80  |     |     |     | 70  |     |     |     | 50  |     |     |  | 30  |     |     |  | 10  |
| RW  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 50  | 30  | 10  |  | 50  | 30  | 10  |  | 50  |
| RCR |     |     |     |     |     |     |     |     |     |     |     |  |     |     |     |  |     |
| 0   | 119 | 119 | 119 | 119 | 116 | 116 | 116 | 116 | 111 | 111 | 111 |  | 106 | 106 | 106 |  | 102 |
| 1   | 112 | 109 | 106 | 103 | 110 | 107 | 104 | 102 | 103 | 100 | 98  |  | 99  | 97  | 96  |  | 95  |
| 2   | 105 | 100 | 95  | 91  | 103 | 98  | 93  | 90  | 94  | 91  | 88  |  | 91  | 88  | 86  |  | 89  |
| 3   | 99  | 91  | 85  | 81  | 97  | 90  | 84  | 80  | 87  | 82  | 79  |  | 85  | 81  | 77  |  | 82  |
| 4   | 93  | 84  | 77  | 72  | 91  | 83  | 77  | 72  | 80  | 75  | 71  |  | 78  | 74  | 70  |  | 76  |
| 5   | 87  | 77  | 71  | 66  | 85  | 76  | 70  | 65  | 75  | 69  | 65  |  | 73  | 68  | 64  |  | 71  |
| 6   | 82  | 72  | 65  | 60  | 80  | 71  | 64  | 60  | 69  | 64  | 59  |  | 68  | 63  | 59  |  | 66  |
| 7   | 77  | 67  | 60  | 55  | 76  | 66  | 59  | 55  | 65  | 59  | 54  |  | 63  | 58  | 54  |  | 62  |
| 8   | 73  | 62  | 55  | 51  | 72  | 62  | 55  | 51  | 60  | 55  | 50  |  | 59  | 54  | 50  |  | 58  |
| 9   | 69  | 58  | 51  | 47  | 68  | 58  | 51  | 47  | 57  | 51  | 47  |  | 56  | 50  | 46  |  | 55  |
| 10  | 65  | 55  | 48  | 44  | 64  | 54  | 48  | 44  | 53  | 47  | 43  |  | 52  | 47  | 43  |  | 52  |

**AVERAGE LUMINANCE (cd/sqm):**

|     |       |
|-----|-------|
|     | 0°    |
| 0°  | 70323 |
| 5°  | 69425 |
| 10° | 66688 |
| 15° | 62384 |
| 20° | 56892 |
| 25° | 50761 |
| 30° | 44412 |
| 35° | 36888 |
| 40° | 29083 |
| 45° | 19723 |
| 50° | 12042 |
| 55° | 6232  |
| 60° | 5833  |
| 65° | 5500  |
| 70° | 5129  |
| 75° | 4490  |
| 80° | 4420  |
| 85° | 3271  |

**MAXIMUM LUMINANCE 45°-90°:**

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 19723 cd/sqm

TEST NUMBER: P1246252

CATALOG NUMBER: P3AS05R559024DE010 E3DLD1MW

**ZONAL LUMENS:**

| Zone      | Lumens | % Fixture |
|-----------|--------|-----------|
| 0°-10°    | 29.6   | 7.9       |
| 10°-20°   | 76.8   | 20.5      |
| 20°-30°   | 96.2   | 25.7      |
| 30°-40°   | 85.8   | 23.0      |
| 40°-50°   | 50.3   | 13.4      |
| 50°-60°   | 17.4   | 4.6       |
| 60°-70°   | 10.5   | 2.8       |
| 70°-80°   | 5.8    | 1.6       |
| 80°-90°   | 1.7    | 0.4       |
| 90°-100°  | 0.0    | 0.0       |
| 100°-110° | 0.0    | 0.0       |
| 110°-120° | 0.0    | 0.0       |
| 120°-130° | 0.0    | 0.0       |
| 130°-140° | 0.0    | 0.0       |
| 140°-150° | 0.0    | 0.0       |
| 150°-160° | 0.0    | 0.0       |
| 160°-170° | 0.0    | 0.0       |
| 170°-180° | 0.0    | 0.0       |
| 0°-30°    | 202.5  | 54.2      |
| 0°-40°    | 288.4  | 77.1      |
| 0°-60°    | 356.0  | 95.2      |
| 0°-90°    | 374.0  | 100.0     |
| 90°-120°  | 0.0    | 0.0       |
| 90°-150°  | 0.0    | 0.0       |
| 90°-180°  | 0.0    | 0.0       |
| 0°-180°   | 374.0  | 100.0     |

**CANDELA DISTRIBUTION:**

|     | 0°  | Flux |
|-----|-----|------|
| 0°  | 321 |      |
| 5°  | 315 | 30   |
| 15° | 275 | 77   |
| 25° | 210 | 96   |
| 35° | 138 | 86   |
| 45° | 64  | 50   |
| 55° | 16  | 17   |
| 65° | 11  | 11   |
| 75° | 5   | 6    |
| 85° | 1   | 2    |
| 90° | 0   |      |

TEST NUMBER: P1246252

CATALOG NUMBER: P3AS05R559024DE010 E3DLD1MW

**CANDELA DISTRIBUTION (FULL):**

| 0°    |       |
|-------|-------|
| 0°    | 320.7 |
| 2.5°  | 318.9 |
| 5°    | 315.4 |
| 7.5°  | 308.3 |
| 10°   | 299.5 |
| 12.5° | 288.4 |
| 15°   | 274.8 |
| 17.5° | 260.2 |
| 20°   | 243.8 |
| 22.5° | 227.0 |
| 25°   | 209.8 |
| 27.5° | 192.6 |
| 30°   | 175.4 |
| 32.5° | 156.8 |
| 35°   | 137.8 |
| 37.5° | 119.3 |
| 40°   | 101.6 |
| 42.5° | 82.6  |
| 45°   | 63.6  |
| 47.5° | 48.6  |
| 50°   | 35.3  |
| 52.5° | 23.0  |
| 55°   | 16.3  |
| 57.5° | 14.6  |
| 60°   | 13.3  |
| 62.5° | 11.9  |
| 65°   | 10.6  |
| 67.5° | 9.3   |
| 70°   | 8.0   |
| 72.5° | 6.6   |
| 75°   | 5.3   |
| 77.5° | 4.4   |
| 80°   | 3.5   |
| 82.5° | 2.2   |
| 85°   | 1.3   |
| 87.5° | 0.9   |
| 90°   | 0.0   |

(END OF REPORT)