

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1246400

Luminaire Tested: P3AS09R159024DE010 E3DLP1GPH

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1246400
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-1)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS09R159024DE010 E3DLP1GPH
Description: 3in Adjustable LED luminaire with, R15 optic, 2400K CCT AND, 90CRI , E3DLP1GPH TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 194.9 lumens
Efficiency: N/A
Efficacy: 17.6 lumens/watt
Spacing Criteria (0/90/45): 0.52 / 0.52 / 0.61
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 11.1
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1246400

CATALOG NUMBER: P3AS09R159024DE010 E3DLP1GPH

Luminous Intensity Polar Plot



TEST NUMBER: P1246400

CATALOG NUMBER: P3AS09R159024DE010 E3DLP1GPH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	110	108	106	111	108	106	104	104	102	101		100	99	98		97
2	108	103	98	95	105	101	97	94	98	95	92		95	92	90		92
3	102	96	91	87	100	94	90	86	92	88	85		89	86	83		87
4	97	90	84	80	95	88	83	79	86	82	78		84	81	78		82
5	93	84	78	74	91	83	78	74	81	77	73		80	76	73		78
6	88	79	73	69	87	79	73	69	77	72	69		76	71	68		74
7	84	75	69	65	83	74	69	65	73	68	64		72	67	64		71
8	80	71	65	61	79	71	65	61	69	64	61		68	64	61		68
9	77	68	62	58	76	67	62	58	66	61	58		65	61	57		64
10	74	64	59	55	73	64	59	55	63	58	55		62	58	55		62

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	84094
5°	77724
10°	62056
15°	46879
20°	35680
25°	27195
30°	19471
35°	12715
40°	7786
45°	4714
50°	3138
55°	2409
60°	2061
65°	1816
70°	1603
75°	1610
80°	1137
85°	755

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 4714 cd/sqm

TEST NUMBER: P1246400

CATALOG NUMBER: P3AS09R159024DE010 E3DLP1GPH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	31.3	16.0
10°-20°	57.7	29.6
20°-30°	51.4	26.3
30°-40°	30.4	15.6
40°-50°	12.5	6.4
50°-60°	5.8	3.0
60°-70°	3.6	1.8
70°-80°	1.9	1.0
80°-90°	0.4	0.2
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	140.3	72.0
0°-40°	170.7	87.6
0°-60°	189.1	97.0
0°-90°	194.9	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	194.9	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	384	
5°	353	31
15°	206	58
25°	112	51
35°	48	30
45°	15	12
55°	6	6
65°	4	4
75°	2	2
85°	0	0
90°	0	



TEST NUMBER: P1246400

CATALOG NUMBER: P3AS09R159024DE010 E3DLP1GPH

CANDELA DISTRIBUTION (FULL):

0°	
0°	383.5
1°	382.5
2°	379.7
3°	374.0
4°	364.5
5°	353.1
6°	340.7
7°	326.2
8°	311.0
9°	295.4
10°	278.7
12.5°	240.3
15°	206.5
17.5°	177.3
20°	152.9
22.5°	131.4
25°	112.4
27.5°	94.0
30°	76.9
32.5°	61.4
35°	47.5
37.5°	36.4
40°	27.2
42.5°	20.3
45°	15.2
47.5°	11.7
50°	9.2
52.5°	7.6
55°	6.3
57.5°	5.4
60°	4.7
62.5°	4.1
65°	3.5
67.5°	3.2
70°	2.5
72.5°	2.2
75°	1.9
77.5°	1.3
80°	0.9
82.5°	0.6
85°	0.3
87.5°	0.3
90°	0.0

(END OF REPORT)