

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1246538

Luminaire Tested: P3AS09R409024DE010 E3DL1GPH

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1246538
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-23)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS09R409024DE010 E3DL1GPH
Description: 3in Adjustable LED luminaire with, R40 optic, 2400K CCT AND, 90CRI , E3DL1GPH TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 369.0 lumens
Efficiency: N/A
Efficacy: 33.2 lumens/watt
Spacing Criteria (0/90/45): 0.65 / 0.65 / 0.63
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 11.1
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1246538

CATALOG NUMBER: P3AS09R409024DE010 E3DL1GPH

Luminous Intensity Polar Plot



TEST NUMBER: P1246538

CATALOG NUMBER: P3AS09R409024DE010 E3DL1GPH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	114	111	109	107	112	109	107	105	105	104	102		102	100	99		98
2	109	105	101	98	107	103	100	97	100	97	95		97	95	93		94
3	104	99	94	91	102	97	93	90	95	91	88		92	89	87		90
4	100	93	88	85	98	92	88	84	90	86	83		88	85	82		86
5	96	88	83	79	94	88	83	79	86	82	78		84	81	78		83
6	92	84	79	75	91	83	78	75	82	77	74		81	77	74		79
7	88	80	75	71	87	79	74	71	78	74	71		77	73	70		76
8	85	76	71	68	84	76	71	67	75	70	67		74	70	67		73
9	82	73	68	64	81	73	68	64	72	67	64		71	67	64		70
10	78	70	65	62	78	70	65	61	69	64	61		68	64	61		67

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	163276
5°	158529
10°	143863
15°	118843
20°	85734
25°	53035
30°	28713
35°	14830
40°	8072
45°	4528
50°	2286
55°	1682
60°	1535
65°	1505
70°	1410
75°	1356
80°	1263
85°	755

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 4528 cd/sqm

TEST NUMBER: P1246538

CATALOG NUMBER: P3AS09R409024DE010 E3DL1GPH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	66.4	18.0
10°-20°	142.6	38.6
20°-30°	101.7	27.6
30°-40°	37.5	10.1
40°-50°	11.8	3.2
50°-60°	4.1	1.1
60°-70°	2.8	0.8
70°-80°	1.7	0.5
80°-90°	0.5	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	310.7	84.2
0°-40°	348.1	94.3
0°-60°	364.0	98.6
0°-90°	369.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	369.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	745	
5°	720	66
15°	524	143
25°	219	102
35°	55	37
45°	15	12
55°	4	4
65°	3	3
75°	2	2
85°	0	0
90°	0	

TEST NUMBER: P1246538

CATALOG NUMBER: P3AS09R409024DE010 E3DL1GPH

CANDELA DISTRIBUTION (FULL):

0°	
0°	744.6
2.5°	738.9
5°	720.2
7.5°	689.2
10°	646.1
12.5°	591.3
15°	523.5
17.5°	447.5
20°	367.4
22.5°	288.5
25°	219.2
27.5°	160.9
30°	113.4
32.5°	79.5
35°	55.4
37.5°	39.3
40°	28.2
42.5°	20.3
45°	14.6
47.5°	9.8
50°	6.7
52.5°	4.8
55°	4.4
57.5°	4.1
60°	3.5
62.5°	3.2
65°	2.9
67.5°	2.5
70°	2.2
72.5°	1.9
75°	1.6
77.5°	1.3
80°	1.0
82.5°	0.6
85°	0.3
87.5°	0.3
90°	0.0

(END OF REPORT)