

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1246656

Luminaire Tested: P3AS09R609024DE010 E3DLD1GPH

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1246656
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-38)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS09R609024DE010 E3DLD1GPH
Description: 3in Adjustable LED luminaire with, R60 optic, 2400K CCT AND, 90CRI , E3DLD1GPH TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 261.0 lumens
Efficiency: N/A
Efficacy: 23.5 lumens/watt
Spacing Criteria (0/90/45): 0.94 / 0.94 / 1
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 11.1
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1246656

CATALOG NUMBER: P3AS09R609024DE010 E3DLD1GPH

Luminous Intensity Polar Plot



TEST NUMBER: P1246656

CATALOG NUMBER: P3AS09R609024DE010 E3DLD1GPH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	112	109	106	103	110	107	104	101	102	100	98		99	97	95		95
2	105	99	94	90	103	97	93	89	94	90	87		91	88	85		88
3	99	91	85	80	96	89	84	79	87	82	78		84	80	77		82
4	92	83	77	72	90	82	76	71	80	75	70		78	73	70		76
5	87	77	70	65	85	76	69	65	74	68	64		72	67	63		71
6	82	71	64	59	80	70	64	59	69	63	58		67	62	58		66
7	77	66	59	54	75	65	59	54	64	58	54		63	57	53		61
8	72	61	55	50	71	61	54	50	60	54	49		59	53	49		58
9	68	57	51	46	67	57	50	46	56	50	46		55	49	46		54
10	65	54	47	43	64	53	47	43	52	47	43		52	46	42		51

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	46334
5°	45807
10°	44221
15°	41771
20°	38503
25°	34865
30°	30967
35°	26448
40°	21039
45°	14823
50°	8870
55°	4473
60°	4298
65°	3943
70°	3654
75°	3474
80°	3157
85°	2516

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 14823 cd/sqm

TEST NUMBER: P1246656

CATALOG NUMBER: P3AS09R609024DE010 E3DLD1GPH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	19.6	7.5
10°-20°	51.4	19.7
20°-30°	66.0	25.3
30°-40°	61.2	23.5
40°-50°	37.3	14.3
50°-60°	12.4	4.8
60°-70°	7.6	2.9
70°-80°	4.3	1.6
80°-90°	1.2	0.5
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	137.0	52.5
0°-40°	198.3	76.0
0°-60°	248.0	95.0
0°-90°	261.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	261.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	211	
5°	208	20
15°	184	51
25°	144	66
35°	99	61
45°	48	37
55°	12	12
65°	8	8
75°	4	4
85°	1	1
90°	0	

TEST NUMBER: P1246656

CATALOG NUMBER: P3AS09R609024DE010 E3DLD1GPH

CANDELA DISTRIBUTION (FULL):

0°	
0°	211.3
2.5°	210.3
5°	208.1
7.5°	204.0
10°	198.6
12.5°	192.0
15°	184.0
17.5°	174.9
20°	165.0
22.5°	154.6
25°	144.1
27.5°	133.4
30°	122.3
32.5°	111.2
35°	98.8
37.5°	85.8
40°	73.5
42.5°	60.5
45°	47.8
47.5°	37.1
50°	26.0
52.5°	15.5
55°	11.7
57.5°	10.8
60°	9.8
62.5°	8.6
65°	7.6
67.5°	6.7
70°	5.7
72.5°	4.8
75°	4.1
77.5°	3.2
80°	2.5
82.5°	1.6
85°	1.0
87.5°	0.6
90°	0.0

(END OF REPORT)