

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1247556

Luminaire Tested: P3AS20R209024D010 E3DL1LI

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1247556
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-7)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS20R209024D010 E3DL1LI
Description: 3in Adjustable LED luminaire with, R20 optic, 2400K CCT AND, 90CRI , E3DL1LI TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 1543.0 lumens
Efficiency: N/A
Efficacy: 53.6 lumens/watt
Spacing Criteria (0/90/45): 0.44 / 0.44 / 0.46
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 28.8
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1247556

CATALOG NUMBER: P3AS20R209024D010 E3DL1LI

Luminous Intensity Polar Plot



TEST NUMBER: P1247556

CATALOG NUMBER: P3AS20R209024D010 E3DL1LI

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	114	112	110	108	112	110	108	106	106	104	103		102	101	100		99
2	110	106	102	100	108	104	101	98	101	98	96		98	96	94		95
3	106	100	96	93	104	99	95	92	97	93	91		94	92	89		92
4	102	96	91	88	100	95	90	87	92	89	86		91	88	85		89
5	98	91	87	83	97	90	86	83	89	85	82		87	84	81		86
6	95	87	83	79	93	87	82	79	85	81	78		84	81	78		83
7	91	84	79	76	90	83	79	76	82	78	75		81	78	75		80
8	88	81	76	73	87	80	76	73	79	75	72		78	75	72		78
9	85	78	73	70	85	77	73	70	77	73	70		76	72	69		75
10	83	75	71	68	82	75	70	67	74	70	67		73	70	67		73

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	1187164
5°	1079152
10°	797558
15°	493374
20°	281751
25°	160848
30°	90216
35°	49068
40°	26879
45°	14792
50°	8631
55°	6270
60°	5877
65°	5396
70°	4809
75°	5083
80°	3788
85°	3774

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 14792 cd/sqm

TEST NUMBER: P1247556

CATALOG NUMBER: P3AS20R209024D010 E3DL1LI

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	424.5	27.5
10°-20°	606.1	39.3
20°-30°	316.3	20.5
30°-40°	122.3	7.9
40°-50°	39.7	2.6
50°-60°	15.6	1.0
60°-70°	10.3	0.7
70°-80°	6.1	0.4
80°-90°	2.0	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1346.9	87.3
0°-40°	1469.3	95.2
0°-60°	1524.6	98.8
0°-90°	1543.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1543.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	5414	
5°	4903	425
15°	2173	606
25°	665	316
35°	183	122
45°	48	40
55°	16	16
65°	10	10
75°	6	6
85°	2	2
90°	0	

TEST NUMBER: P1247556

CATALOG NUMBER: P3AS20R209024D010 E3DL1LI

CANDELA DISTRIBUTION (FULL):

0°	
0°	5413.9
1°	5403.5
2°	5339.4
3°	5241.0
4°	5088.9
5°	4902.6
6°	4682.0
7°	4437.5
8°	4154.3
9°	3878.6
10°	3581.9
12.5°	2847.1
15°	2173.3
17.5°	1626.3
20°	1207.4
22.5°	894.4
25°	664.8
27.5°	490.4
30°	356.3
32.5°	257.9
35°	183.3
37.5°	132.7
40°	93.9
42.5°	67.1
45°	47.7
47.5°	34.3
50°	25.3
52.5°	19.4
55°	16.4
57.5°	14.9
60°	13.4
62.5°	11.9
65°	10.4
67.5°	8.9
70°	7.5
72.5°	7.5
75°	6.0
77.5°	4.5
80°	3.0
82.5°	3.0
85°	1.5
87.5°	1.5
90°	0.0

(END OF REPORT)