

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1247993

Luminaire Tested: P3AS02R159027DE010 E3PHLP1MW

Issue Date: 1/29/2026

Test Information

Test Method: LM-79-2019
Report Number: P1247993
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2509-551-5)
Test Lab: INNOVATION CENTER
Issue Date: 1/29/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS02R159027DE010 E3PHLP1MW
Description: 3in Adjustable LED luminaire with, R15 optic, 2700K CCT AND, 90CRI , E3PHLP1MW TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 106.0 lumens
Efficiency: N/A
Efficacy: 29.5 lumens/watt
Spacing Criteria (0/90/45): 0.51 / 0.51 / 0.6
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 3.6
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1247993

CATALOG NUMBER: P3AS02R159027DE010 E3PHLP1MW

Luminous Intensity Polar Plot



TEST NUMBER: P1247993

CATALOG NUMBER: P3AS02R159027DE010 E3PHLP1MW

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	112	108	105	102	109	106	103	100	102	99	97		98	96	94		95
2	105	99	94	90	102	97	92	89	94	90	87		91	87	85		88
3	99	91	85	80	96	89	84	80	87	82	78		84	80	77		82
4	93	84	78	73	91	83	77	72	81	76	71		79	74	71		77
5	88	78	72	67	86	77	71	67	76	70	66		74	69	65		72
6	83	73	67	62	82	73	66	62	71	65	61		70	65	61		68
7	79	69	62	58	78	68	62	58	67	61	57		66	61	57		65
8	75	65	59	54	74	65	58	54	63	58	54		62	57	54		61
9	72	62	55	51	71	61	55	51	60	55	51		59	54	51		58
10	69	59	52	48	68	58	52	48	57	52	48		56	51	48		56

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	39668
5°	36430
10°	29035
15°	21703
20°	16475
25°	12485
30°	9217
35°	6585
40°	4523
45°	3163
50°	2695
55°	2638
60°	2719
65°	2906
70°	2949
75°	3050
80°	3283
85°	3271

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 82.5°

Luminance: 3864 cd/sqm

TEST NUMBER: P1247993

CATALOG NUMBER: P3AS02R159027DE010 E3PHLP1MW

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	14.7	13.8
10°-20°	26.8	25.3
20°-30°	23.7	22.4
30°-40°	15.5	14.7
40°-50°	8.3	7.9
50°-60°	6.3	5.9
60°-70°	5.4	5.1
70°-80°	3.7	3.5
80°-90°	1.5	1.4
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	65.2	61.5
0°-40°	80.8	76.2
0°-60°	95.4	90.0
0°-90°	106.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	106.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	181	
5°	166	15
15°	96	27
25°	52	24
35°	25	16
45°	10	8
55°	7	6
65°	6	5
75°	4	4
85°	1	2
90°	0	

TEST NUMBER: P1247993

CATALOG NUMBER: P3AS02R159027DE010 E3PHLP1MW

CANDELA DISTRIBUTION (FULL):

	0°
0°	180.9
2.5°	176.7
5°	165.5
7.5°	149.1
10°	130.4
12.5°	112.3
15°	95.6
17.5°	82.1
20°	70.6
22.5°	60.4
25°	51.6
27.5°	43.7
30°	36.4
32.5°	30.2
35°	24.6
37.5°	19.7
40°	15.8
42.5°	12.5
45°	10.2
47.5°	8.9
50°	7.9
52.5°	7.6
55°	6.9
57.5°	6.6
60°	6.2
62.5°	5.9
65°	5.6
67.5°	4.9
70°	4.6
72.5°	3.9
75°	3.6
77.5°	3.0
80°	2.6
82.5°	2.3
85°	1.3
87.5°	0.7
90°	0.0

(END OF REPORT)