

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1248426

Luminaire Tested: P3AS05R209027DE010 E3PHLP1MW

Issue Date: 1/29/2026

Test Information

Test Method: LM-79-2019
Report Number: P1248426
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2509-551-6)
Test Lab: INNOVATION CENTER
Issue Date: 1/29/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS05R209027DE010 E3PHLP1MW
Description: 3in Adjustable LED luminaire with, R20 optic, 2700K CCT AND, 90CRI , E3PHLP1MW TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 229.0 lumens
Efficiency: N/A
Efficacy: 31.8 lumens/watt
Spacing Criteria (0/90/45): 0.55 / 0.55 / 0.63
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 7.2
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1248426

CATALOG NUMBER: P3AS05R209027DE010 E3PHLP1MW

Luminous Intensity Polar Plot



TEST NUMBER: P1248426

CATALOG NUMBER: P3AS05R209027DE010 E3PHLP1MW

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	112	108	105	102	109	106	103	101	102	100	97		98	96	95		95
2	105	99	94	90	103	97	93	89	94	90	87		91	88	85		88
3	99	91	85	80	97	90	84	80	87	82	78		84	80	77		82
4	93	84	78	73	91	83	77	73	81	76	72		79	74	71		77
5	88	79	72	67	86	78	71	67	76	70	66		74	69	66		72
6	84	74	67	62	82	73	66	62	71	66	61		70	65	61		68
7	79	69	63	58	78	68	62	58	67	62	57		66	61	57		65
8	76	65	59	54	74	65	58	54	64	58	54		62	57	54		61
9	72	62	55	51	71	61	55	51	60	55	51		59	54	51		58
10	69	59	52	48	68	58	52	48	57	52	48		57	52	48		56

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	81441
5°	75963
10°	63036
15°	48196
20°	36170
25°	27244
30°	20130
35°	14081
40°	9647
45°	6698
50°	5731
55°	5658
60°	5921
65°	5967
70°	6027
75°	6270
80°	6819
85°	6793

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 82.5°

Luminance: 7896 cd/sqm

TEST NUMBER: P1248426

CATALOG NUMBER: P3AS05R209027DE010 E3PHLP1MW

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	30.9	13.5
10°-20°	59.0	25.8
20°-30°	51.9	22.7
30°-40°	33.5	14.6
40°-50°	17.8	7.8
50°-60°	13.4	5.8
60°-70°	11.4	5.0
70°-80°	8.0	3.5
80°-90°	3.1	1.4
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	141.9	62.0
0°-40°	175.4	76.6
0°-60°	206.6	90.2
0°-90°	229.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	229.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	371	
5°	345	31
15°	212	59
25°	113	52
35°	53	34
45°	22	18
55°	15	13
65°	12	11
75°	7	8
85°	3	3
90°	0	

TEST NUMBER: P1248426

CATALOG NUMBER: P3AS05R209027DE010 E3PHLP1MW

CANDELA DISTRIBUTION (FULL):

0°	
0°	371.4
2.5°	364.0
5°	345.1
7.5°	316.1
10°	283.1
12.5°	246.7
15°	212.3
17.5°	181.3
20°	155.0
22.5°	132.8
25°	112.6
27.5°	95.0
30°	79.5
32.5°	65.4
35°	52.6
37.5°	42.5
40°	33.7
42.5°	27.0
45°	21.6
47.5°	18.9
50°	16.8
52.5°	15.5
55°	14.8
57.5°	14.2
60°	13.5
62.5°	12.1
65°	11.5
67.5°	10.8
70°	9.4
72.5°	8.8
75°	7.4
77.5°	6.7
80°	5.4
82.5°	4.7
85°	2.7
87.5°	1.3
90°	0.0

(END OF REPORT)