

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1248970

Luminaire Tested: P3AS09R509027DE010 E3DLD1WH

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1248970
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-30)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS09R509027DE010 E3DLD1WH
Description: 3in Adjustable LED luminaire with, R50 optic, 2700K CCT AND, 90CRI , E3DLD1WH TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 599.0 lumens
Efficiency: N/A
Efficacy: 54.0 lumens/watt
Spacing Criteria (0/90/45): 0.88 / 0.88 / 0.93
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 11.1
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1248970

CATALOG NUMBER: P3AS09R509027DE010 E3DLD1WH

Luminous Intensity Polar Plot



TEST NUMBER: P1248970

CATALOG NUMBER: P3AS09R509027DE010 E3DLD1WH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	112	109	106	103	110	107	104	102	103	101	99		99	97	96		95
2	106	100	95	91	103	98	94	90	95	91	88		92	89	86		89
3	99	92	86	81	97	90	85	81	88	83	79		85	81	78		83
4	93	85	78	73	91	83	77	73	81	76	72		79	75	71		77
5	88	78	72	67	86	77	71	66	75	70	66		74	69	65		72
6	83	73	66	61	81	72	65	61	70	65	60		69	64	60		67
7	78	68	61	56	77	67	61	56	66	60	56		64	59	55		63
8	74	63	57	52	73	63	56	52	61	56	52		60	55	51		59
9	70	59	53	48	69	59	52	48	58	52	48		57	52	48		56
10	66	56	49	45	65	55	49	45	54	49	45		54	48	45		53

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	121723
5°	119942
10°	114627
15°	106153
20°	95395
25°	83860
30°	71327
35°	57822
40°	43453
45°	27972
50°	13304
55°	10437
60°	9911
65°	9236
70°	8335
75°	7540
80°	6945
85°	6793

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 27972 cd/sqm

TEST NUMBER: P1248970

CATALOG NUMBER: P3AS09R509027DE010 E3DLD1WH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	51.1	8.5
10°-20°	130.4	21.8
20°-30°	158.4	26.4
30°-40°	134.3	22.4
40°-50°	69.8	11.7
50°-60°	25.2	4.2
60°-70°	17.4	2.9
70°-80°	9.5	1.6
80°-90°	3.0	0.5
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	339.9	56.7
0°-40°	474.2	79.2
0°-60°	569.1	95.0
0°-90°	599.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	599.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	555	
5°	545	51
15°	468	130
25°	347	158
35°	216	134
45°	90	70
55°	27	25
65°	18	17
75°	9	9
85°	3	3
90°	0	

TEST NUMBER: P1248970

CATALOG NUMBER: P3AS09R509027DE010 E3DLD1WH

CANDELA DISTRIBUTION (FULL):

	0°
0°	555.1
2.5°	553.1
5°	544.9
7.5°	532.6
10°	514.8
12.5°	492.2
15°	467.6
17.5°	439.6
20°	408.8
22.5°	377.4
25°	346.6
27.5°	314.5
30°	281.7
32.5°	248.8
35°	216.0
37.5°	183.9
40°	151.8
42.5°	121.0
45°	90.2
47.5°	60.2
50°	39.0
52.5°	30.1
55°	27.3
57.5°	24.6
60°	22.6
62.5°	19.8
65°	17.8
67.5°	15.0
70°	13.0
72.5°	10.9
75°	8.9
77.5°	6.8
80°	5.5
82.5°	4.1
85°	2.7
87.5°	1.4
90°	0.0

(END OF REPORT)