

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1249075

Luminaire Tested: P3AS09R709027DE010 E3D1WMH

Issue Date: 1/29/2026

Test Information

Test Method: LM-79-2019
Report Number: P1249075
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2501-338-17)
Test Lab: INNOVATION CENTER
Issue Date: 1/29/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS09R709027DE010 E3D1WMH
Description: 3in Adjustable LED luminaire with, R70 optic, 2700K CCT AND, 90CRI , E3D1WMH TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 814.9 lumens
Efficiency: N/A
Efficacy: 73.4 lumens/watt
Spacing Criteria (0/90/45): 1.02 / 1.02 / 1.06
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 11.1
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1249075

CATALOG NUMBER: P3AS09R709027DE010 E3D1WMH

Luminous Intensity Polar Plot



TEST NUMBER: P1249075

CATALOG NUMBER: P3AS09R709027DE010 E3D1WMH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	110	108	105	111	108	106	104	104	102	100		100	99	97		97
2	107	102	98	94	105	100	96	93	97	94	91		94	91	89		91
3	101	94	89	85	99	93	88	84	90	86	83		88	84	81		86
4	95	87	81	77	94	86	81	77	84	79	76		82	78	75		80
5	90	81	75	70	88	80	74	70	78	73	69		77	72	69		75
6	85	75	69	64	83	75	69	64	73	68	64		72	67	63		70
7	80	70	64	59	79	70	63	59	68	63	59		67	62	58		66
8	76	66	59	55	75	65	59	55	64	58	54		63	58	54		62
9	72	61	55	51	71	61	55	51	60	54	50		59	54	50		58
10	68	58	51	47	67	57	51	47	56	51	47		55	50	47		55

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	158474
5°	149416
10°	141681
15°	139138
20°	134108
25°	126419
30°	125513
35°	109326
40°	70704
45°	33430
50°	4674
55°	382
60°	307
65°	363
70°	192
75°	254
80°	379
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 33430 cd/sqm

TEST NUMBER: P1249075

CATALOG NUMBER: P3AS09R709027DE010 E3D1WMH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	63.4	7.8
10°-20°	172.1	21.1
20°-30°	243.5	29.9
30°-40°	244.7	30.0
40°-50°	88.0	10.8
50°-60°	2.4	0.3
60°-70°	0.5	0.1
70°-80°	0.3	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	479.0	58.8
0°-40°	723.7	88.8
0°-60°	814.0	99.9
0°-90°	814.9	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	814.9	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	723	
5°	679	63
15°	613	172
25°	522	243
35°	408	245
45°	108	88
55°	1	2
65°	1	1
75°	0	0
85°	0	0
90°	0	

TEST NUMBER: P1249075

CATALOG NUMBER: P3AS09R709027DE010 E3D1WMH

CANDELA DISTRIBUTION (FULL):

0°	
0°	722.7
1°	720.7
2°	714.3
3°	704.3
4°	691.6
5°	678.8
6°	666.8
7°	657.4
8°	649.0
9°	642.4
10°	636.3
11°	631.3
12°	626.6
13°	621.9
14°	617.6
15°	612.9
16°	607.2
17°	601.2
18°	593.8
19°	584.8
20°	574.7
21°	563.7
22°	552.6
23°	541.9
24°	531.6
25°	522.5
26°	516.2
27°	511.1
28°	507.1
29°	502.4
30°	495.7
31°	486.0
32°	472.3
32.5°	464.6
33°	454.2
34°	433.8
35°	408.4
36°	380.3
37°	348.5
37.5°	333.7
38°	313.6
39°	277.8
40°	247.0
42.5°	171.0
45°	107.8

TEST NUMBER: P1249075

CATALOG NUMBER: P3AS09R709027DE010 E3D1WMH

CANDELA DISTRIBUTION (continued):

	0°
47.5°	57.9
50°	13.7
52.5°	1.7
55°	1.0
57.5°	1.0
60°	0.7
62.5°	0.7
65°	0.7
67.5°	0.3
70°	0.3
72.5°	0.3
75°	0.3
77.5°	0.3
80°	0.3
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)