

Scaled data based on original data using  
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-  
State Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1249521

Luminaire Tested: P3AS17R129027DE010 E3DLP1H

Issue Date: 1/30/2026

**Test Information**

Test Method: LM-79-2019  
Report Number: P1249521  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-1)  
Test Lab: INNOVATION CENTER  
Issue Date: 1/30/2026  
Manufacturer: COOPER LIGHTING SOLUTIONS  
Product Line: IRiS  
Catalog Number: P3AS17R129027DE010 E3DLP1H  
Description: 3in Adjustable LED luminaire with, R12 optic, 2700K CCT AND, 90CRI , E3DLP1H TRIM  
Light Source: -  
Ballast/Driver: -

**Summary**


Lumens per Lamp: N/A  
Luminaire Lumens: 625.0 lumens  
Efficiency: N/A  
Efficacy: 27.3 lumens/watt  
Spacing Criteria (0/90/45): 0.52 / 0.52 / 0.61  
Luminous Opening: Circular (Dia: 0.25' x H: 0')  
CIE Type: Direct

Input Watts (W): 22.9  
Input Voltage (V): NR  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 24 FT

TEST NUMBER: P1249521

CATALOG NUMBER: P3AS17R129027DE010 E3DLP1H

### Luminous Intensity Polar Plot



TEST NUMBER: P1249521

CATALOG NUMBER: P3AS17R129027DE010 E3DLP1H

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

|     |     |     |     |     |     |     |     |     |     |     |     |  |     |     |     |  |     |
|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|--|-----|-----|-----|--|-----|
| RF  | 20  |     |     |     | 20  |     |     |     | 20  |     |     |  | 20  |     |     |  | 20  |
| RC  | 80  |     |     |     | 70  |     |     |     | 50  |     |     |  | 30  |     |     |  | 10  |
| RW  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 50  | 30  | 10  |  | 50  | 30  | 10  |  | 50  |
| RCR |     |     |     |     |     |     |     |     |     |     |     |  |     |     |     |  |     |
| 0   | 119 | 119 | 119 | 119 | 116 | 116 | 116 | 116 | 111 | 111 | 111 |  | 106 | 106 | 106 |  | 102 |
| 1   | 113 | 110 | 108 | 106 | 111 | 108 | 106 | 104 | 104 | 102 | 101 |  | 100 | 99  | 98  |  | 97  |
| 2   | 108 | 103 | 98  | 95  | 105 | 101 | 97  | 94  | 98  | 95  | 92  |  | 95  | 92  | 90  |  | 92  |
| 3   | 102 | 96  | 91  | 87  | 100 | 94  | 90  | 86  | 92  | 88  | 85  |  | 89  | 86  | 83  |  | 87  |
| 4   | 97  | 90  | 84  | 80  | 95  | 88  | 83  | 79  | 86  | 82  | 78  |  | 84  | 81  | 78  |  | 82  |
| 5   | 93  | 84  | 78  | 74  | 91  | 83  | 78  | 74  | 81  | 77  | 73  |  | 80  | 76  | 72  |  | 78  |
| 6   | 88  | 79  | 73  | 69  | 87  | 79  | 73  | 69  | 77  | 72  | 69  |  | 76  | 71  | 68  |  | 74  |
| 7   | 84  | 75  | 69  | 65  | 83  | 74  | 69  | 65  | 73  | 68  | 64  |  | 72  | 67  | 64  |  | 71  |
| 8   | 80  | 71  | 65  | 61  | 79  | 71  | 65  | 61  | 69  | 64  | 61  |  | 68  | 64  | 61  |  | 67  |
| 9   | 77  | 68  | 62  | 58  | 76  | 67  | 62  | 58  | 66  | 61  | 58  |  | 65  | 61  | 57  |  | 64  |
| 10  | 74  | 64  | 59  | 55  | 73  | 64  | 59  | 55  | 63  | 58  | 55  |  | 62  | 58  | 55  |  | 62  |

**AVERAGE LUMINANCE (cd/sqm):**

|     |        |
|-----|--------|
|     | 0°     |
| 0°  | 269518 |
| 5°  | 249086 |
| 10° | 198861 |
| 15° | 150217 |
| 20° | 114390 |
| 25° | 87174  |
| 30° | 62440  |
| 35° | 40743  |
| 40° | 24990  |
| 45° | 15102  |
| 50° | 10030  |
| 55° | 7761   |
| 60° | 6666   |
| 65° | 5811   |
| 70° | 5193   |
| 75° | 5168   |
| 80° | 3788   |
| 85° | 2516   |

**MAXIMUM LUMINANCE 45°-90°:**

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 15102 cd/sqm

TEST NUMBER: P1249521

CATALOG NUMBER: P3AS17R129027DE010 E3DLP1H

**ZONAL LUMENS:**

| Zone      | Lumens | % Fixture |
|-----------|--------|-----------|
| 0°-10°    | 100.2  | 16.0      |
| 10°-20°   | 185.0  | 29.6      |
| 20°-30°   | 164.7  | 26.3      |
| 30°-40°   | 97.4   | 15.6      |
| 40°-50°   | 40.0   | 6.4       |
| 50°-60°   | 18.8   | 3.0       |
| 60°-70°   | 11.4   | 1.8       |
| 70°-80°   | 6.0    | 1.0       |
| 80°-90°   | 1.5    | 0.2       |
| 90°-100°  | 0.0    | 0.0       |
| 100°-110° | 0.0    | 0.0       |
| 110°-120° | 0.0    | 0.0       |
| 120°-130° | 0.0    | 0.0       |
| 130°-140° | 0.0    | 0.0       |
| 140°-150° | 0.0    | 0.0       |
| 150°-160° | 0.0    | 0.0       |
| 160°-170° | 0.0    | 0.0       |
| 170°-180° | 0.0    | 0.0       |
| <hr/>     |        |           |
| 0°-30°    | 449.9  | 72.0      |
| 0°-40°    | 547.3  | 87.6      |
| 0°-60°    | 606.1  | 97.0      |
| 0°-90°    | 625.0  | 100.0     |
| 90°-120°  | 0.0    | 0.0       |
| 90°-150°  | 0.0    | 0.0       |
| 90°-180°  | 0.0    | 0.0       |
| 0°-180°   | 625.0  | 100.0     |

**CANDELA DISTRIBUTION:**

|     | 0°   | Flux |
|-----|------|------|
| 0°  | 1229 |      |
| 5°  | 1132 | 100  |
| 15° | 662  | 185  |
| 25° | 360  | 165  |
| 35° | 152  | 97   |
| 45° | 49   | 40   |
| 55° | 20   | 19   |
| 65° | 11   | 11   |
| 75° | 6    | 6    |
| 85° | 1    | 1    |
| 90° | 0    |      |

TEST NUMBER: P1249521

CATALOG NUMBER: P3AS17R129027DE010 E3DLP1H

**CANDELA DISTRIBUTION (FULL):**

| 0°    |        |
|-------|--------|
| 0°    | 1229.1 |
| 1°    | 1226.0 |
| 2°    | 1216.9 |
| 3°    | 1198.6 |
| 4°    | 1168.2 |
| 5°    | 1131.6 |
| 6°    | 1092.1 |
| 7°    | 1045.4 |
| 8°    | 996.7  |
| 9°    | 946.9  |
| 10°   | 893.1  |
| 12.5° | 770.3  |
| 15°   | 661.7  |
| 17.5° | 568.4  |
| 20°   | 490.2  |
| 22.5° | 421.2  |
| 25°   | 360.3  |
| 27.5° | 301.4  |
| 30°   | 246.6  |
| 32.5° | 196.9  |
| 35°   | 152.2  |
| 37.5° | 116.7  |
| 40°   | 87.3   |
| 42.5° | 65.0   |
| 45°   | 48.7   |
| 47.5° | 37.6   |
| 50°   | 29.4   |
| 52.5° | 24.4   |
| 55°   | 20.3   |
| 57.5° | 17.3   |
| 60°   | 15.2   |
| 62.5° | 13.2   |
| 65°   | 11.2   |
| 67.5° | 10.1   |
| 70°   | 8.1    |
| 72.5° | 7.1    |
| 75°   | 6.1    |
| 77.5° | 4.1    |
| 80°   | 3.0    |
| 82.5° | 2.0    |
| 85°   | 1.0    |
| 87.5° | 1.0    |
| 90°   | 0.0    |

(END OF REPORT)