

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1249551

Luminaire Tested: P3AS17R159027DE010 E3DLP1GPH

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1249551
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-1)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS17R159027DE010 E3DLP1GPH
Description: 3in Adjustable LED luminaire with, R15 optic, 2700K CCT AND, 90CRI , E3DLP1GPH TRIM
Light Source: -
Ballast/Driver: -


Summary

Lumens per Lamp: N/A
Luminaire Lumens: 363.0 lumens
Efficiency: N/A
Efficacy: 17.1 lumens/watt
Spacing Criteria (0/90/45): 0.52 / 0.52 / 0.61
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 21.2
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1249551
CATALOG NUMBER: P3AS17R159027DE010 E3DLP1GPH

Luminous Intensity Polar Plot





TEST NUMBER: P1249551
 CATALOG NUMBER: P3AS17R159027DE010 E3DLP1GPH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

| | | | | | | | | | | | | | | | | | | | | | |
|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| RF | 20 | | | | 20 | | | | 20 | | | | 20 | | | | 20 | | | | 20 |
| RC | 80 | | | | 70 | | | | 50 | | | | 30 | | | | 10 | | | | 0 |
| RW | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 50 | 30 | 10 | 50 | 30 | 10 | 50 | 30 | 10 | 50 | 30 | 10 | 0 |
| RCR | | | | | | | | | | | | | | | | | | | | | |
| 0 | 119 | 119 | 119 | 119 | 116 | 116 | 116 | 116 | 111 | 111 | 111 | 106 | 106 | 106 | 102 | 102 | 102 | 100 | 100 | 100 | 100 |
| 1 | 113 | 110 | 108 | 106 | 111 | 108 | 106 | 104 | 104 | 102 | 101 | 100 | 99 | 98 | 97 | 96 | 95 | 93 | 93 | 93 | 93 |
| 2 | 108 | 103 | 98 | 95 | 105 | 101 | 97 | 94 | 98 | 95 | 92 | 95 | 92 | 90 | 92 | 90 | 88 | 86 | 86 | 86 | 86 |
| 3 | 102 | 96 | 91 | 87 | 100 | 94 | 90 | 86 | 92 | 88 | 85 | 89 | 86 | 83 | 87 | 84 | 82 | 80 | 80 | 80 | 80 |
| 4 | 97 | 90 | 84 | 80 | 95 | 88 | 83 | 79 | 86 | 82 | 78 | 84 | 81 | 78 | 82 | 79 | 77 | 75 | 75 | 75 | 75 |
| 5 | 93 | 84 | 78 | 74 | 91 | 83 | 78 | 74 | 81 | 77 | 73 | 80 | 76 | 72 | 78 | 75 | 72 | 70 | 70 | 70 | 70 |
| 6 | 88 | 79 | 73 | 69 | 87 | 79 | 73 | 69 | 77 | 72 | 69 | 76 | 71 | 68 | 74 | 71 | 68 | 66 | 66 | 66 | 66 |
| 7 | 84 | 75 | 69 | 65 | 83 | 74 | 69 | 65 | 73 | 68 | 64 | 72 | 67 | 64 | 71 | 67 | 64 | 62 | 62 | 62 | 62 |
| 8 | 80 | 71 | 65 | 61 | 79 | 71 | 65 | 61 | 69 | 64 | 61 | 68 | 64 | 61 | 67 | 63 | 60 | 59 | 59 | 59 | 59 |
| 9 | 77 | 68 | 62 | 58 | 76 | 67 | 62 | 58 | 66 | 61 | 58 | 65 | 61 | 57 | 64 | 60 | 57 | 56 | 56 | 56 | 56 |
| 10 | 74 | 64 | 59 | 55 | 73 | 64 | 59 | 55 | 63 | 58 | 55 | 62 | 58 | 55 | 62 | 57 | 54 | 53 | 53 | 53 | 53 |

AVERAGE LUMINANCE (cd/sqm):

| | |
|-----|--------|
| | 0° |
| 0° | 156544 |
| 5° | 144684 |
| 10° | 115496 |
| 15° | 87242 |
| 20° | 66436 |
| 25° | 50640 |
| 30° | 36259 |
| 35° | 23664 |
| 40° | 14513 |
| 45° | 8776 |
| 50° | 5833 |
| 55° | 4511 |
| 60° | 3859 |
| 65° | 3373 |
| 70° | 3013 |
| 75° | 2965 |
| 80° | 2273 |
| 85° | 1510 |

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 8776 cd/sqm



TEST NUMBER: P1249551
 CATALOG NUMBER: P3AS17R159027DE010 E3DLP1GPH

ZONAL LUMENS:

| Zone | Lumens | % Fixture |
|-----------|--------|-----------|
| 0°-10° | 58.2 | 16.0 |
| 10°-20° | 107.4 | 29.6 |
| 20°-30° | 95.6 | 26.3 |
| 30°-40° | 56.6 | 15.6 |
| 40°-50° | 23.2 | 6.4 |
| 50°-60° | 10.9 | 3.0 |
| 60°-70° | 6.6 | 1.8 |
| 70°-80° | 3.5 | 1.0 |
| 80°-90° | 0.9 | 0.2 |
| 90°-100° | 0.0 | 0.0 |
| 100°-110° | 0.0 | 0.0 |
| 110°-120° | 0.0 | 0.0 |
| 120°-130° | 0.0 | 0.0 |
| 130°-140° | 0.0 | 0.0 |
| 140°-150° | 0.0 | 0.0 |
| 150°-160° | 0.0 | 0.0 |
| 160°-170° | 0.0 | 0.0 |
| 170°-180° | 0.0 | 0.0 |
| 0°-30° | 261.3 | 72.0 |
| 0°-40° | 317.9 | 87.6 |
| 0°-60° | 352.0 | 97.0 |
| 0°-90° | 363.0 | 100.0 |
| 90°-120° | 0.0 | 0.0 |
| 90°-150° | 0.0 | 0.0 |
| 90°-180° | 0.0 | 0.0 |
| 0°-180° | 363.0 | 100.0 |

CANDELA DISTRIBUTION:

| | 0° | Flux |
|-----|-----|------|
| 0° | 714 | |
| 5° | 657 | 58 |
| 15° | 384 | 107 |
| 25° | 209 | 96 |
| 35° | 88 | 57 |
| 45° | 28 | 23 |
| 55° | 12 | 11 |
| 65° | 6 | 7 |
| 75° | 4 | 3 |
| 85° | 1 | 1 |
| 90° | 0 | |



TEST NUMBER: P1249551
CATALOG NUMBER: P3AS17R159027DE010 E3DLP1GPH

CANDELA DISTRIBUTION (FULL):

| 0° | |
|-------|-------|
| 0° | 713.9 |
| 1° | 712.1 |
| 2° | 706.8 |
| 3° | 696.2 |
| 4° | 678.5 |
| 5° | 657.3 |
| 6° | 634.3 |
| 7° | 607.2 |
| 8° | 578.9 |
| 9° | 550.0 |
| 10° | 518.7 |
| 12.5° | 447.4 |
| 15° | 384.3 |
| 17.5° | 330.1 |
| 20° | 284.7 |
| 22.5° | 244.6 |
| 25° | 209.3 |
| 27.5° | 175.1 |
| 30° | 143.2 |
| 32.5° | 114.4 |
| 35° | 88.4 |
| 37.5° | 67.8 |
| 40° | 50.7 |
| 42.5° | 37.7 |
| 45° | 28.3 |
| 47.5° | 21.8 |
| 50° | 17.1 |
| 52.5° | 14.1 |
| 55° | 11.8 |
| 57.5° | 10.0 |
| 60° | 8.8 |
| 62.5° | 7.7 |
| 65° | 6.5 |
| 67.5° | 5.9 |
| 70° | 4.7 |
| 72.5° | 4.1 |
| 75° | 3.5 |
| 77.5° | 2.4 |
| 80° | 1.8 |
| 82.5° | 1.2 |
| 85° | 0.6 |
| 87.5° | 0.6 |
| 90° | 0.0 |

(END OF REPORT)