

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1249828

Luminaire Tested: P3AS17R659027DE010 E3D1WH

Issue Date: 1/29/2026

Test Information

Test Method: LM-79-2019
Report Number: P1249828
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2501-338-16)
Test Lab: INNOVATION CENTER
Issue Date: 1/29/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS17R659027DE010 E3D1WH
Description: 3in Adjustable LED luminaire with, R65 optic, 2700K CCT AND, 90CRI , E3D1WH TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 1434.0 lumens
Efficiency: N/A
Efficacy: 67.6 lumens/watt
Spacing Criteria (0/90/45): 0.92 / 0.92 / 0.88
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 21.2
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1249828

CATALOG NUMBER: P3AS17R659027DE010 E3D1WH

Luminous Intensity Polar Plot



TEST NUMBER: P1249828

CATALOG NUMBER: P3AS17R659027DE010 E3D1WH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	114	111	109	106	111	109	107	105	105	103	102		101	100	99		98
2	108	104	100	96	106	102	98	95	99	96	93		96	93	91		93
3	103	97	92	88	101	95	91	88	93	89	86		90	87	85		88
4	98	91	85	81	96	90	85	81	87	83	80		85	82	79		84
5	93	85	79	75	92	84	79	75	82	78	74		81	77	74		79
6	89	80	74	70	87	79	74	70	78	73	69		76	72	69		75
7	84	75	70	65	83	75	69	65	73	69	65		72	68	65		71
8	80	71	65	61	79	71	65	61	69	64	61		68	64	61		67
9	77	67	61	58	76	67	61	57	66	61	57		65	60	57		64
10	73	64	58	54	72	63	58	54	62	57	54		62	57	54		61

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	384246
5°	356790
10°	345039
15°	332510
20°	307397
25°	280081
30°	216388
35°	125441
40°	49779
45°	21212
50°	5015
55°	688
60°	526
65°	311
70°	385
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 21212 cd/sqm

TEST NUMBER: P1249828

CATALOG NUMBER: P3AS17R659027DE010 E3D1WH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	152.9	10.7
10°-20°	408.1	28.5
20°-30°	516.5	36.0
30°-40°	294.1	20.5
40°-50°	58.5	4.1
50°-60°	3.0	0.2
60°-70°	0.8	0.1
70°-80°	0.1	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1077.5	75.1
0°-40°	1371.7	95.7
0°-60°	1433.1	99.9
0°-90°	1434.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1434.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1752	
5°	1621	153
15°	1465	408
25°	1158	517
35°	469	294
45°	68	58
55°	2	3
65°	1	1
75°	0	0
85°	0	0
90°	0	

TEST NUMBER: P1249828

CATALOG NUMBER: P3AS17R659027DE010 E3D1WH

CANDELA DISTRIBUTION (FULL):

0°	
0°	1752.3
1°	1739.4
2°	1711.1
3°	1678.1
4°	1645.6
5°	1620.9
6°	1602.6
7°	1587.9
8°	1574.9
9°	1561.9
10°	1549.6
11°	1536.0
12°	1521.9
13°	1504.8
14°	1486.5
15°	1464.7
16°	1438.8
17°	1410.5
18°	1379.8
19°	1347.4
20°	1317.3
21°	1286.7
22°	1259.0
23°	1230.1
24°	1196.5
25°	1157.6
26°	1111.0
27°	1055.0
28°	992.0
29°	924.8
30°	854.6
31°	777.4
32°	700.8
32.5°	661.3
33°	623.0
34°	545.2
35°	468.6
36°	397.9
37°	327.7
37.5°	291.8
38°	262.9
39°	212.8
40°	173.9
42.5°	107.3
45°	68.4



TEST NUMBER: P1249828

CATALOG NUMBER: P3AS17R659027DE010 E3D1WH

CANDELA DISTRIBUTION (continued):

	0°
47.5°	40.1
50°	14.7
52.5°	2.9
55°	1.8
57.5°	1.2
60°	1.2
62.5°	1.2
65°	0.6
67.5°	0.6
70°	0.6
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)