

Scaled data based on original data using  
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-  
State Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1250258

Luminaire Tested: P3AS24R209027D010 E3D1MW

Issue Date: 1/30/2026

**Test Information**

Test Method: LM-79-2019  
Report Number: P1250258  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-8)  
Test Lab: INNOVATION CENTER  
Issue Date: 1/30/2026  
Manufacturer: COOPER LIGHTING SOLUTIONS  
Product Line: IRiS  
Catalog Number: P3AS24R209027D010 E3D1MW  
Description: 3in Adjustable LED luminaire with, R20 optic, 2700K CCT AND, 90CRI , E3D1MW TRIM  
Light Source: -  
Ballast/Driver: -

**Summary**


Lumens per Lamp: N/A  
Luminaire Lumens: 2283.0 lumens  
Efficiency: N/A  
Efficacy: 79.3 lumens/watt  
Spacing Criteria (0/90/45): 0.35 / 0.35 / 0.34  
Luminous Opening: Circular (Dia: 0.25' x H: 0')  
CIE Type: Direct

Input Watts (W): 28.8  
Input Voltage (V): NR  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 24 FT

TEST NUMBER: P1250258

CATALOG NUMBER: P3AS24R209027D010 E3D1MW

### Luminous Intensity Polar Plot



TEST NUMBER: P1250258

CATALOG NUMBER: P3AS24R209027D010 E3D1MW

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

|     |     |     |     |     |     |     |     |     |     |     |     |  |     |     |     |  |     |
|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|--|-----|-----|-----|--|-----|
| RF  | 20  |     |     |     | 20  |     |     |     | 20  |     |     |  | 20  |     |     |  | 20  |
| RC  | 80  |     |     |     | 70  |     |     |     | 50  |     |     |  | 30  |     |     |  | 10  |
| RW  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 50  | 30  | 10  |  | 50  | 30  | 10  |  | 50  |
| RCR |     |     |     |     |     |     |     |     |     |     |     |  |     |     |     |  |     |
| 0   | 119 | 119 | 119 | 119 | 116 | 116 | 116 | 116 | 111 | 111 | 111 |  | 106 | 106 | 106 |  | 102 |
| 1   | 116 | 114 | 112 | 110 | 113 | 112 | 110 | 109 | 108 | 106 | 105 |  | 104 | 103 | 102 |  | 101 |
| 2   | 112 | 109 | 107 | 104 | 110 | 108 | 105 | 103 | 104 | 103 | 101 |  | 102 | 100 | 99  |  | 99  |
| 3   | 109 | 105 | 102 | 100 | 108 | 104 | 101 | 99  | 102 | 99  | 97  |  | 99  | 98  | 96  |  | 97  |
| 4   | 107 | 102 | 99  | 96  | 105 | 101 | 98  | 96  | 99  | 97  | 95  |  | 97  | 95  | 93  |  | 96  |
| 5   | 104 | 99  | 96  | 93  | 103 | 98  | 95  | 93  | 97  | 94  | 92  |  | 95  | 93  | 91  |  | 94  |
| 6   | 102 | 97  | 93  | 91  | 101 | 96  | 93  | 90  | 95  | 92  | 90  |  | 94  | 91  | 89  |  | 93  |
| 7   | 100 | 94  | 91  | 88  | 99  | 94  | 91  | 88  | 93  | 90  | 88  |  | 92  | 89  | 87  |  | 91  |
| 8   | 98  | 92  | 89  | 86  | 97  | 92  | 89  | 86  | 91  | 88  | 86  |  | 90  | 88  | 86  |  | 89  |
| 9   | 96  | 90  | 87  | 85  | 95  | 90  | 87  | 85  | 89  | 86  | 84  |  | 89  | 86  | 84  |  | 88  |
| 10  | 94  | 89  | 85  | 83  | 93  | 88  | 85  | 83  | 88  | 85  | 83  |  | 87  | 84  | 83  |  | 87  |

**AVERAGE LUMINANCE (cd/sqm):**

|     |         |
|-----|---------|
|     | 0°      |
| 0°  | 3545769 |
| 5°  | 3077606 |
| 10° | 1901635 |
| 15° | 660481  |
| 20° | 202831  |
| 25° | 71714   |
| 30° | 26536   |
| 35° | 10654   |
| 40° | 5696    |
| 45° | 2233    |
| 50° | 1228    |
| 55° | 1376    |
| 60° | 1579    |
| 65° | 934     |
| 70° | 1154    |
| 75° | 1525    |
| 80° | 0       |
| 85° | 0       |

**MAXIMUM LUMINANCE 45°-90°:**

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 2233 cd/sqm

TEST NUMBER: P1250258

CATALOG NUMBER: P3AS24R209027D010 E3D1MW

**ZONAL LUMENS:**

| Zone      | Lumens | % Fixture |
|-----------|--------|-----------|
| 0°-10°    | 1160.4 | 50.8      |
| 10°-20°   | 920.7  | 40.3      |
| 20°-30°   | 159.4  | 7.0       |
| 30°-40°   | 29.0   | 1.3       |
| 40°-50°   | 6.6    | 0.3       |
| 50°-60°   | 3.2    | 0.1       |
| 60°-70°   | 2.0    | 0.1       |
| 70°-80°   | 1.7    | 0.1       |
| 80°-90°   | 0.0    | 0.0       |
| 90°-100°  | 0.0    | 0.0       |
| 100°-110° | 0.0    | 0.0       |
| 110°-120° | 0.0    | 0.0       |
| 120°-130° | 0.0    | 0.0       |
| 130°-140° | 0.0    | 0.0       |
| 140°-150° | 0.0    | 0.0       |
| 150°-160° | 0.0    | 0.0       |
| 160°-170° | 0.0    | 0.0       |
| 170°-180° | 0.0    | 0.0       |
| <hr/>     |        |           |
| 0°-30°    | 2240.5 | 98.1      |
| 0°-40°    | 2269.4 | 99.4      |
| 0°-60°    | 2279.3 | 99.8      |
| 0°-90°    | 2283.0 | 100.0     |
| 90°-120°  | 0.0    | 0.0       |
| 90°-150°  | 0.0    | 0.0       |
| 90°-180°  | 0.0    | 0.0       |
| 0°-180°   | 2283.0 | 100.0     |

**CANDELA DISTRIBUTION:**

|     | 0°    | Flux |
|-----|-------|------|
| 0°  | 16170 |      |
| 5°  | 13982 | ###  |
| 15° | 2909  | 921  |
| 25° | 296   | 159  |
| 35° | 40    | 29   |
| 45° | 7     | 7    |
| 55° | 4     | 3    |
| 65° | 2     | 2    |
| 75° | 2     | 2    |
| 85° | 0     | 0    |
| 90° | 0     |      |



TEST NUMBER: P1250258

CATALOG NUMBER: P3AS24R209027D010 E3D1MW

**CANDELA DISTRIBUTION (FULL):**

| 0°    |         |
|-------|---------|
| 0°    | 16170.0 |
| 1°    | 16092.3 |
| 2°    | 15785.0 |
| 3°    | 15291.7 |
| 4°    | 14713.4 |
| 5°    | 13981.6 |
| 6°    | 13143.1 |
| 7°    | 12167.2 |
| 8°    | 11055.9 |
| 9°    | 9807.1  |
| 10°   | 8540.4  |
| 12.5° | 5387.0  |
| 15°   | 2909.4  |
| 17.5° | 1554.1  |
| 20°   | 869.2   |
| 22.5° | 497.0   |
| 25°   | 296.4   |
| 27.5° | 180.7   |
| 30°   | 104.8   |
| 32.5° | 61.4    |
| 35°   | 39.8    |
| 37.5° | 27.1    |
| 40°   | 19.9    |
| 42.5° | 12.6    |
| 45°   | 7.2     |
| 47.5° | 3.6     |
| 50°   | 3.6     |
| 52.5° | 3.6     |
| 55°   | 3.6     |
| 57.5° | 3.6     |
| 60°   | 3.6     |
| 62.5° | 1.8     |
| 65°   | 1.8     |
| 67.5° | 1.8     |
| 70°   | 1.8     |
| 72.5° | 1.8     |
| 75°   | 1.8     |
| 77.5° | 1.8     |
| 80°   | 0.0     |
| 82.5° | 0.0     |
| 85°   | 0.0     |
| 87.5° | 0.0     |
| 90°   | 0.0     |

(END OF REPORT)