

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1250375

Luminaire Tested: P3AS24R409027D010 E3D1LI

Issue Date: 1/29/2026

Test Information

Test Method: LM-79-2019
Report Number: P1250375
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2501-338-12)
Test Lab: INNOVATION CENTER
Issue Date: 1/29/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS24R409027D010 E3D1LI
Description: 3in Adjustable LED luminaire with, R40 optic, 2700K CCT AND, 90CRI , E3D1LI TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 2531.0 lumens
Efficiency: N/A
Efficacy: 87.9 lumens/watt
Spacing Criteria (0/90/45): 0.7 / 0.7 / 0.6
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 28.8
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1250375

CATALOG NUMBER: P3AS24R409027D010 E3D1LI

Luminous Intensity Polar Plot



TEST NUMBER: P1250375

CATALOG NUMBER: P3AS24R409027D010 E3D1LI

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	115	112	110	109	112	110	109	107	106	105	104		103	102	101		99
2	111	107	104	101	109	105	102	100	102	100	98		99	97	96		96
3	107	102	98	95	105	100	97	94	98	95	93		96	93	91		93
4	103	97	93	90	101	96	92	89	94	91	88		92	89	87		90
5	99	93	89	85	98	92	88	85	91	87	84		89	86	84		88
6	96	89	85	81	95	89	84	81	87	83	81		86	83	80		85
7	93	86	81	78	92	85	81	78	84	80	77		83	80	77		82
8	90	83	78	75	89	82	78	75	81	77	75		80	77	74		79
9	87	80	75	72	86	79	75	72	78	75	72		78	74	72		77
10	84	77	72	70	83	77	72	69	76	72	69		75	72	69		74

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	1290116
5°	1280802
10°	1247271
15°	1114149
20°	738774
25°	276766
30°	74037
35°	28938
40°	10391
45°	4931
50°	1501
55°	688
60°	395
65°	467
70°	0
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 4931 cd/sqm

TEST NUMBER: P1250375

CATALOG NUMBER: P3AS24R409027D010 E3D1LI

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	549.1	21.7
10°-20°	1300.4	51.4
20°-30°	589.7	23.3
30°-40°	76.4	3.0
40°-50°	13.2	0.5
50°-60°	1.6	0.1
60°-70°	0.6	0.0
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2439.2	96.4
0°-40°	2515.7	99.4
0°-60°	2530.5	100.0
0°-90°	2531.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2531.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	5883	
5°	5819	549
15°	4908	1300
25°	1144	590
35°	108	76
45°	16	13
55°	2	2
65°	1	1
75°	0	0
85°	0	0
90°	0	

TEST NUMBER: P1250375

CATALOG NUMBER: P3AS24R409027D010 E3D1LI

CANDELA DISTRIBUTION (FULL):

0°	
0°	5883.4
1°	5879.8
2°	5871.0
3°	5857.7
4°	5840.8
5°	5818.7
6°	5793.0
7°	5761.1
8°	5722.1
9°	5668.9
10°	5601.6
11°	5522.7
12°	5417.3
13°	5287.1
14°	5116.9
15°	4907.8
16°	4641.1
17°	4337.2
18°	3972.2
19°	3586.7
20°	3165.9
21°	2745.0
22°	2330.3
23°	1917.4
24°	1511.6
25°	1143.9
26°	847.1
27°	620.2
28°	466.1
29°	362.4
30°	292.4
31°	241.9
32°	202.0
32.5°	184.3
33°	166.6
34°	135.6
35°	108.1
36°	85.1
37°	67.3
37.5°	60.3
38°	53.2
39°	44.3
40°	36.3
42.5°	23.9
45°	15.9



TEST NUMBER: P1250375
CATALOG NUMBER: P3AS24R409027D010 E3D1LI

CANDELA DISTRIBUTION (continued):

	0°
47.5°	9.7
50°	4.4
52.5°	1.8
55°	1.8
57.5°	0.9
60°	0.9
62.5°	0.9
65°	0.9
67.5°	0.0
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)