

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1250489

Luminaire Tested: P3AS24R609027D010 E3D1WH

Issue Date: 1/29/2026

Test Information

Test Method: LM-79-2019
Report Number: P1250489
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2501-338-15)
Test Lab: INNOVATION CENTER
Issue Date: 1/29/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS24R609027D010 E3D1WH
Description: 3in Adjustable LED luminaire with, R60 optic, 2700K CCT AND, 90CRI , E3D1WH TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 2166.0 lumens
Efficiency: N/A
Efficacy: 75.2 lumens/watt
Spacing Criteria (0/90/45): 0.94 / 0.94 / 0.88
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 28.8
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1250489

CATALOG NUMBER: P3AS24R609027D010 E3D1WH

Luminous Intensity Polar Plot



TEST NUMBER: P1250489

CATALOG NUMBER: P3AS24R609027D010 E3D1WH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	114	111	109	106	111	109	107	105	105	103	102		101	100	99		98
2	108	104	100	96	106	102	98	95	99	96	93		96	93	91		93
3	103	97	92	88	101	96	91	88	93	89	86		91	87	85		88
4	98	91	85	81	96	90	85	81	88	83	80		86	82	79		84
5	93	85	80	75	92	84	79	75	83	78	74		81	77	74		79
6	89	80	74	70	87	79	74	70	78	73	70		77	72	69		75
7	85	76	70	66	83	75	69	65	74	69	65		72	68	65		71
8	81	71	65	61	79	71	65	61	70	65	61		69	64	61		68
9	77	67	62	58	76	67	61	58	66	61	57		65	61	57		64
10	73	64	58	54	72	63	58	54	63	58	54		62	57	54		61

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	567520
5°	535746
10°	521834
15°	509901
20°	474105
25°	423823
30°	323721
35°	186903
40°	72536
45°	30236
50°	6652
55°	1032
60°	789
65°	467
70°	577
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 30236 cd/sqm

TEST NUMBER: P1250489

CATALOG NUMBER: P3AS24R609027D010 E3D1WH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	229.8	10.6
10°-20°	625.7	28.9
20°-30°	783.6	36.2
30°-40°	438.1	20.2
40°-50°	83.3	3.8
50°-60°	4.3	0.2
60°-70°	1.0	0.0
70°-80°	0.4	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1639.1	75.7
0°-40°	2077.1	95.9
0°-60°	2164.7	99.9
0°-90°	2166.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2166.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2588	
5°	2434	230
15°	2246	626
25°	1752	784
35°	698	438
45°	98	83
55°	3	4
65°	1	1
75°	0	0
85°	0	0
90°	0	

TEST NUMBER: P1250489

CATALOG NUMBER: P3AS24R609027D010 E3D1WH

CANDELA DISTRIBUTION (FULL):

0°	
0°	2588.1
1°	2577.5
2°	2543.8
3°	2503.9
4°	2466.7
5°	2433.9
6°	2409.1
7°	2387.9
8°	2371.9
9°	2356.9
10°	2343.6
11°	2330.3
12°	2315.2
13°	2296.6
14°	2274.5
15°	2246.1
16°	2211.5
17°	2172.6
18°	2128.3
19°	2077.8
20°	2031.7
21°	1982.1
22°	1930.7
23°	1876.6
24°	1817.3
25°	1751.7
26°	1674.6
27°	1588.7
28°	1492.1
29°	1389.3
30°	1278.5
31°	1166.9
32°	1051.7
32.5°	988.8
33°	932.1
34°	814.3
35°	698.2
36°	593.6
37°	482.9
37.5°	432.4
38°	382.8
39°	308.3
40°	253.4
42.5°	154.2
45°	97.5



TEST NUMBER: P1250489

CATALOG NUMBER: P3AS24R609027D010 E3D1WH

CANDELA DISTRIBUTION (continued):

	0°
47.5°	54.0
50°	19.5
52.5°	4.4
55°	2.7
57.5°	1.8
60°	1.8
62.5°	0.9
65°	0.9
67.5°	0.9
70°	0.9
72.5°	0.9
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)