

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1250668

Luminaire Tested: P3AS02R129030DE010 E3PHLP1MW

Issue Date: 1/29/2026

Test Information

Test Method: LM-79-2019
Report Number: P1250668
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2509-551-5)
Test Lab: INNOVATION CENTER
Issue Date: 1/29/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS02R129030DE010 E3PHLP1MW
Description: 3in Adjustable LED luminaire with, R12 optic, 3000K CCT AND, 90CRI , E3PHLP1MW TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 130.0 lumens
Efficiency: N/A
Efficacy: 35.1 lumens/watt
Spacing Criteria (0/90/45): 0.51 / 0.51 / 0.6
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 3.7
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1250668

CATALOG NUMBER: P3AS02R129030DE010 E3PHLP1MW

Luminous Intensity Polar Plot



TEST NUMBER: P1250668

CATALOG NUMBER: P3AS02R129030DE010 E3PHLP1MW

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	112	108	105	102	109	106	103	100	102	99	97		98	96	94		95
2	105	99	94	90	102	97	92	89	94	90	87		91	88	85		88
3	99	91	85	80	97	89	84	80	87	82	78		84	80	77		82
4	93	84	78	73	91	83	77	72	81	76	72		79	74	71		77
5	88	78	72	67	86	77	71	67	76	70	66		74	69	65		72
6	83	73	67	62	82	73	66	62	71	65	61		70	65	61		68
7	79	69	62	58	78	68	62	58	67	61	57		66	61	57		65
8	75	65	59	54	74	65	58	54	63	58	54		62	57	54		61
9	72	62	55	51	71	61	55	51	60	55	51		59	54	51		58
10	69	59	52	48	68	58	52	48	57	52	48		56	51	48		56

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	48658
5°	44684
10°	35604
15°	26606
20°	20208
25°	15291
30°	11318
35°	8084
40°	5525
45°	3876
50°	3309
55°	3250
60°	3377
65°	3528
70°	3590
75°	3728
80°	4041
85°	4026

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 82.5°

Luminance: 4704 cd/sqm

TEST NUMBER: P1250668

CATALOG NUMBER: P3AS02R129030DE010 E3PHLP1MW

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	18.0	13.8
10°-20°	32.9	25.3
20°-30°	29.1	22.4
30°-40°	19.1	14.7
40°-50°	10.2	7.8
50°-60°	7.7	6.0
60°-70°	6.6	5.1
70°-80°	4.5	3.5
80°-90°	1.9	1.4
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	80.0	61.5
0°-40°	99.0	76.2
0°-60°	117.0	90.0
0°-90°	130.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	130.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	222	
5°	203	18
15°	117	33
25°	63	29
35°	30	19
45°	12	10
55°	8	8
65°	7	7
75°	4	5
85°	2	2
90°	0	

TEST NUMBER: P1250668

CATALOG NUMBER: P3AS02R129030DE010 E3PHLP1MW

CANDELA DISTRIBUTION (FULL):

0°	
0°	221.9
2.5°	216.7
5°	203.0
7.5°	182.8
10°	159.9
12.5°	137.7
15°	117.2
17.5°	100.7
20°	86.6
22.5°	74.1
25°	63.2
27.5°	53.6
30°	44.7
32.5°	37.0
35°	30.2
37.5°	24.2
40°	19.3
42.5°	15.3
45°	12.5
47.5°	10.9
50°	9.7
52.5°	9.3
55°	8.5
57.5°	8.1
60°	7.7
62.5°	7.2
65°	6.8
67.5°	6.0
70°	5.6
72.5°	4.8
75°	4.4
77.5°	3.6
80°	3.2
82.5°	2.8
85°	1.6
87.5°	0.8
90°	0.0

(END OF REPORT)