

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1250981

Luminaire Tested: P3AS02R659030DE010 E3DLD1WH

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1250981
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-42)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS02R659030DE010 E3DLD1WH
Description: 3in Adjustable LED luminaire with, R65 optic, 3000K CCT AND, 90CRI , E3DLD1WH TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 191.9 lumens
Efficiency: N/A
Efficacy: 53.3 lumens/watt
Spacing Criteria (0/90/45): 0.94 / 0.94 / 1
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 3.6
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1250981

CATALOG NUMBER: P3AS02R659030DE010 E3DLD1WH

Luminous Intensity Polar Plot



TEST NUMBER: P1250981

CATALOG NUMBER: P3AS02R659030DE010 E3DLD1WH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	112	109	106	103	110	107	104	101	102	100	98		99	97	95		95
2	105	99	94	90	103	98	93	89	94	90	87		91	88	85		88
3	99	91	85	80	96	89	84	79	87	82	78		84	80	77		82
4	92	83	77	72	90	82	76	71	80	75	71		78	73	70		76
5	87	77	70	65	85	76	69	65	74	68	64		72	67	63		71
6	82	71	64	59	80	70	64	59	69	63	58		67	62	58		66
7	77	66	59	54	75	65	59	54	64	58	54		63	57	53		61
8	72	61	55	50	71	61	54	50	60	54	49		59	53	49		58
9	68	57	51	46	67	57	50	46	56	50	46		55	49	46		54
10	65	54	47	43	64	53	47	43	52	47	43		52	46	42		51

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	34164
5°	33700
10°	32576
15°	30715
20°	28329
25°	25719
30°	22788
35°	19381
40°	15429
45°	10885
50°	6311
55°	3441
60°	3201
65°	2906
70°	2629
75°	2457
80°	2147
85°	1761

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 10885 cd/sqm

TEST NUMBER: P1250981

CATALOG NUMBER: P3AS02R659030DE010 E3DLD1WH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	14.4	7.5
10°-20°	37.9	19.7
20°-30°	48.7	25.4
30°-40°	45.0	23.5
40°-50°	27.2	14.2
50°-60°	9.2	4.8
60°-70°	5.6	2.9
70°-80°	3.1	1.6
80°-90°	0.9	0.5
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	100.9	52.6
0°-40°	145.9	76.0
0°-60°	182.4	95.0
0°-90°	191.9	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	191.9	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	156	
5°	153	14
15°	135	38
25°	106	49
35°	72	45
45°	35	27
55°	9	9
65°	6	6
75°	3	3
85°	1	1
90°	0	

TEST NUMBER: P1250981

CATALOG NUMBER: P3AS02R659030DE010 E3DLD1WH

CANDELA DISTRIBUTION (FULL):

	0°
0°	155.8
2.5°	155.1
5°	153.1
7.5°	150.2
10°	146.3
12.5°	141.4
15°	135.3
17.5°	128.7
20°	121.4
22.5°	113.9
25°	106.3
27.5°	98.3
30°	90.0
32.5°	81.7
35°	72.4
37.5°	63.4
40°	53.9
42.5°	44.4
45°	35.1
47.5°	26.6
50°	18.5
52.5°	11.7
55°	9.0
57.5°	8.0
60°	7.3
62.5°	6.3
65°	5.6
67.5°	4.9
70°	4.1
72.5°	3.7
75°	2.9
77.5°	2.4
80°	1.7
82.5°	1.2
85°	0.7
87.5°	0.5
90°	0.0

(END OF REPORT)