

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1251452

Luminaire Tested: P3AS09R159030DE010 E3CB1MB

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1251452
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-4)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS09R159030DE010 E3CB1MB
Description: 3in Adjustable LED luminaire with, R15 optic, 3000K CCT AND, 90CRI , E3CB1MB TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 925.0 lumens
Efficiency: N/A
Efficacy: 83.3 lumens/watt
Spacing Criteria (0/90/45): 0.3 / 0.3 / 0.29
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 11.1
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1251452

CATALOG NUMBER: P3AS09R159030DE010 E3CB1MB

Luminous Intensity Polar Plot



TEST NUMBER: P1251452

CATALOG NUMBER: P3AS09R159030DE010 E3CB1MB

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20					20					20					20
RC	80				70					50					30					10
RW	70	50	30	10	70	50	30	10		50	30	10			50	30	10			50
RCR																				
0	119	119	119	119	116	116	116	116		111	111	111			106	106	106			102
1	116	114	112	111	113	112	110	109		108	107	106			104	103	103			101
2	113	110	107	105	111	108	106	104		105	103	101			102	101	99			99
3	110	106	103	100	108	105	102	100		102	100	98			100	98	97			98
4	107	103	100	97	106	102	99	97		100	97	95			98	96	94			97
5	105	100	97	94	104	99	96	94		98	95	93			96	94	92			95
6	103	98	94	92	102	97	94	92		96	93	91			95	92	91			94
7	101	96	92	90	100	95	92	90		94	91	89			93	91	89			92
8	99	94	90	88	98	93	90	88		92	90	88			92	89	87			91
9	97	92	89	87	97	92	89	87		91	88	86			90	88	86			90
10	96	90	87	85	95	90	87	85		89	87	85			89	86	85			88

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	1797970
5°	1506886
10°	709806
15°	214008
20°	79177
25°	30776
30°	11470
35°	3534
40°	1260
45°	682
50°	512
55°	573
60°	658
65°	363
70°	449
75°	593
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 682 cd/sqm

TEST NUMBER: P1251452

CATALOG NUMBER: P3AS09R159030DE010 E3CB1MB

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	529.2	57.2
10°-20°	314.6	34.0
20°-30°	66.1	7.1
30°-40°	10.7	1.2
40°-50°	1.8	0.2
50°-60°	1.3	0.1
60°-70°	0.8	0.1
70°-80°	0.5	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	909.9	98.4
0°-40°	920.6	99.5
0°-60°	923.7	99.9
0°-90°	925.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	925.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	8199	
5°	6846	529
15°	943	315
25°	127	66
35°	13	11
45°	2	2
55°	2	1
65°	1	1
75°	1	0
85°	0	0
90°	0	

TEST NUMBER: P1251452

CATALOG NUMBER: P3AS09R159030DE010 E3CB1MB

CANDELA DISTRIBUTION (FULL):

0°	
0°	8199.4
1°	8173.8
2°	8043.7
3°	7783.3
4°	7401.6
5°	6845.8
6°	6192.7
7°	5446.1
8°	4733.0
9°	3925.7
10°	3187.8
12.5°	1720.0
15°	942.7
17.5°	552.1
20°	339.3
22.5°	207.7
25°	127.2
27.5°	76.8
30°	45.3
32.5°	25.6
35°	13.2
37.5°	7.3
40°	4.4
42.5°	2.9
45°	2.2
47.5°	1.5
50°	1.5
52.5°	1.5
55°	1.5
57.5°	1.5
60°	1.5
62.5°	0.7
65°	0.7
67.5°	0.7
70°	0.7
72.5°	0.7
75°	0.7
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)