

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1251934

Luminaire Tested: P3AS13R259030DE010 E3DLD1GPH

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1251934
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-10)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS13R259030DE010 E3DLD1GPH
Description: 3in Adjustable LED luminaire with, R25 optic, 3000K CCT AND, 90CRI , E3DLD1GPH TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 382.0 lumens
Efficiency: N/A
Efficacy: 26.2 lumens/watt
Spacing Criteria (0/90/45): 0.78 / 0.78 / 0.85
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 14.6
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1251934

CATALOG NUMBER: P3AS13R259030DE010 E3DLD1GPH

Luminous Intensity Polar Plot



TEST NUMBER: P1251934

CATALOG NUMBER: P3AS13R259030DE010 E3DLD1GPH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	112	109	106	104	110	107	105	102	103	101	99		99	98	96		96
2	106	100	96	92	104	99	94	91	95	92	89		92	89	87		89
3	100	92	87	82	98	91	86	82	88	84	80		86	82	79		83
4	94	85	79	74	92	84	78	74	82	77	73		80	76	72		78
5	89	79	73	68	87	78	72	68	76	71	67		75	70	66		73
6	84	74	67	62	82	73	67	62	71	66	62		70	65	61		69
7	79	69	62	58	78	68	62	58	67	61	57		66	61	57		65
8	75	65	58	54	74	64	58	53	63	57	53		62	57	53		61
9	71	61	54	50	70	60	54	50	59	54	50		58	53	50		57
10	68	57	51	47	67	57	51	47	56	50	47		55	50	46		54

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	90782
5°	88620
10°	82118
15°	73145
20°	62865
25°	53422
30°	43981
35°	34265
40°	24646
45°	15630
50°	9245
55°	6384
60°	5833
65°	5448
70°	4873
75°	4406
80°	4167
85°	3522

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 15630 cd/sqm

TEST NUMBER: P1251934

CATALOG NUMBER: P3AS13R259030DE010 E3DLD1GPH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	37.3	9.8
10°-20°	89.4	23.4
20°-30°	101.1	26.5
30°-40°	79.9	20.9
40°-50°	40.4	10.6
50°-60°	16.2	4.2
60°-70°	10.3	2.7
70°-80°	5.7	1.5
80°-90°	1.6	0.4
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	227.8	59.6
0°-40°	307.8	80.6
0°-60°	364.3	95.4
0°-90°	382.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	382.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	414	
5°	403	37
15°	322	89
25°	221	101
35°	128	80
45°	50	40
55°	17	16
65°	10	10
75°	5	6
85°	1	2
90°	0	

TEST NUMBER: P1251934

CATALOG NUMBER: P3AS13R259030DE010 E3DLD1GPH

CANDELA DISTRIBUTION (FULL):

0°	
0°	414.0
1°	414.0
2°	412.6
3°	410.2
4°	406.9
5°	402.6
6°	397.4
7°	391.2
8°	384.5
9°	376.9
10°	368.8
11°	359.8
12°	351.2
13°	341.2
14°	331.7
15°	322.2
17.5°	295.5
20°	269.4
22.5°	244.6
25°	220.8
27.5°	197.5
30°	173.7
32.5°	151.3
35°	128.0
37.5°	106.6
40°	86.1
42.5°	67.1
45°	50.4
47.5°	37.6
50°	27.1
52.5°	20.5
55°	16.7
57.5°	15.2
60°	13.3
62.5°	11.9
65°	10.5
67.5°	9.0
70°	7.6
72.5°	6.7
75°	5.2
77.5°	4.3
80°	3.3
82.5°	2.4
85°	1.4
87.5°	0.5



TEST NUMBER: P1251934

CATALOG NUMBER: P3AS13R259030DE010 E3DLD1GPH

CANDELA DISTRIBUTION (continued):

0°
90° | 0.0

(END OF REPORT)