

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1251939

Luminaire Tested: P3AS13R259030DE010 E3DLD1WMH

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1251939
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-10)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS13R259030DE010 E3DLD1WMH
Description: 3in Adjustable LED luminaire with, R25 optic, 3000K CCT AND, 90CRI , E3DLD1WMH TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 780.0 lumens
Efficiency: N/A
Efficacy: 53.4 lumens/watt
Spacing Criteria (0/90/45): 0.78 / 0.78 / 0.85
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 14.6
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1251939

CATALOG NUMBER: P3AS13R259030DE010 E3DLD1WMH

Luminous Intensity Polar Plot



TEST NUMBER: P1251939

CATALOG NUMBER: P3AS13R259030DE010 E3DLD1WMH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	112	109	106	104	110	107	105	102	103	101	99		99	98	96		96
2	106	100	96	92	104	99	94	91	95	92	89		92	89	87		89
3	100	92	87	82	98	91	86	82	88	84	80		86	82	79		83
4	94	85	79	74	92	84	78	74	82	77	73		80	76	72		78
5	89	79	73	68	87	78	72	68	76	71	67		75	70	66		73
6	84	74	67	62	82	73	67	62	71	66	62		70	65	61		69
7	79	69	62	58	78	68	62	58	67	61	57		66	61	57		65
8	75	65	58	54	74	64	58	53	63	57	53		62	57	53		61
9	71	61	54	50	70	60	54	50	59	54	50		58	53	50		57
10	68	57	51	47	67	57	51	47	56	50	47		55	50	46		54

TEST NUMBER: P1251939

CATALOG NUMBER: P3AS13R259030DE010 E3DLD1WMH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	76.2	9.8
10°-20°	182.6	23.4
20°-30°	206.4	26.5
30°-40°	163.2	20.9
40°-50°	82.5	10.6
50°-60°	33.0	4.2
60°-70°	21.2	2.7
70°-80°	11.6	1.5
80°-90°	3.3	0.4
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	465.2	59.6
0°-40°	628.5	80.6
0°-60°	743.9	95.4
0°-90°	780.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	780.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	845	
5°	822	76
15°	658	183
25°	451	206
35°	261	163
45°	103	82
55°	34	33
65°	21	21
75°	11	12
85°	3	3
90°	0	

TEST NUMBER: P1251939

CATALOG NUMBER: P3AS13R259030DE010 E3DLD1WMH

CANDELA DISTRIBUTION (FULL):

0°	
0°	845.4
1°	845.4
2°	842.5
3°	837.6
4°	830.8
5°	822.1
6°	811.4
7°	798.8
8°	785.1
9°	769.6
10°	753.1
11°	734.6
12°	717.1
13°	696.7
14°	677.3
15°	657.9
17.5°	603.4
20°	550.0
22.5°	499.5
25°	450.9
27.5°	403.3
30°	354.7
32.5°	309.0
35°	261.4
37.5°	217.7
40°	175.9
42.5°	137.0
45°	103.0
47.5°	76.8
50°	55.4
52.5°	41.8
55°	34.0
57.5°	31.1
60°	27.2
62.5°	24.3
65°	21.4
67.5°	18.5
70°	15.5
72.5°	13.6
75°	10.7
77.5°	8.7
80°	6.8
82.5°	4.9
85°	2.9
87.5°	1.0



TEST NUMBER: P1251939

CATALOG NUMBER: P3AS13R259030DE010 E3DLD1WMH

CANDELA DISTRIBUTION (continued):

0°
90° | 0.0

(END OF REPORT)