

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1252102

Luminaire Tested: P3AS13R559030DE010 E3D1WMH

Issue Date: 1/29/2026

Test Information

Test Method: LM-79-2019
Report Number: P1252102
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2501-338-14)
Test Lab: INNOVATION CENTER
Issue Date: 1/29/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS13R559030DE010 E3D1WMH
Description: 3in Adjustable LED luminaire with, R55 optic, 3000K CCT AND, 90CRI , E3D1WMH TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 1254.0 lumens
Efficiency: N/A
Efficacy: 85.9 lumens/watt
Spacing Criteria (0/90/45): 0.93 / 0.93 / 0.82
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 14.6
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1252102

CATALOG NUMBER: P3AS13R559030DE010 E3D1WMH

Luminous Intensity Polar Plot



TEST NUMBER: P1252102

CATALOG NUMBER: P3AS13R559030DE010 E3D1WMH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	114	111	109	107	112	109	107	105	105	104	102		102	100	99		98
2	109	105	101	98	107	103	100	97	100	97	95		97	95	93		94
3	104	98	94	90	102	97	93	90	95	91	88		92	89	87		90
4	100	93	88	84	98	92	87	84	90	86	83		88	84	82		86
5	95	88	82	79	94	87	82	78	85	81	78		84	80	77		82
6	91	83	78	74	90	82	77	74	81	76	73		80	76	73		78
7	87	79	73	70	86	78	73	69	77	72	69		76	72	69		75
8	83	75	69	66	82	74	69	66	73	69	65		72	68	65		71
9	80	71	66	62	79	71	66	62	70	65	62		69	65	62		68
10	77	68	62	59	76	67	62	59	67	62	59		66	62	59		65

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	363655
5°	350781
10°	363320
15°	358186
20°	331502
25°	268104
30°	160683
35°	54449
40°	15000
45°	6636
50°	1944
55°	382
60°	219
65°	259
70°	321
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 6636 cd/sqm

TEST NUMBER: P1252102

CATALOG NUMBER: P3AS13R559030DE010 E3D1WMH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	154.2	12.3
10°-20°	439.3	35.0
20°-30°	488.3	38.9
30°-40°	152.0	12.1
40°-50°	18.2	1.5
50°-60°	1.4	0.1
60°-70°	0.5	0.0
70°-80°	0.1	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1081.8	86.3
0°-40°	1233.8	98.4
0°-60°	1253.5	100.0
0°-90°	1254.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1254.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1658	
5°	1594	154
15°	1578	439
25°	1108	488
35°	203	152
45°	21	18
55°	1	1
65°	0	0
75°	0	0
85°	0	0
90°	0	

TEST NUMBER: P1252102

CATALOG NUMBER: P3AS13R559030DE010 E3D1WMH

CANDELA DISTRIBUTION (FULL):

0°	
0°	1658.4
1°	1652.2
2°	1636.0
3°	1616.0
4°	1597.9
5°	1593.6
6°	1598.3
7°	1608.3
8°	1619.8
9°	1628.8
10°	1631.7
11°	1629.8
12°	1622.2
13°	1610.2
14°	1596.4
15°	1577.8
16°	1556.4
17°	1529.3
18°	1498.8
19°	1462.1
20°	1420.6
21°	1373.5
22°	1317.7
23°	1256.3
24°	1185.8
25°	1108.1
26°	1022.8
27°	932.3
28°	835.6
29°	736.0
30°	634.6
31°	532.6
32°	433.0
32.5°	388.7
33°	343.0
34°	265.4
35°	203.4
36°	154.8
37°	114.8
37.5°	98.1
38°	85.3
39°	64.8
40°	52.4
42.5°	33.3
45°	21.4

TEST NUMBER: P1252102

CATALOG NUMBER: P3AS13R559030DE010 E3D1WMH

CANDELA DISTRIBUTION (continued):

	0°
47.5°	12.9
50°	5.7
52.5°	1.9
55°	1.0
57.5°	0.5
60°	0.5
62.5°	0.5
65°	0.5
67.5°	0.5
70°	0.5
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)