

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1252150

Luminaire Tested: P3AS13R659030DE010 E3CB1MB

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1252150
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-44)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS13R659030DE010 E3CB1MB
Description: 3in Adjustable LED luminaire with, R65 optic, 3000K CCT AND, 90CRI , E3CB1MB TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 1202.0 lumens
Efficiency: N/A
Efficacy: 82.3 lumens/watt
Spacing Criteria (0/90/45): 0.98 / 0.98 / 0.9
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 14.6
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1252150

CATALOG NUMBER: P3AS13R659030DE010 E3CB1MB

Luminous Intensity Polar Plot



TEST NUMBER: P1252150

CATALOG NUMBER: P3AS13R659030DE010 E3CB1MB

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	114	111	108	106	111	109	106	104	105	103	101		101	99	98		97
2	108	103	99	96	106	101	98	95	98	95	93		95	93	91		92
3	103	96	91	87	101	95	90	87	92	88	85		90	87	84		88
4	97	90	84	80	96	89	84	80	87	82	79		85	81	78		83
5	93	84	78	74	91	83	78	74	82	77	73		80	76	73		78
6	88	79	73	69	86	78	73	69	77	72	68		75	71	68		74
7	84	74	68	64	82	74	68	64	72	67	64		71	67	63		70
8	80	70	64	60	78	69	64	60	68	63	60		67	63	59		66
9	76	66	60	56	75	66	60	56	65	60	56		64	59	56		63
10	72	63	57	53	71	62	57	53	61	56	53		60	56	53		60

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	293748
5°	276469
10°	272941
15°	268129
20°	253165
25°	234957
30°	182636
35°	105658
40°	42565
45°	19599
50°	7642
55°	2982
60°	2544
65°	2542
70°	2500
75°	2457
80°	2399
85°	2516

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 19599 cd/sqm

TEST NUMBER: P1252150

CATALOG NUMBER: P3AS13R659030DE010 E3CB1MB

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	119.4	9.9
10°-20°	329.8	27.4
20°-30°	431.8	35.9
30°-40°	250.1	20.8
40°-50°	53.5	4.5
50°-60°	8.7	0.7
60°-70°	4.8	0.4
70°-80°	2.8	0.2
80°-90°	1.1	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	881.0	73.3
0°-40°	1131.1	94.1
0°-60°	1193.3	99.3
0°-90°	1202.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1202.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1340	
5°	1256	119
15°	1181	330
25°	971	432
35°	395	250
45°	63	54
55°	8	9
65°	5	5
75°	3	3
85°	1	1
90°	0	

TEST NUMBER: P1252150

CATALOG NUMBER: P3AS13R659030DE010 E3CB1MB

CANDELA DISTRIBUTION (FULL):

0°	
0°	1339.6
2.5°	1301.7
5°	1256.0
7.5°	1237.5
10°	1225.8
12.5°	1209.3
15°	1181.1
17.5°	1137.4
20°	1084.9
22.5°	1035.3
25°	971.1
27.5°	863.2
30°	721.3
32.5°	559.0
35°	394.7
37.5°	249.8
40°	148.7
42.5°	93.3
45°	63.2
47.5°	40.8
50°	22.4
52.5°	10.7
55°	7.8
57.5°	6.8
60°	5.8
62.5°	5.8
65°	4.9
67.5°	3.9
70°	3.9
72.5°	2.9
75°	2.9
77.5°	1.9
80°	1.9
82.5°	1.0
85°	1.0
87.5°	1.0
90°	0.0

(END OF REPORT)