

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1252170

Luminaire Tested: P3AS13R659030DE010 E3DLD1MW

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1252170
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-42)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS13R659030DE010 E3DLD1MW
Description: 3in Adjustable LED luminaire with, R65 optic, 3000K CCT AND, 90CRI , E3DLD1MW TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 765.0 lumens
Efficiency: N/A
Efficacy: 52.4 lumens/watt
Spacing Criteria (0/90/45): 0.94 / 0.94 / 1
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 14.6
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1252170

CATALOG NUMBER: P3AS13R659030DE010 E3DLD1MW

Luminous Intensity Polar Plot



TEST NUMBER: P1252170

CATALOG NUMBER: P3AS13R659030DE010 E3DLD1MW

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	112	109	106	103	110	107	104	101	102	100	98		99	97	95		95
2	105	99	94	90	103	97	93	89	94	90	87		91	88	85		88
3	99	91	85	80	96	89	84	79	87	82	78		84	80	77		82
4	92	83	77	72	90	82	76	71	80	75	70		78	73	70		76
5	87	77	70	65	85	76	69	65	74	68	64		72	67	63		71
6	82	71	64	59	80	70	64	59	69	63	58		67	62	58		66
7	77	66	59	54	75	65	59	54	64	58	54		63	57	53		61
8	72	61	55	50	71	61	54	50	60	54	49		59	53	49		58
9	68	57	51	46	67	57	50	46	56	50	46		55	49	46		54
10	65	54	47	43	64	53	47	43	52	47	43		52	46	42		51

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	136129
5°	134294
10°	129791
15°	122407
20°	112896
25°	102490
30°	90773
35°	77256
40°	61458
45°	43384
50°	25176
55°	13725
60°	12762
65°	11571
70°	10579
75°	9913
80°	8587
85°	7296

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 43384 cd/sqm

TEST NUMBER: P1252170

CATALOG NUMBER: P3AS13R659030DE010 E3DLD1MW

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	57.4	7.5
10°-20°	150.9	19.7
20°-30°	193.9	25.3
30°-40°	179.4	23.4
40°-50°	108.3	14.2
50°-60°	36.9	4.8
60°-70°	22.2	2.9
70°-80°	12.6	1.6
80°-90°	3.6	0.5
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	402.1	52.6
0°-40°	581.5	76.0
0°-60°	726.6	95.0
0°-90°	765.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	765.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	621	
5°	610	57
15°	539	151
25°	424	194
35°	289	179
45°	140	108
55°	36	37
65°	22	22
75°	12	13
85°	3	4
90°	0	

TEST NUMBER: P1252170

CATALOG NUMBER: P3AS13R659030DE010 E3DLD1MW

CANDELA DISTRIBUTION (FULL):

0°	
0°	620.8
2.5°	617.9
5°	610.1
7.5°	598.5
10°	582.9
12.5°	563.5
15°	539.2
17.5°	513.0
20°	483.8
22.5°	453.7
25°	423.6
27.5°	391.5
30°	358.5
32.5°	325.5
35°	288.6
37.5°	252.6
40°	214.7
42.5°	176.8
45°	139.9
47.5°	105.9
50°	73.8
52.5°	46.6
55°	35.9
57.5°	32.1
60°	29.1
62.5°	25.3
65°	22.3
67.5°	19.4
70°	16.5
72.5°	14.6
75°	11.7
77.5°	9.7
80°	6.8
82.5°	4.9
85°	2.9
87.5°	1.9
90°	0.0

(END OF REPORT)