

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1252251

Luminaire Tested: P3AS17R159030DE010 E3DL1WMH

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1252251
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-3)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS17R159030DE010 E3DL1WMH
Description: 3in Adjustable LED luminaire with, R15 optic, 3000K CCT AND, 90CRI , E3DL1WMH TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 1336.0 lumens
Efficiency: N/A
Efficacy: 63.0 lumens/watt
Spacing Criteria (0/90/45): 0.4 / 0.4 / 0.43
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 21.2
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1252251

CATALOG NUMBER: P3AS17R159030DE010 E3DL1WMH

Luminous Intensity Polar Plot



TEST NUMBER: P1252251

CATALOG NUMBER: P3AS17R159030DE010 E3DL1WMH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	114	112	110	108	112	110	108	106	106	104	103		102	101	100		99
2	110	106	103	100	108	104	101	99	101	99	97		98	96	95		96
3	106	101	97	93	104	99	96	93	97	94	91		94	92	90		92
4	102	96	92	88	100	95	91	88	93	89	87		91	88	86		89
5	98	92	87	84	97	91	87	83	89	85	83		88	84	82		86
6	95	88	83	80	94	87	83	80	86	82	79		85	81	79		83
7	92	85	80	77	91	84	80	76	83	79	76		82	78	76		81
8	89	81	77	74	88	81	77	73	80	76	73		79	75	73		78
9	86	79	74	71	85	78	74	71	77	73	71		77	73	70		76
10	84	76	71	68	83	76	71	68	75	71	68		74	71	68		74

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	1141290
5°	1013072
10°	703527
15°	416052
20°	236971
25°	135468
30°	74948
35°	39966
40°	22099
45°	11970
50°	7471
55°	5887
60°	5087
65°	4670
70°	4103
75°	4321
80°	3283
85°	3271

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 11970 cd/sqm

TEST NUMBER: P1252251

CATALOG NUMBER: P3AS17R159030DE010 E3DL1WMH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	391.4	29.3
10°-20°	516.5	38.7
20°-30°	266.0	19.9
30°-40°	99.9	7.5
40°-50°	32.7	2.4
50°-60°	14.1	1.1
60°-70°	8.9	0.7
70°-80°	5.2	0.4
80°-90°	1.4	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1173.8	87.9
0°-40°	1273.7	95.3
0°-60°	1320.4	98.8
0°-90°	1336.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1336.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	5205	
5°	4602	391
15°	1833	517
25°	560	266
35°	149	100
45°	39	33
55°	15	14
65°	9	9
75°	5	5
85°	1	1
90°	0	

TEST NUMBER: P1252251

CATALOG NUMBER: P3AS17R159030DE010 E3DL1WMH

CANDELA DISTRIBUTION (FULL):

0°	
0°	5204.7
1°	5194.4
2°	5126.2
3°	4996.2
4°	4825.0
5°	4602.4
6°	4350.1
7°	4073.4
8°	3765.8
9°	3462.1
10°	3159.6
12.5°	2431.2
15°	1832.7
17.5°	1372.0
20°	1015.5
22.5°	758.1
25°	559.9
27.5°	408.0
30°	296.0
32.5°	209.8
35°	149.3
37.5°	106.8
40°	77.2
42.5°	55.3
45°	38.6
47.5°	28.3
50°	21.9
52.5°	18.0
55°	15.4
57.5°	12.9
60°	11.6
62.5°	10.3
65°	9.0
67.5°	7.7
70°	6.4
72.5°	6.4
75°	5.1
77.5°	3.9
80°	2.6
82.5°	2.6
85°	1.3
87.5°	0.0
90°	0.0

(END OF REPORT)