

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1252618

Luminaire Tested: P3AS20R209030D010 E3D1B

Issue Date: 1/29/2026

Test Information

Test Method: LM-79-2019
Report Number: P1252618
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2501-338-8)
Test Lab: INNOVATION CENTER
Issue Date: 1/29/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS20R209030D010 E3D1B
Description: 3in Adjustable LED luminaire with, R20 optic, 3000K CCT AND, 90CRI , E3D1B TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 2119.0 lumens
Efficiency: N/A
Efficacy: 73.6 lumens/watt
Spacing Criteria (0/90/45): 0.35 / 0.35 / 0.34
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 28.8
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1252618

CATALOG NUMBER: P3AS20R209030D010 E3D1B

Luminous Intensity Polar Plot



TEST NUMBER: P1252618

CATALOG NUMBER: P3AS20R209030D010 E3D1B

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	115	114	112	110	113	111	110	108	107	106	105		104	103	102		100
2	112	109	106	104	110	107	105	103	104	102	101		101	100	98		99
3	109	105	102	99	107	104	101	98	101	99	97		99	97	95		97
4	106	101	98	95	105	100	97	95	99	96	94		97	95	93		95
5	104	98	95	92	102	98	94	92	96	93	91		95	92	90		93
6	101	96	92	89	100	95	92	89	94	91	89		93	90	88		92
7	99	93	90	87	98	93	89	87	92	89	86		91	88	86		90
8	97	91	87	85	96	91	87	85	90	87	85		89	86	84		88
9	95	89	85	83	94	89	85	83	88	85	83		87	84	83		87
10	93	87	84	81	92	87	83	81	86	83	81		86	83	81		85

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	3214348
5°	2706332
10°	1690349
15°	631967
20°	216926
25°	90417
30°	42589
35°	19086
40°	9017
45°	4621
50°	1706
55°	306
60°	351
65°	415
70°	0
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 4621 cd/sqm

TEST NUMBER: P1252618

CATALOG NUMBER: P3AS20R209030D010 E3D1B

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	1022.4	48.3
10°-20°	842.2	39.7
20°-30°	191.4	9.0
30°-40°	48.7	2.3
40°-50°	12.2	0.6
50°-60°	1.5	0.1
60°-70°	0.5	0.0
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2056.0	97.0
0°-40°	2104.7	99.3
0°-60°	2118.5	100.0
0°-90°	2119.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2119.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	14659	
5°	12295	###
15°	2784	842
25°	374	191
35°	71	49
45°	15	12
55°	1	2
65°	1	0
75°	0	0
85°	0	0
90°	0	

TEST NUMBER: P1252618

CATALOG NUMBER: P3AS20R209030D010 E3D1B

CANDELA DISTRIBUTION (FULL):

0°	
0°	14658.6
1°	14534.3
2°	14168.1
3°	13642.9
4°	12998.3
5°	12294.9
6°	11511.2
7°	10646.2
8°	9637.1
9°	8637.1
10°	7591.5
11°	6478.9
12°	5367.8
13°	4426.7
14°	3526.9
15°	2783.8
16°	2197.2
17°	1733.2
18°	1392.7
19°	1132.6
20°	929.6
21°	777.1
22°	648.7
23°	539.4
24°	449.9
25°	373.7
27.5°	244.4
30°	168.2
32.5°	103.6
35°	71.3
37.5°	45.6
40°	31.5
42.5°	21.5
45°	14.9
47.5°	9.9
50°	5.0
52.5°	2.5
55°	0.8
57.5°	0.8
60°	0.8
62.5°	0.8
65°	0.8
67.5°	0.0
70°	0.0
72.5°	0.0

TEST NUMBER: P1252618

CATALOG NUMBER: P3AS20R209030D010 E3D1B

CANDELA DISTRIBUTION (continued):

	0°
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)