

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1252848

Luminaire Tested: P3AS20R609030D010 E3D1H

Issue Date: 1/29/2026

Test Information

Test Method: LM-79-2019
Report Number: P1252848
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2501-338-15)
Test Lab: INNOVATION CENTER
Issue Date: 1/29/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS20R609030D010 E3D1H
Description: 3in Adjustable LED luminaire with, R60 optic, 3000K CCT AND, 90CRI , E3D1H TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 2025.0 lumens
Efficiency: N/A
Efficacy: 70.3 lumens/watt
Spacing Criteria (0/90/45): 0.94 / 0.94 / 0.88
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 28.8
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1252848

CATALOG NUMBER: P3AS20R609030D010 E3D1H

Luminous Intensity Polar Plot



TEST NUMBER: P1252848

CATALOG NUMBER: P3AS20R609030D010 E3D1H

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	114	111	109	106	111	109	107	105	105	103	102		101	100	99		98
2	108	104	100	96	106	102	98	95	99	96	93		96	93	91		93
3	103	97	92	88	101	96	91	88	93	89	86		91	87	85		88
4	98	91	85	81	96	90	85	81	88	83	80		86	82	79		84
5	93	85	80	75	92	84	79	75	83	78	74		81	77	74		79
6	89	80	74	70	87	79	74	70	78	73	70		77	72	69		75
7	85	76	70	66	83	75	69	65	74	69	65		72	68	65		71
8	81	71	65	61	79	71	65	61	70	65	61		69	64	61		68
9	77	67	62	58	76	67	61	58	66	61	57		65	61	57		64
10	73	64	58	54	72	63	58	54	63	58	54		62	57	54		61

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	530572
5°	500879
10°	487856
15°	476711
20°	443232
25°	396241
30°	302654
35°	174723
40°	67813
45°	28251
50°	6209
55°	956
60°	746
65°	415
70°	513
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 28251 cd/sqm

TEST NUMBER: P1252848

CATALOG NUMBER: P3AS20R609030D010 E3D1H

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	214.8	10.6
10°-20°	584.9	28.9
20°-30°	732.6	36.2
30°-40°	409.6	20.2
40°-50°	77.8	3.8
50°-60°	4.0	0.2
60°-70°	0.9	0.0
70°-80°	0.3	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1532.4	75.7
0°-40°	1941.9	95.9
0°-60°	2023.7	99.9
0°-90°	2025.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2025.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2420	
5°	2276	215
15°	2100	585
25°	1638	733
35°	653	410
45°	91	78
55°	2	4
65°	1	1
75°	0	0
85°	0	0
90°	0	

TEST NUMBER: P1252848

CATALOG NUMBER: P3AS20R609030D010 E3D1H

CANDELA DISTRIBUTION (FULL):

0°	
0°	2419.6
1°	2409.7
2°	2378.2
3°	2340.9
4°	2306.1
5°	2275.5
6°	2252.3
7°	2232.4
8°	2217.5
9°	2203.4
10°	2191.0
11°	2178.6
12°	2164.5
13°	2147.1
14°	2126.4
15°	2099.9
16°	2067.6
17°	2031.1
18°	1989.7
19°	1942.5
20°	1899.4
21°	1853.0
22°	1805.0
23°	1754.5
24°	1699.0
25°	1637.7
26°	1565.6
27°	1485.2
28°	1395.0
29°	1298.9
30°	1195.3
31°	1090.9
32°	983.3
32.5°	924.4
33°	871.4
34°	761.3
35°	652.7
36°	555.0
37°	451.5
37.5°	404.2
38°	357.9
39°	288.3
40°	236.9
42.5°	144.1
45°	91.1



TEST NUMBER: P1252848

CATALOG NUMBER: P3AS20R609030D010 E3D1H

CANDELA DISTRIBUTION (continued):

	0°
47.5°	50.5
50°	18.2
52.5°	4.1
55°	2.5
57.5°	1.7
60°	1.7
62.5°	0.8
65°	0.8
67.5°	0.8
70°	0.8
72.5°	0.8
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)