

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1252868

Luminaire Tested: P3AS20R609030D010 E3DLP1MW

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1252868
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-37)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS20R609030D010 E3DLP1MW
Description: 3in Adjustable LED luminaire with, R60 optic, 3000K CCT AND, 90CRI , E3DLP1MW TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 1229.0 lumens
Efficiency: N/A
Efficacy: 42.7 lumens/watt
Spacing Criteria (0/90/45): 0.79 / 0.79 / 0.83
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 28.8
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1252868

CATALOG NUMBER: P3AS20R609030D010 E3DLP1MW

Luminous Intensity Polar Plot



TEST NUMBER: P1252868

CATALOG NUMBER: P3AS20R609030D010 E3DLP1MW

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	110	107	105	110	108	105	103	104	102	100		100	98	97		96
2	107	101	97	93	104	100	96	92	96	93	90		93	91	88		91
3	101	94	88	84	99	92	87	83	90	86	82		87	84	81		85
4	95	87	81	77	93	86	80	76	84	79	75		82	78	74		80
5	90	81	75	70	88	80	74	70	78	73	69		77	72	69		75
6	85	76	69	65	84	75	69	65	73	68	64		72	67	64		71
7	81	71	65	60	79	70	64	60	69	64	60		68	63	59		67
8	77	67	60	56	75	66	60	56	65	60	56		64	59	55		63
9	73	63	57	52	72	62	56	52	61	56	52		60	55	52		60
10	69	59	53	49	68	59	53	49	58	53	49		57	52	49		56

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	311466
5°	304468
10°	285054
15°	255734
20°	219912
25°	181849
30°	143693
35°	106702
40°	73481
45°	46082
50°	25347
55°	14833
60°	13332
65°	11415
70°	9745
75°	9997
80°	8587
85°	8554

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 46082 cd/sqm

TEST NUMBER: P1252868

CATALOG NUMBER: P3AS20R609030D010 E3DLP1MW

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	128.8	10.5
10°-20°	312.9	25.5
20°-30°	343.2	27.9
30°-40°	250.0	20.3
40°-50°	118.1	9.6
50°-60°	38.7	3.1
60°-70°	21.9	1.8
70°-80°	11.8	1.0
80°-90°	3.7	0.3
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	784.8	63.9
0°-40°	1034.8	84.2
0°-60°	1191.6	97.0
0°-90°	1229.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1229.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1420	
5°	1383	129
15°	1126	313
25°	752	343
35°	399	250
45°	149	118
55°	39	39
65°	22	22
75°	12	12
85°	3	4
90°	0	

TEST NUMBER: P1252868

CATALOG NUMBER: P3AS20R609030D010 E3DLP1MW

CANDELA DISTRIBUTION (FULL):

0°	
0°	1420.4
2.5°	1412.0
5°	1383.2
7.5°	1339.3
10°	1280.2
12.5°	1209.3
15°	1126.5
17.5°	1037.0
20°	942.4
22.5°	846.2
25°	751.6
27.5°	657.0
30°	567.5
32.5°	481.3
35°	398.6
37.5°	324.3
40°	256.7
42.5°	197.6
45°	148.6
47.5°	108.1
50°	74.3
52.5°	49.0
55°	38.8
57.5°	33.8
60°	30.4
62.5°	25.3
65°	22.0
67.5°	18.6
70°	15.2
72.5°	13.5
75°	11.8
77.5°	8.4
80°	6.8
82.5°	5.1
85°	3.4
87.5°	1.7
90°	0.0

(END OF REPORT)