

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1253490

Luminaire Tested: P3AS02R309035DE010 E3DLP1H

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1253490
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-13)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS02R309035DE010 E3DLP1H
Description: 3in Adjustable LED luminaire with, R30 optic, 3500K CCT AND, 90CRI , E3DLP1H TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 162.1 lumens
Efficiency: N/A
Efficacy: 45.0 lumens/watt
Spacing Criteria (0/90/45): 0.66 / 0.66 / 0.7
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 3.6
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1253490

CATALOG NUMBER: P3AS02R309035DE010 E3DLP1H

Luminous Intensity Polar Plot



TEST NUMBER: P1253490

CATALOG NUMBER: P3AS02R309035DE010 E3DLP1H

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	110	108	105	111	108	106	104	104	102	100		100	99	97		97
2	107	102	98	95	105	101	97	94	97	94	92		94	92	90		92
3	102	95	90	86	100	94	89	85	91	87	84		89	86	83		87
4	97	89	83	79	95	88	83	79	86	81	78		84	80	77		82
5	92	84	78	73	90	83	77	73	81	76	72		79	75	72		78
6	88	79	73	68	86	78	72	68	76	71	68		75	71	67		74
7	83	74	68	64	82	74	68	64	72	67	63		71	66	63		70
8	80	70	64	60	78	70	64	60	68	63	60		67	63	60		67
9	76	67	61	57	75	66	60	57	65	60	56		64	60	56		63
10	73	63	58	54	72	63	57	54	62	57	53		61	57	53		60

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	55368
5°	53643
10°	48318
15°	39978
20°	30943
25°	23227
30°	16863
35°	11243
40°	6899
45°	4062
50°	2490
55°	2026
60°	1754
65°	1453
70°	1282
75°	1271
80°	1010
85°	1258

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 4062 cd/sqm

TEST NUMBER: P1253490

CATALOG NUMBER: P3AS02R309035DE010 E3DLP1H

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	22.4	13.8
10°-20°	48.5	29.9
20°-30°	44.1	27.2
30°-40°	26.7	16.5
40°-50°	10.7	6.6
50°-60°	4.7	2.9
60°-70°	2.9	1.8
70°-80°	1.6	1.0
80°-90°	0.5	0.3
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	115.0	71.0
0°-40°	141.7	87.4
0°-60°	157.2	97.0
0°-90°	162.1	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	162.1	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	252	
5°	244	22
15°	176	48
25°	96	44
35°	42	27
45°	13	11
55°	5	5
65°	3	3
75°	2	2
85°	0	0
90°	0	

TEST NUMBER: P1253490

CATALOG NUMBER: P3AS02R309035DE010 E3DLP1H

CANDELA DISTRIBUTION (FULL):

0°	
0°	252.5
1°	252.2
2°	251.2
3°	249.4
4°	246.9
5°	243.7
6°	239.6
7°	235.4
8°	229.8
9°	223.6
10°	217.0
11°	209.5
12°	201.5
13°	193.4
14°	184.6
15°	176.1
17.5°	153.7
20°	132.6
22.5°	113.0
25°	96.0
27.5°	80.4
30°	66.6
32.5°	53.8
35°	42.0
37.5°	32.2
40°	24.1
42.5°	17.6
45°	13.1
47.5°	9.8
50°	7.3
52.5°	5.8
55°	5.3
57.5°	4.5
60°	4.0
62.5°	3.3
65°	2.8
67.5°	2.5
70°	2.0
72.5°	1.8
75°	1.5
77.5°	1.3
80°	0.8
82.5°	0.5
85°	0.5
87.5°	0.3



TEST NUMBER: P1253490
CATALOG NUMBER: P3AS02R309035DE010 E3DLP1H

CANDELA DISTRIBUTION (continued):

0°
90° | 0.0

(END OF REPORT)