

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1253926

Luminaire Tested: P3AS05R359035DE010 E3DLP1LI

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1253926
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-17)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS05R359035DE010 E3DLP1LI
Description: 3in Adjustable LED luminaire with, R35 optic, 3500K CCT AND, 90CRI , E3DLP1LI TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 334.0 lumens
Efficiency: N/A
Efficacy: 46.4 lumens/watt
Spacing Criteria (0/90/45): 0.69 / 0.69 / 0.72
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 7.2
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1253926

CATALOG NUMBER: P3AS05R359035DE010 E3DLP1LI

Luminous Intensity Polar Plot



TEST NUMBER: P1253926

CATALOG NUMBER: P3AS05R359035DE010 E3DLP1LI

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	110	108	105	111	108	106	104	104	102	100		100	99	97		97
2	107	102	98	94	105	100	97	93	97	94	91		94	92	89		91
3	102	95	90	86	100	94	89	85	91	87	84		89	85	82		86
4	97	89	83	79	95	88	82	78	86	81	77		84	80	77		82
5	92	83	77	73	90	82	77	73	81	76	72		79	75	71		77
6	87	78	72	68	86	77	72	68	76	71	67		75	70	67		73
7	83	74	68	63	82	73	67	63	72	67	63		71	66	63		69
8	79	70	64	60	78	69	63	59	68	63	59		67	62	59		66
9	76	66	60	56	75	66	60	56	65	59	56		64	59	56		63
10	72	63	57	53	71	62	57	53	61	56	53		61	56	53		60

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	107360
5°	104710
10°	95723
15°	81249
20°	64312
25°	48656
30°	35423
35°	23958
40°	14713
45°	8466
50°	5083
55°	4129
60°	3596
65°	3217
70°	2629
75°	2626
80°	2652
85°	2516

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 8466 cd/sqm

TEST NUMBER: P1253926

CATALOG NUMBER: P3AS05R359035DE010 E3DLP1LI

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	44.0	13.2
10°-20°	98.7	29.5
20°-30°	92.3	27.6
30°-40°	56.5	16.9
40°-50°	22.3	6.7
50°-60°	9.8	2.9
60°-70°	6.1	1.8
70°-80°	3.3	1.0
80°-90°	1.1	0.3
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	235.0	70.4
0°-40°	291.4	87.3
0°-60°	323.5	96.9
0°-90°	334.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	334.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	490	
5°	476	44
15°	358	99
25°	201	92
35°	90	56
45°	27	22
55°	11	10
65°	6	6
75°	3	3
85°	1	1
90°	0	

TEST NUMBER: P1253926

CATALOG NUMBER: P3AS05R359035DE010 E3DLP1LI

CANDELA DISTRIBUTION (FULL):

0°	
0°	489.6
1°	490.1
2°	488.6
3°	485.5
4°	480.8
5°	475.7
6°	469.0
7°	461.3
8°	452.0
9°	441.8
10°	429.9
11°	417.6
12°	404.2
13°	389.8
14°	373.9
15°	357.9
17.5°	316.8
20°	275.6
22.5°	236.1
25°	201.1
27.5°	168.7
30°	139.9
32.5°	113.1
35°	89.5
37.5°	68.4
40°	51.4
42.5°	37.0
45°	27.3
47.5°	19.5
50°	14.9
52.5°	12.3
55°	10.8
57.5°	9.3
60°	8.2
62.5°	7.2
65°	6.2
67.5°	5.1
70°	4.1
72.5°	3.6
75°	3.1
77.5°	2.6
80°	2.1
82.5°	1.5
85°	1.0
87.5°	0.5



TEST NUMBER: P1253926
CATALOG NUMBER: P3AS05R359035DE010 E3DLP1LI

CANDELA DISTRIBUTION (continued):

0°
90° | 0.0

(END OF REPORT)