

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1253997

Luminaire Tested: P3AS05R509035DE010 E3D1WMH

Issue Date: 1/29/2026

Test Information

Test Method: LM-79-2019
Report Number: P1253997
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2501-338-13)
Test Lab: INNOVATION CENTER
Issue Date: 1/29/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS05R509035DE010 E3D1WMH
Description: 3in Adjustable LED luminaire with, R50 optic, 3500K CCT AND, 90CRI , E3D1WMH TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 716.0 lumens
Efficiency: N/A
Efficacy: 99.5 lumens/watt
Spacing Criteria (0/90/45): 0.82 / 0.82 / 0.77
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 7.2
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1253997

CATALOG NUMBER: P3AS05R509035DE010 E3D1WMH

Luminous Intensity Polar Plot



TEST NUMBER: P1253997

CATALOG NUMBER: P3AS05R509035DE010 E3D1WMH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	114	112	109	107	112	110	108	106	105	104	102		102	101	99		98
2	109	105	101	98	107	103	100	97	100	97	95		97	95	93		94
3	105	99	95	91	103	98	94	90	95	92	89		93	90	88		91
4	100	94	89	85	99	92	88	85	90	87	84		88	85	83		87
5	96	89	84	80	94	88	83	79	86	82	79		84	81	78		83
6	92	84	79	75	91	83	78	75	82	78	74		81	77	74		79
7	88	80	75	71	87	79	74	71	78	74	70		77	73	70		76
8	84	76	71	67	83	76	71	67	74	70	67		74	69	66		73
9	81	73	67	64	80	72	67	64	71	67	63		70	66	63		70
10	78	69	64	61	77	69	64	61	68	64	60		67	63	60		67

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	250221
5°	243561
10°	232416
15°	210398
20°	182039
25°	149307
30°	85785
35°	26635
40°	7156
45°	2512
50°	614
55°	191
60°	132
65°	156
70°	0
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 2512 cd/sqm

TEST NUMBER: P1253997

CATALOG NUMBER: P3AS05R509035DE010 E3D1WMH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	103.6	14.5
10°-20°	256.8	35.9
20°-30°	269.9	37.7
30°-40°	77.3	10.8
40°-50°	7.5	1.1
50°-60°	0.6	0.1
60°-70°	0.3	0.0
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	630.4	88.0
0°-40°	707.6	98.8
0°-60°	715.8	100.0
0°-90°	716.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	716.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1141	
5°	1106	104
15°	927	257
25°	617	270
35°	100	77
45°	8	8
55°	0	1
65°	0	0
75°	0	0
85°	0	0
90°	0	

TEST NUMBER: P1253997

CATALOG NUMBER: P3AS05R509035DE010 E3D1WMH

CANDELA DISTRIBUTION (FULL):

0°	
0°	1141.1
1°	1139.3
2°	1134.2
3°	1126.9
4°	1117.1
5°	1106.5
6°	1095.1
7°	1083.0
8°	1071.6
9°	1058.5
10°	1043.8
11°	1026.9
12°	1007.4
13°	983.2
14°	956.9
15°	926.8
16°	895.0
17°	864.2
18°	832.6
19°	804.8
20°	780.1
21°	756.3
22°	729.3
23°	698.2
24°	661.9
25°	617.1
26°	568.6
27°	514.6
28°	460.8
29°	402.7
30°	338.8
31°	278.9
32°	223.8
32.5°	199.8
33°	175.6
34°	134.6
35°	99.5
36°	73.0
37°	54.3
37.5°	47.0
38°	40.7
39°	31.6
40°	25.0
42.5°	14.1
45°	8.1



TEST NUMBER: P1253997

CATALOG NUMBER: P3AS05R509035DE010 E3D1WMH

CANDELA DISTRIBUTION (continued):

	0°
47.5°	4.5
50°	1.8
52.5°	0.8
55°	0.5
57.5°	0.5
60°	0.3
62.5°	0.3
65°	0.3
67.5°	0.3
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)