

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1254290

Luminaire Tested: P3AS09R359035DE010 E3DL1LI

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1254290
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-19)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS09R359035DE010 E3DL1LI
Description: 3in Adjustable LED luminaire with, R35 optic, 3500K CCT AND, 90CRI , E3DL1LI TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 791.0 lumens
Efficiency: N/A
Efficacy: 71.3 lumens/watt
Spacing Criteria (0/90/45): 0.58 / 0.58 / 0.58
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 11.1
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1254290

CATALOG NUMBER: P3AS09R359035DE010 E3DL1LI

Luminous Intensity Polar Plot



TEST NUMBER: P1254290

CATALOG NUMBER: P3AS09R359035DE010 E3DL1LI

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	114	112	109	107	112	109	107	106	105	104	102		102	100	99		98
2	109	105	101	98	107	103	100	97	100	97	95		97	95	93		94
3	105	99	95	91	103	98	94	90	95	92	89		93	90	88		91
4	100	94	89	85	99	93	88	85	91	87	84		89	85	83		87
5	96	89	84	80	95	88	83	80	86	82	79		85	81	78		83
6	92	85	80	76	91	84	79	76	83	78	75		81	77	75		80
7	89	81	76	72	88	80	75	72	79	75	71		78	74	71		77
8	85	77	72	69	84	77	72	68	76	71	68		75	71	68		74
9	82	74	69	66	81	74	69	65	73	68	65		72	68	65		71
10	79	71	66	63	78	71	66	63	70	66	63		69	65	62		69

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	398937
5°	383402
10°	334062
15°	255870
20°	171188
25°	103579
30°	59452
35°	33221
40°	17662
45°	9086
50°	4367
55°	3441
60°	3289
65°	2750
70°	2885
75°	2542
80°	2904
85°	2013

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 9086 cd/sqm

TEST NUMBER: P1254290

CATALOG NUMBER: P3AS09R359035DE010 E3DL1LI

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	158.5	20.0
10°-20°	307.1	38.8
20°-30°	201.1	25.4
30°-40°	81.6	10.3
40°-50°	24.5	3.1
50°-60°	8.3	1.1
60°-70°	5.6	0.7
70°-80°	3.3	0.4
80°-90°	1.2	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	666.7	84.3
0°-40°	748.2	94.6
0°-60°	781.0	98.7
0°-90°	791.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	791.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1819	
5°	1742	158
15°	1127	307
25°	428	201
35°	124	82
45°	29	24
55°	9	8
65°	5	6
75°	3	3
85°	1	1
90°	0	

TEST NUMBER: P1254290

CATALOG NUMBER: P3AS09R359035DE010 E3DL1LI

CANDELA DISTRIBUTION (FULL):

0°	
0°	1819.3
1°	1816.3
2°	1808.1
3°	1791.5
4°	1771.9
5°	1741.8
6°	1704.2
7°	1662.1
8°	1614.7
9°	1560.5
10°	1500.3
11°	1433.4
12°	1363.4
13°	1285.1
14°	1210.6
15°	1127.1
17.5°	924.7
20°	733.6
22.5°	564.3
25°	428.1
27.5°	319.0
30°	234.8
32.5°	172.3
35°	124.1
37.5°	88.0
40°	61.7
42.5°	42.9
45°	29.3
47.5°	19.6
50°	12.8
52.5°	9.8
55°	9.0
57.5°	8.3
60°	7.5
62.5°	6.8
65°	5.3
67.5°	4.5
70°	4.5
72.5°	3.8
75°	3.0
77.5°	2.3
80°	2.3
82.5°	1.5
85°	0.8
87.5°	0.8



TEST NUMBER: P1254290
CATALOG NUMBER: P3AS09R359035DE010 E3DL1LI

CANDELA DISTRIBUTION (continued):

0°
90° | 0.0

(END OF REPORT)