

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1254436

Luminaire Tested: P3AS09R609035DE010 E3DL1WH

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1254436
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-37)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS09R609035DE010 E3DL1WH
Description: 3in Adjustable LED luminaire with, R60 optic, 3500K CCT AND, 90CRI , E3DL1WH TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 548.0 lumens
Efficiency: N/A
Efficacy: 49.4 lumens/watt
Spacing Criteria (0/90/45): 0.79 / 0.79 / 0.83
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 11.1
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1254436

CATALOG NUMBER: P3AS09R609035DE010 E3DL1WH

Luminous Intensity Polar Plot



TEST NUMBER: P1254436

CATALOG NUMBER: P3AS09R609035DE010 E3DL1WH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	110	107	105	110	108	105	103	104	102	100		100	98	97		96
2	107	101	97	93	104	100	96	92	96	93	90		93	91	88		91
3	101	94	88	84	99	92	87	83	90	86	82		87	84	81		85
4	95	87	81	77	93	86	80	76	84	79	75		82	78	74		80
5	90	81	75	70	88	80	74	70	78	73	69		77	72	69		75
6	85	76	69	65	84	75	69	65	73	68	64		72	67	64		71
7	81	71	65	60	79	70	64	60	69	64	60		68	63	59		67
8	77	67	60	56	75	66	60	56	65	60	56		64	59	55		63
9	73	63	57	52	72	62	56	52	61	56	52		60	55	52		60
10	69	59	53	49	68	59	53	49	58	53	49		57	52	49		56

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	138870
5°	135769
10°	127096
15°	114030
20°	98055
25°	81077
30°	64060
35°	47569
40°	32776
45°	20560
50°	11292
55°	6614
60°	5964
65°	5085
70°	4360
75°	4490
80°	3788
85°	3774

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 20560 cd/sqm

TEST NUMBER: P1254436

CATALOG NUMBER: P3AS09R609035DE010 E3DL1WH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	57.4	10.5
10°-20°	139.5	25.5
20°-30°	153.0	27.9
30°-40°	111.5	20.3
40°-50°	52.7	9.6
50°-60°	17.2	3.1
60°-70°	9.8	1.8
70°-80°	5.3	1.0
80°-90°	1.7	0.3
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	349.9	63.9
0°-40°	461.4	84.2
0°-60°	531.3	96.9
0°-90°	548.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	548.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	633	
5°	617	57
15°	502	140
25°	335	153
35°	178	111
45°	66	53
55°	17	17
65°	10	10
75°	5	5
85°	2	2
90°	0	

TEST NUMBER: P1254436

CATALOG NUMBER: P3AS09R609035DE010 E3DL1WH

CANDELA DISTRIBUTION (FULL):

	0°
0°	633.3
2.5°	629.6
5°	616.8
7.5°	597.2
10°	570.8
12.5°	539.2
15°	502.3
17.5°	462.4
20°	420.2
22.5°	377.3
25°	335.1
27.5°	292.9
30°	253.0
32.5°	214.6
35°	177.7
37.5°	144.6
40°	114.5
42.5°	88.1
45°	66.3
47.5°	48.2
50°	33.1
52.5°	21.8
55°	17.3
57.5°	15.1
60°	13.6
62.5°	11.3
65°	9.8
67.5°	8.3
70°	6.8
72.5°	6.0
75°	5.3
77.5°	3.8
80°	3.0
82.5°	2.3
85°	1.5
87.5°	0.8
90°	0.0

(END OF REPORT)