

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1254443

Luminaire Tested: P3AS09R609035DE010 E3DLD1WMH

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1254443
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-38)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS09R609035DE010 E3DLD1WMH
Description: 3in Adjustable LED luminaire with, R60 optic, 3500K CCT AND, 90CRI , E3DLD1WMH TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 621.0 lumens
Efficiency: N/A
Efficacy: 55.9 lumens/watt
Spacing Criteria (0/90/45): 0.94 / 0.94 / 1
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 11.1
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1254443

CATALOG NUMBER: P3AS09R609035DE010 E3DLD1WMH

Luminous Intensity Polar Plot



TEST NUMBER: P1254443

CATALOG NUMBER: P3AS09R609035DE010 E3DLD1WMH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	112	109	106	103	110	107	104	101	102	100	98		99	97	95		95
2	105	99	94	90	103	97	93	89	94	90	87		91	88	85		88
3	99	91	85	80	96	89	84	79	87	82	78		84	80	77		82
4	92	83	77	72	90	82	76	71	80	75	70		78	73	70		76
5	87	77	70	65	85	76	69	65	74	68	64		72	67	63		71
6	82	71	64	59	80	70	64	59	69	63	58		67	62	58		66
7	77	66	59	54	75	65	59	54	64	58	54		63	57	53		61
8	72	61	55	50	71	61	54	50	60	54	49		59	53	49		58
9	68	57	51	46	67	57	50	46	56	50	46		55	49	46		54
10	65	54	47	43	64	53	47	43	52	47	43		52	46	42		51

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	110232
5°	109003
10°	105231
15°	99410
20°	91638
25°	82964
30°	73657
35°	62961
40°	50065
45°	35290
50°	21082
55°	10666
60°	10262
65°	9391
70°	8719
75°	8303
80°	7577
85°	5787

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 35290 cd/sqm

TEST NUMBER: P1254443

CATALOG NUMBER: P3AS09R609035DE010 E3DLD1WMH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	46.5	7.5
10°-20°	122.4	19.7
20°-30°	157.1	25.3
30°-40°	145.7	23.5
40°-50°	88.7	14.3
50°-60°	29.6	4.8
60°-70°	18.0	2.9
70°-80°	10.1	1.6
80°-90°	2.9	0.5
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	326.0	52.5
0°-40°	471.7	76.0
0°-60°	590.0	95.0
0°-90°	621.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	621.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	503	
5°	495	47
15°	438	122
25°	343	157
35°	235	146
45°	114	89
55°	28	30
65°	18	18
75°	10	10
85°	2	3
90°	0	

TEST NUMBER: P1254443

CATALOG NUMBER: P3AS09R609035DE010 E3DLD1WMH

CANDELA DISTRIBUTION (FULL):

0°	
0°	502.7
2.5°	500.5
5°	495.2
7.5°	485.4
10°	472.6
12.5°	456.7
15°	437.9
17.5°	416.0
20°	392.7
22.5°	367.8
25°	342.9
27.5°	317.3
30°	290.9
32.5°	264.5
35°	235.2
37.5°	204.3
40°	174.9
42.5°	144.0
45°	113.8
47.5°	88.2
50°	61.8
52.5°	36.9
55°	27.9
57.5°	25.6
60°	23.4
62.5°	20.3
65°	18.1
67.5°	15.8
70°	13.6
72.5°	11.3
75°	9.8
77.5°	7.5
80°	6.0
82.5°	3.8
85°	2.3
87.5°	1.5
90°	0.0

(END OF REPORT)