

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1254527

Luminaire Tested: P3AS10R129035DE010 E3DLD1WMH

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1254527
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-2)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS10R129035DE010 E3DLD1WMH
Description: 3in Adjustable LED luminaire with, R12 optic, 3500K CCT AND, 90CRI , E3DLD1WMH TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 567.0 lumens
Efficiency: N/A
Efficacy: 48.5 lumens/watt
Spacing Criteria (0/90/45): 0.76 / 0.76 / 0.82
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 11.7
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1254527

CATALOG NUMBER: P3AS10R129035DE010 E3DLD1WMH

Luminous Intensity Polar Plot



TEST NUMBER: P1254527

CATALOG NUMBER: P3AS10R129035DE010 E3DLD1WMH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	109	106	104	110	107	105	102	103	101	99		99	98	96		96
2	106	100	96	92	104	99	95	91	95	92	89		92	90	87		90
3	100	93	87	83	98	91	86	82	89	84	81		86	82	79		84
4	94	86	80	75	92	85	79	74	82	77	73		80	76	73		78
5	89	80	73	68	87	79	73	68	77	72	67		75	71	67		74
6	84	74	68	63	83	73	67	63	72	66	62		70	66	62		69
7	80	69	63	58	78	69	63	58	67	62	58		66	61	57		65
8	76	65	59	54	74	65	58	54	63	58	54		62	57	54		61
9	72	61	55	51	71	61	55	51	60	54	50		59	54	50		58
10	68	58	52	48	67	57	51	47	57	51	47		56	51	47		55

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	143015
5°	139137
10°	127141
15°	111374
20°	95535
25°	79771
30°	63833
35°	47890
40°	34751
45°	22731
50°	14226
55°	9596
60°	8508
65°	7835
70°	7373
75°	6693
80°	6314
85°	5535

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 22731 cd/sqm

TEST NUMBER: P1254527

CATALOG NUMBER: P3AS10R129035DE010 E3DLD1WMH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	58.3	10.3
10°-20°	136.7	24.1
20°-30°	150.6	26.6
30°-40°	112.8	19.9
40°-50°	58.5	10.3
50°-60°	24.2	4.3
60°-70°	15.0	2.6
70°-80°	8.4	1.5
80°-90°	2.4	0.4
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	345.6	61.0
0°-40°	458.4	80.8
0°-60°	541.2	95.4
0°-90°	567.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	567.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	652	
5°	632	58
15°	491	137
25°	330	151
35°	179	113
45°	73	58
55°	25	24
65°	15	15
75°	8	8
85°	2	2
90°	0	

TEST NUMBER: P1254527

CATALOG NUMBER: P3AS10R129035DE010 E3DLD1WMH

CANDELA DISTRIBUTION (FULL):

0°	
0°	652.2
1°	652.9
2°	650.8
3°	646.5
4°	640.0
5°	632.1
6°	622.0
7°	611.3
8°	598.3
9°	584.7
10°	571.0
12.5°	531.5
15°	490.6
17.5°	449.7
20°	409.4
22.5°	368.5
25°	329.7
27.5°	290.9
30°	252.1
32.5°	214.1
35°	178.9
37.5°	148.7
40°	121.4
42.5°	96.3
45°	73.3
47.5°	55.3
50°	41.7
52.5°	30.9
55°	25.1
57.5°	22.3
60°	19.4
62.5°	17.2
65°	15.1
67.5°	12.9
70°	11.5
72.5°	9.3
75°	7.9
77.5°	6.5
80°	5.0
82.5°	3.6
85°	2.2
87.5°	0.7
90°	0.0

(END OF REPORT)