

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1254641

Luminaire Tested: P3AS13R259035DE010 E3DLD1GPH

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1254641
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-10)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS13R259035DE010 E3DLD1GPH
Description: 3in Adjustable LED luminaire with, R25 optic, 3500K CCT AND, 90CRI , E3DLD1GPH TRIM
Light Source: -
Ballast/Driver: -


Summary

Lumens per Lamp: N/A
Luminaire Lumens: 393.0 lumens
Efficiency: N/A
Efficacy: 26.9 lumens/watt
Spacing Criteria (0/90/45): 0.78 / 0.78 / 0.85
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 14.6
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1254641
CATALOG NUMBER: P3AS13R259035DE010 E3DLD1GPH

Luminous Intensity Polar Plot





TEST NUMBER: P1254641

CATALOG NUMBER: P3AS13R259035DE010 E3DLD1GPH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

| | | | | | | | | | | | | | | | | | | | | | |
|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|----|-----|
| RF | 20 | | | | 20 | | | | 20 | | | | 20 | | | | 20 | | | | |
| RC | 80 | | | | 70 | | | | 50 | | | | 30 | | | | 10 | | | 0 | |
| RW | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 50 | 30 | 10 | 50 | 30 | 10 | 50 | 30 | 10 | 50 | 30 | 10 | 0 |
| RCR | | | | | | | | | | | | | | | | | | | | | |
| 0 | 119 | 119 | 119 | 119 | 116 | 116 | 116 | 116 | 111 | 111 | 111 | 106 | 106 | 106 | 102 | 102 | 102 | 100 | | | 100 |
| 1 | 112 | 109 | 106 | 104 | 110 | 107 | 105 | 102 | 103 | 101 | 99 | 99 | 98 | 96 | 96 | 94 | 93 | 91 | | | 91 |
| 2 | 106 | 100 | 96 | 92 | 104 | 99 | 94 | 91 | 95 | 92 | 89 | 92 | 89 | 87 | 89 | 87 | 85 | 83 | | | 83 |
| 3 | 100 | 92 | 87 | 82 | 98 | 91 | 86 | 82 | 88 | 84 | 80 | 86 | 82 | 79 | 83 | 80 | 78 | 76 | | | 76 |
| 4 | 94 | 85 | 79 | 74 | 92 | 84 | 78 | 74 | 82 | 77 | 73 | 80 | 76 | 72 | 78 | 74 | 71 | 70 | | | 70 |
| 5 | 89 | 79 | 73 | 68 | 87 | 78 | 72 | 68 | 76 | 71 | 67 | 75 | 70 | 66 | 73 | 69 | 66 | 64 | | | 64 |
| 6 | 84 | 74 | 67 | 62 | 82 | 73 | 67 | 62 | 71 | 66 | 62 | 70 | 65 | 61 | 69 | 64 | 61 | 59 | | | 59 |
| 7 | 79 | 69 | 62 | 58 | 78 | 68 | 62 | 58 | 67 | 61 | 57 | 66 | 61 | 57 | 65 | 60 | 57 | 55 | | | 55 |
| 8 | 75 | 65 | 58 | 54 | 74 | 64 | 58 | 53 | 63 | 57 | 53 | 62 | 57 | 53 | 61 | 56 | 53 | 51 | | | 51 |
| 9 | 71 | 61 | 54 | 50 | 70 | 60 | 54 | 50 | 59 | 54 | 50 | 58 | 53 | 50 | 57 | 53 | 49 | 48 | | | 48 |
| 10 | 68 | 57 | 51 | 47 | 67 | 57 | 51 | 47 | 56 | 50 | 47 | 55 | 50 | 46 | 54 | 50 | 46 | 45 | | | 45 |

AVERAGE LUMINANCE (cd/sqm):

| | |
|-----|-------|
| | 0° |
| 0° | 93392 |
| 5° | 91173 |
| 10° | 84479 |
| 15° | 75256 |
| 20° | 64662 |
| 25° | 54971 |
| 30° | 45247 |
| 35° | 35255 |
| 40° | 25362 |
| 45° | 16095 |
| 50° | 9518 |
| 55° | 6537 |
| 60° | 6008 |
| 65° | 5604 |
| 70° | 5001 |
| 75° | 4575 |
| 80° | 4293 |
| 85° | 3774 |

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 16095 cd/sqm



TEST NUMBER: P1254641
 CATALOG NUMBER: P3AS13R259035DE010 E3DLD1GPH

ZONAL LUMENS:

| Zone | Lumens | % Fixture |
|-----------|--------|-----------|
| 0°-10° | 38.4 | 9.8 |
| 10°-20° | 92.0 | 23.4 |
| 20°-30° | 104.0 | 26.5 |
| 30°-40° | 82.2 | 20.9 |
| 40°-50° | 41.5 | 10.6 |
| 50°-60° | 16.6 | 4.2 |
| 60°-70° | 10.6 | 2.7 |
| 70°-80° | 5.9 | 1.5 |
| 80°-90° | 1.7 | 0.4 |
| 90°-100° | 0.0 | 0.0 |
| 100°-110° | 0.0 | 0.0 |
| 110°-120° | 0.0 | 0.0 |
| 120°-130° | 0.0 | 0.0 |
| 130°-140° | 0.0 | 0.0 |
| 140°-150° | 0.0 | 0.0 |
| 150°-160° | 0.0 | 0.0 |
| 160°-170° | 0.0 | 0.0 |
| 170°-180° | 0.0 | 0.0 |
| 0°-30° | 234.4 | 59.6 |
| 0°-40° | 316.6 | 80.6 |
| 0°-60° | 374.8 | 95.4 |
| 0°-90° | 393.0 | 100.0 |
| 90°-120° | 0.0 | 0.0 |
| 90°-150° | 0.0 | 0.0 |
| 90°-180° | 0.0 | 0.0 |
| 0°-180° | 393.0 | 100.0 |

CANDELA DISTRIBUTION:

| | 0° | Flux |
|-----|-----|------|
| 0° | 426 | |
| 5° | 414 | 38 |
| 15° | 332 | 92 |
| 25° | 227 | 104 |
| 35° | 132 | 82 |
| 45° | 52 | 42 |
| 55° | 17 | 17 |
| 65° | 11 | 11 |
| 75° | 5 | 6 |
| 85° | 2 | 2 |
| 90° | 0 | |



TEST NUMBER: P1254641
CATALOG NUMBER: P3AS13R259035DE010 E3DLD1GPH

CANDELA DISTRIBUTION (FULL):

| 0° | |
|-------|-------|
| 0° | 425.9 |
| 1° | 425.9 |
| 2° | 424.5 |
| 3° | 422.0 |
| 4° | 418.6 |
| 5° | 414.2 |
| 6° | 408.8 |
| 7° | 402.4 |
| 8° | 395.6 |
| 9° | 387.8 |
| 10° | 379.4 |
| 11° | 370.1 |
| 12° | 361.3 |
| 13° | 351.0 |
| 14° | 341.2 |
| 15° | 331.5 |
| 17.5° | 304.0 |
| 20° | 277.1 |
| 22.5° | 251.7 |
| 25° | 227.2 |
| 27.5° | 203.2 |
| 30° | 178.7 |
| 32.5° | 155.7 |
| 35° | 131.7 |
| 37.5° | 109.7 |
| 40° | 88.6 |
| 42.5° | 69.0 |
| 45° | 51.9 |
| 47.5° | 38.7 |
| 50° | 27.9 |
| 52.5° | 21.1 |
| 55° | 17.1 |
| 57.5° | 15.7 |
| 60° | 13.7 |
| 62.5° | 12.2 |
| 65° | 10.8 |
| 67.5° | 9.3 |
| 70° | 7.8 |
| 72.5° | 6.9 |
| 75° | 5.4 |
| 77.5° | 4.4 |
| 80° | 3.4 |
| 82.5° | 2.4 |
| 85° | 1.5 |
| 87.5° | 0.5 |



TEST NUMBER: P1254641
CATALOG NUMBER: P3AS13R259035DE010 E3DLD1GPH

CANDELA DISTRIBUTION (continued):

0°
90° | 0.0

(END OF REPORT)