

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1254798

Luminaire Tested: P3AS13R509035DE010 E3DLP1WMH

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1254798
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-29)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS13R509035DE010 E3DLP1WMH
Description: 3in Adjustable LED luminaire with, R50 optic, 3500K CCT AND, 90CRI , E3DLP1WMH TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 738.1 lumens
Efficiency: N/A
Efficacy: 50.6 lumens/watt
Spacing Criteria (0/90/45): 0.75 / 0.75 / 0.77
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 14.6
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1254798

CATALOG NUMBER: P3AS13R509035DE010 E3DLP1WMH

Luminous Intensity Polar Plot



TEST NUMBER: P1254798

CATALOG NUMBER: P3AS13R509035DE010 E3DLP1WMH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	110	107	105	111	108	106	103	104	102	100		100	99	97		97
2	107	102	98	94	105	100	96	93	97	94	91		94	91	89		91
3	101	95	89	85	99	93	88	85	91	87	83		88	85	82		86
4	96	88	82	78	94	87	82	78	85	80	77		83	79	76		81
5	91	83	76	72	90	82	76	72	80	75	71		78	74	70		77
6	87	77	71	67	85	77	71	67	75	70	66		74	69	66		72
7	82	73	67	62	81	72	66	62	71	66	62		70	65	61		68
8	78	69	63	58	77	68	62	58	67	62	58		66	61	58		65
9	75	65	59	55	74	64	59	55	63	58	55		63	58	54		62
10	71	61	56	52	70	61	55	52	60	55	51		59	55	51		59

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	214654
5°	208870
10°	192604
15°	169377
20°	141716
25°	112386
30°	82443
35°	56697
40°	36039
45°	20126
50°	10916
55°	9175
60°	7894
65°	7264
70°	6411
75°	5931
80°	5051
85°	5032

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 20126 cd/sqm

TEST NUMBER: P1254798

CATALOG NUMBER: P3AS13R509035DE010 E3DLP1WMH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	87.9	11.9
10°-20°	206.6	28.0
20°-30°	211.4	28.6
30°-40°	134.0	18.2
40°-50°	53.3	7.2
50°-60°	21.6	2.9
60°-70°	13.8	1.9
70°-80°	7.1	1.0
80°-90°	2.2	0.3
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	505.9	68.5
0°-40°	639.9	86.7
0°-60°	714.9	96.9
0°-90°	738.1	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	738.1	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	979	
5°	949	88
15°	746	207
25°	464	211
35°	212	134
45°	65	53
55°	24	22
65°	14	14
75°	7	7
85°	2	2
90°	0	

TEST NUMBER: P1254798

CATALOG NUMBER: P3AS13R509035DE010 E3DLP1WMH

CANDELA DISTRIBUTION (FULL):

0°	
0°	978.9
2.5°	971.9
5°	948.9
7.5°	912.9
10°	865.0
12.5°	808.1
15°	746.1
17.5°	678.2
20°	607.3
22.5°	536.4
25°	464.5
27.5°	392.5
30°	325.6
32.5°	265.7
35°	211.8
37.5°	165.8
40°	125.9
42.5°	92.9
45°	64.9
47.5°	43.9
50°	32.0
52.5°	27.0
55°	24.0
57.5°	21.0
60°	18.0
62.5°	16.0
65°	14.0
67.5°	12.0
70°	10.0
72.5°	8.0
75°	7.0
77.5°	5.0
80°	4.0
82.5°	3.0
85°	2.0
87.5°	1.0
90°	0.0

(END OF REPORT)