

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1254867

Luminaire Tested: P3AS13R659035DE010 E3D1WMH

Issue Date: 1/29/2026

Test Information

Test Method: LM-79-2019
Report Number: P1254867
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2501-338-16)
Test Lab: INNOVATION CENTER
Issue Date: 1/29/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS13R659035DE010 E3D1WMH
Description: 3in Adjustable LED luminaire with, R65 optic, 3500K CCT AND, 90CRI , E3D1WMH TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 1193.0 lumens
Efficiency: N/A
Efficacy: 81.7 lumens/watt
Spacing Criteria (0/90/45): 0.92 / 0.92 / 0.88
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 14.6
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1254867

CATALOG NUMBER: P3AS13R659035DE010 E3D1WMH

Luminous Intensity Polar Plot



TEST NUMBER: P1254867

CATALOG NUMBER: P3AS13R659035DE010 E3D1WMH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	114	111	109	106	111	109	107	105	105	103	102		101	100	99		98
2	108	104	100	96	106	102	98	95	99	96	93		96	93	91		93
3	103	97	92	88	101	95	91	88	93	89	86		90	87	85		88
4	98	91	85	81	96	90	85	81	87	83	80		85	82	79		84
5	93	85	79	75	92	84	79	75	82	78	74		81	77	74		79
6	89	80	74	70	87	79	74	70	78	73	69		76	72	69		75
7	84	75	70	65	83	75	69	65	73	69	65		72	68	65		71
8	80	71	65	61	79	71	65	61	69	64	61		68	64	61		67
9	77	67	61	58	76	67	61	57	66	61	57		65	60	57		64
10	73	64	58	54	72	63	58	54	62	57	54		62	57	54		61

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	319667
5°	296830
10°	287035
15°	276619
20°	255732
25°	233022
30°	180028
35°	104346
40°	41420
45°	17645
50°	4196
55°	573
60°	439
65°	259
70°	321
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 17645 cd/sqm

TEST NUMBER: P1254867

CATALOG NUMBER: P3AS13R659035DE010 E3D1WMH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	127.2	10.7
10°-20°	339.5	28.5
20°-30°	429.7	36.0
30°-40°	244.7	20.5
40°-50°	48.6	4.1
50°-60°	2.5	0.2
60°-70°	0.7	0.1
70°-80°	0.1	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	896.4	75.1
0°-40°	1141.1	95.6
0°-60°	1192.3	99.9
0°-90°	1193.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1193.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1458	
5°	1348	127
15°	1218	340
25°	963	430
35°	390	245
45°	57	49
55°	2	3
65°	0	1
75°	0	0
85°	0	0
90°	0	

TEST NUMBER: P1254867

CATALOG NUMBER: P3AS13R659035DE010 E3D1WMH

CANDELA DISTRIBUTION (FULL):

0°	
0°	1457.8
1°	1447.0
2°	1423.5
3°	1396.0
4°	1369.1
5°	1348.5
6°	1333.3
7°	1321.0
8°	1310.2
9°	1299.4
10°	1289.1
11°	1277.9
12°	1266.1
13°	1251.9
14°	1236.7
15°	1218.5
16°	1197.0
17°	1173.4
18°	1147.9
19°	1120.9
20°	1095.9
21°	1070.4
22°	1047.4
23°	1023.4
24°	995.4
25°	963.1
26°	924.3
27°	877.7
28°	825.3
29°	769.4
30°	711.0
31°	646.8
32°	583.0
32.5°	550.2
33°	518.3
34°	453.6
35°	389.8
36°	331.0
37°	272.6
37.5°	242.7
38°	218.7
39°	177.0
40°	144.7
42.5°	89.2
45°	56.9



TEST NUMBER: P1254867

CATALOG NUMBER: P3AS13R659035DE010 E3D1WMH

CANDELA DISTRIBUTION (continued):

	0°
47.5°	33.3
50°	12.3
52.5°	2.5
55°	1.5
57.5°	1.0
60°	1.0
62.5°	1.0
65°	0.5
67.5°	0.5
70°	0.5
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)