

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1254961

Luminaire Tested: P3AS17R159035DE010 E3DLD1LI

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1254961
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-2)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS17R159035DE010 E3DLD1LI
Description: 3in Adjustable LED luminaire with, R15 optic, 3500K CCT AND, 90CRI , E3DLD1LI TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 1046.0 lumens
Efficiency: N/A
Efficacy: 49.3 lumens/watt
Spacing Criteria (0/90/45): 0.76 / 0.76 / 0.82
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 21.2
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1254961

CATALOG NUMBER: P3AS17R159035DE010 E3DLD1LI

Luminous Intensity Polar Plot



TEST NUMBER: P1254961

CATALOG NUMBER: P3AS17R159035DE010 E3DLD1LI

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	109	106	104	110	107	105	102	103	101	99		99	98	96		96
2	106	100	96	92	104	99	95	91	95	92	89		92	90	87		90
3	100	93	87	83	98	91	86	82	89	84	81		86	82	79		84
4	94	86	80	75	92	85	79	74	82	77	73		80	76	73		78
5	89	80	73	68	87	79	73	68	77	72	67		75	70	67		74
6	84	74	68	63	83	73	67	63	72	66	62		70	66	62		69
7	80	69	63	58	78	69	63	58	67	62	58		66	61	57		65
8	76	65	59	54	74	65	58	54	63	58	54		62	57	54		61
9	72	61	55	51	71	61	55	51	60	54	50		59	54	50		58
10	68	58	52	48	67	57	51	47	57	51	47		56	51	47		55

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	263839
5°	256680
10°	234576
15°	205472
20°	176252
25°	147154
30°	117765
35°	88338
40°	64092
45°	41927
50°	26234
55°	17739
60°	15700
65°	14424
70°	13592
75°	12370
80°	11744
85°	10064

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 41927 cd/sqm

TEST NUMBER: P1254961

CATALOG NUMBER: P3AS17R159035DE010 E3DLD1LI

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	107.6	10.3
10°-20°	252.2	24.1
20°-30°	277.8	26.6
30°-40°	208.1	19.9
40°-50°	107.9	10.3
50°-60°	44.7	4.3
60°-70°	27.7	2.6
70°-80°	15.5	1.5
80°-90°	4.5	0.4
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	637.6	61.0
0°-40°	845.7	80.8
0°-60°	998.3	95.4
0°-90°	1046.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1046.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1203	
5°	1166	108
15°	905	252
25°	608	278
35°	330	208
45°	135	108
55°	46	45
65°	28	28
75°	15	16
85°	4	5
90°	0	

TEST NUMBER: P1254961

CATALOG NUMBER: P3AS17R159035DE010 E3DLD1LI

CANDELA DISTRIBUTION (FULL):

0°	
0°	1203.2
1°	1204.5
2°	1200.6
3°	1192.6
4°	1180.7
5°	1166.1
6°	1147.6
7°	1127.7
8°	1103.8
9°	1078.6
10°	1053.5
12.5°	980.6
15°	905.1
17.5°	829.5
20°	755.3
22.5°	679.8
25°	608.2
27.5°	536.7
30°	465.1
32.5°	394.9
35°	330.0
37.5°	274.3
40°	223.9
42.5°	177.6
45°	135.2
47.5°	102.0
50°	76.9
52.5°	57.0
55°	46.4
57.5°	41.1
60°	35.8
62.5°	31.8
65°	27.8
67.5°	23.9
70°	21.2
72.5°	17.2
75°	14.6
77.5°	11.9
80°	9.3
82.5°	6.6
85°	4.0
87.5°	1.3
90°	0.0

(END OF REPORT)