

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1255107

Luminaire Tested: P3AS17R409035DE010 E3DL1WH

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1255107
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-21)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS17R409035DE010 E3DL1WH
Description: 3in Adjustable LED luminaire with, R40 optic, 3500K CCT AND, 90CRI , E3DL1WH TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 973.0 lumens
Efficiency: N/A
Efficacy: 45.9 lumens/watt
Spacing Criteria (0/90/45): 0.73 / 0.73 / 0.74
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 21.2
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1255107

CATALOG NUMBER: P3AS17R409035DE010 E3DL1WH

Luminous Intensity Polar Plot



TEST NUMBER: P1255107

CATALOG NUMBER: P3AS17R409035DE010 E3DL1WH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	110	108	105	111	108	106	104	104	102	100		100	99	97		97
2	107	102	98	95	105	101	97	93	97	94	91		94	92	89		92
3	102	95	90	86	100	94	89	85	91	87	84		89	85	83		86
4	97	89	83	79	95	88	83	79	86	81	78		84	80	77		82
5	92	83	77	73	90	82	77	73	81	76	72		79	75	71		77
6	87	78	72	68	86	78	72	68	76	71	67		75	70	67		73
7	83	74	68	64	82	73	68	64	72	67	63		71	66	63		70
8	79	70	64	60	78	69	64	60	68	63	59		67	63	59		66
9	76	66	60	56	75	66	60	56	65	60	56		64	59	56		63
10	72	63	57	53	71	62	57	53	62	57	53		61	56	53		60

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	302980
5°	296830
10°	276370
15°	240887
20°	194127
25°	145508
30°	102294
35°	67030
40°	40562
45°	24251
50°	14464
55°	11660
60°	10438
65°	8924
70°	8463
75°	6693
80°	6693
85°	6542

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 24251 cd/sqm

TEST NUMBER: P1255107

CATALOG NUMBER: P3AS17R409035DE010 E3DL1WH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	125.2	12.9
10°-20°	292.3	30.0
20°-30°	275.4	28.3
30°-40°	159.2	16.4
40°-50°	63.5	6.5
50°-60°	28.1	2.9
60°-70°	17.4	1.8
70°-80°	9.1	0.9
80°-90°	2.9	0.3
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	692.9	71.2
0°-40°	852.1	87.6
0°-60°	943.7	97.0
0°-90°	973.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	973.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1382	
5°	1348	125
15°	1061	292
25°	601	275
35°	250	159
45°	78	63
55°	30	28
65°	17	17
75°	8	9
85°	3	3
90°	0	

TEST NUMBER: P1255107

CATALOG NUMBER: P3AS17R409035DE010 E3DL1WH

CANDELA DISTRIBUTION (FULL):

0°	
0°	1381.7
2.5°	1373.7
5°	1348.5
7.5°	1302.2
10°	1241.2
12.5°	1159.1
15°	1061.1
17.5°	951.1
20°	831.9
22.5°	712.7
25°	601.4
27.5°	498.1
30°	404.0
32.5°	321.9
35°	250.4
37.5°	189.4
40°	141.7
42.5°	106.0
45°	78.2
47.5°	57.0
50°	42.4
52.5°	34.4
55°	30.5
57.5°	27.8
60°	23.8
62.5°	19.9
65°	17.2
67.5°	14.6
70°	13.2
72.5°	10.6
75°	7.9
77.5°	6.6
80°	5.3
82.5°	4.0
85°	2.6
87.5°	1.3
90°	0.0

(END OF REPORT)