

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1255129

Luminaire Tested: P3AS17R459035DE010 E3DL1H

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1255129
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-27)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS17R459035DE010 E3DL1H
Description: 3in Adjustable LED luminaire with, R45 optic, 3500K CCT AND, 90CRI , E3DL1H TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 1481.0 lumens
Efficiency: N/A
Efficacy: 69.9 lumens/watt
Spacing Criteria (0/90/45): 0.69 / 0.69 / 0.69
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 21.2
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1255129

CATALOG NUMBER: P3AS17R459035DE010 E3DL1H

Luminous Intensity Polar Plot



TEST NUMBER: P1255129

CATALOG NUMBER: P3AS17R459035DE010 E3DL1H

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	114	111	109	107	111	109	107	105	105	103	102		101	100	99		98
2	109	104	100	97	106	102	99	96	99	96	94		96	94	92		93
3	104	98	93	89	102	96	92	88	94	90	87		91	88	86		89
4	99	92	87	83	97	91	86	82	89	85	81		87	83	80		85
5	94	87	81	77	93	86	81	77	84	80	76		82	79	76		81
6	90	82	77	73	89	81	76	72	80	75	72		78	74	71		77
7	86	78	72	68	85	77	72	68	76	71	68		75	71	67		74
8	83	74	68	65	82	73	68	65	72	68	64		71	67	64		70
9	79	70	65	61	78	70	65	61	69	64	61		68	64	61		67
10	76	67	62	58	75	67	62	58	66	61	58		65	61	58		65

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	556162
5°	543142
10°	499278
15°	423044
20°	328235
25°	229441
30°	144529
35°	85099
40°	48147
45°	23413
50°	8119
55°	6576
60°	6403
65°	6174
70°	5963
75°	5592
80°	5051
85°	3271

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 23413 cd/sqm

TEST NUMBER: P1255129

CATALOG NUMBER: P3AS17R459035DE010 E3DL1H

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	228.4	15.4
10°-20°	511.7	34.6
20°-30°	434.5	29.3
30°-40°	207.3	14.0
40°-50°	62.4	4.2
50°-60°	15.8	1.1
60°-70°	11.8	0.8
70°-80°	7.0	0.5
80°-90°	2.0	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1174.7	79.3
0°-40°	1382.0	93.3
0°-60°	1460.2	98.6
0°-90°	1481.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1481.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2536	
5°	2468	228
15°	1864	512
25°	948	435
35°	318	207
45°	76	62
55°	17	16
65°	12	12
75°	7	7
85°	1	2
90°	0	

TEST NUMBER: P1255129

CATALOG NUMBER: P3AS17R459035DE010 E3DL1H

CANDELA DISTRIBUTION (FULL):

	0°
0°	2536.3
2.5°	2520.4
5°	2467.5
7.5°	2376.1
10°	2242.3
12.5°	2064.8
15°	1863.5
17.5°	1639.7
20°	1406.6
22.5°	1169.5
25°	948.3
27.5°	747.0
30°	570.8
32.5°	429.1
35°	317.9
37.5°	234.4
40°	168.2
42.5°	116.6
45°	75.5
47.5°	42.4
50°	23.8
52.5°	18.5
55°	17.2
57.5°	15.9
60°	14.6
62.5°	13.2
65°	11.9
67.5°	10.6
70°	9.3
72.5°	7.9
75°	6.6
77.5°	5.3
80°	4.0
82.5°	2.6
85°	1.3
87.5°	1.3
90°	0.0

(END OF REPORT)