

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1255181

Luminaire Tested: P3AS17R559035DE010 E3D1H

Issue Date: 1/29/2026

Test Information

Test Method: LM-79-2019
Report Number: P1255181
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2501-338-14)
Test Lab: INNOVATION CENTER
Issue Date: 1/29/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS17R559035DE010 E3D1H
Description: 3in Adjustable LED luminaire with, R55 optic, 3500K CCT AND, 90CRI , E3D1H TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 1709.9 lumens
Efficiency: N/A
Efficacy: 80.7 lumens/watt
Spacing Criteria (0/90/45): 0.93 / 0.93 / 0.82
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 21.2
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1255181

CATALOG NUMBER: P3AS17R559035DE010 E3D1H

Luminous Intensity Polar Plot



TEST NUMBER: P1255181

CATALOG NUMBER: P3AS17R559035DE010 E3D1H

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	114	111	109	107	112	109	107	105	105	104	102		102	100	99		98
2	109	105	101	98	107	103	100	97	100	97	95		97	95	93		94
3	104	98	94	90	102	97	93	90	95	91	88		92	89	87		90
4	100	93	88	84	98	92	87	84	90	86	83		88	84	82		86
5	95	88	83	79	94	87	82	78	85	81	78		84	80	77		82
6	91	83	78	74	90	82	77	74	81	76	73		80	76	73		78
7	87	79	73	70	86	78	73	69	77	72	69		76	72	69		75
8	83	75	69	66	82	74	69	66	73	69	65		72	68	65		71
9	80	71	66	62	79	71	66	62	70	65	62		69	65	62		68
10	77	68	62	59	76	67	62	59	67	62	59		66	62	59		65

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	495881
5°	478317
10°	495426
15°	488448
20°	452053
25°	365610
30°	219097
35°	74258
40°	20467
45°	9055
50°	2661
55°	497
60°	263
65°	311
70°	385
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 9055 cd/sqm

TEST NUMBER: P1255181

CATALOG NUMBER: P3AS17R559035DE010 E3D1H

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	210.2	12.3
10°-20°	599.0	35.0
20°-30°	665.9	38.9
30°-40°	207.3	12.1
40°-50°	24.9	1.5
50°-60°	1.9	0.1
60°-70°	0.6	0.0
70°-80°	0.1	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1475.2	86.3
0°-40°	1682.5	98.4
0°-60°	1709.2	100.0
0°-90°	1709.9	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1709.9	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2261	
5°	2173	210
15°	2152	599
25°	1511	666
35°	277	207
45°	29	25
55°	1	2
65°	1	1
75°	0	0
85°	0	0
90°	0	

TEST NUMBER: P1255181

CATALOG NUMBER: P3AS17R559035DE010 E3D1H

CANDELA DISTRIBUTION (FULL):

0°	
0°	2261.4
1°	2253.0
2°	2230.9
3°	2203.6
4°	2178.9
5°	2173.0
6°	2179.5
7°	2193.2
8°	2208.8
9°	2221.1
10°	2225.0
11°	2222.4
12°	2212.0
13°	2195.8
14°	2176.9
15°	2151.6
16°	2122.4
17°	2085.3
18°	2043.8
19°	1993.7
20°	1937.2
21°	1872.9
22°	1796.9
23°	1713.1
24°	1617.0
25°	1511.1
26°	1394.8
27°	1271.3
28°	1139.5
29°	1003.7
30°	865.3
31°	726.3
32°	590.5
32.5°	530.1
33°	467.7
34°	361.8
35°	277.4
36°	211.1
37°	156.6
37.5°	133.8
38°	116.3
39°	88.4
40°	71.5
42.5°	45.5
45°	29.2

TEST NUMBER: P1255181

CATALOG NUMBER: P3AS17R559035DE010 E3D1H

CANDELA DISTRIBUTION (continued):

	0°
47.5°	17.5
50°	7.8
52.5°	2.6
55°	1.3
57.5°	0.6
60°	0.6
62.5°	0.6
65°	0.6
67.5°	0.6
70°	0.6
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)