

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1255460

Luminaire Tested: P3AS20R409035D010 E3DLP1GPH

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1255460
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-21)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS20R409035D010 E3DLP1GPH
Description: 3in Adjustable LED luminaire with, R40 optic, 3500K CCT AND, 90CRI , E3DLP1GPH TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 626.0 lumens
Efficiency: N/A
Efficacy: 21.7 lumens/watt
Spacing Criteria (0/90/45): 0.73 / 0.73 / 0.74
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 28.8
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1255460

CATALOG NUMBER: P3AS20R409035D010 E3DLP1GPH

Luminous Intensity Polar Plot



TEST NUMBER: P1255460

CATALOG NUMBER: P3AS20R409035D010 E3DLP1GPH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	110	108	105	111	108	106	104	104	102	100		100	99	97		97
2	107	102	98	95	105	101	97	93	97	94	91		94	92	89		92
3	102	95	90	86	100	94	89	85	91	87	84		89	85	83		86
4	97	89	83	79	95	88	83	79	86	81	78		84	80	77		82
5	92	83	77	73	90	82	77	73	81	76	72		79	75	71		77
6	87	78	72	68	86	78	72	68	76	71	67		75	70	67		73
7	83	74	68	64	82	73	68	63	72	67	63		71	66	63		70
8	79	70	64	60	78	69	64	60	68	63	59		67	63	59		66
9	76	66	60	56	75	66	60	56	65	60	56		64	59	56		63
10	72	63	57	53	71	62	57	53	62	57	53		61	56	53		60

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	194919
5°	190975
10°	177819
15°	154984
20°	124891
25°	93610
30°	65808
35°	43125
40°	26106
45°	15599
50°	9313
55°	7493
60°	6710
65°	5759
70°	5450
75°	4321
80°	4293
85°	4277

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 15599 cd/sqm

TEST NUMBER: P1255460

CATALOG NUMBER: P3AS20R409035D010 E3DLP1GPH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	80.6	12.9
10°-20°	188.0	30.0
20°-30°	177.2	28.3
30°-40°	102.5	16.4
40°-50°	40.8	6.5
50°-60°	18.1	2.9
60°-70°	11.2	1.8
70°-80°	5.8	0.9
80°-90°	1.9	0.3
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	445.8	71.2
0°-40°	548.2	87.6
0°-60°	607.1	97.0
0°-90°	626.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	626.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	889	
5°	868	81
15°	683	188
25°	387	177
35°	161	102
45°	50	41
55°	20	18
65°	11	11
75°	5	6
85°	2	2
90°	0	

TEST NUMBER: P1255460

CATALOG NUMBER: P3AS20R409035D010 E3DLP1GPH

CANDELA DISTRIBUTION (FULL):

0°	
0°	888.9
2.5°	883.8
5°	867.6
7.5°	837.8
10°	798.6
12.5°	745.7
15°	682.7
17.5°	611.9
20°	535.2
22.5°	458.5
25°	386.9
27.5°	320.5
30°	259.9
32.5°	207.1
35°	161.1
37.5°	121.9
40°	91.2
42.5°	68.2
45°	50.3
47.5°	36.6
50°	27.3
52.5°	22.2
55°	19.6
57.5°	17.9
60°	15.3
62.5°	12.8
65°	11.1
67.5°	9.4
70°	8.5
72.5°	6.8
75°	5.1
77.5°	4.3
80°	3.4
82.5°	2.6
85°	1.7
87.5°	0.9
90°	0.0

(END OF REPORT)