

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1256528

Luminaire Tested: P3AS05R209040DE010 E3D1B

Issue Date: 1/29/2026

Test Information

Test Method: LM-79-2019
Report Number: P1256528
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2501-338-8)
Test Lab: INNOVATION CENTER
Issue Date: 1/29/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS05R209040DE010 E3D1B
Description: 3in Adjustable LED luminaire with, R20 optic, 4000K CCT AND, 90CRI , E3D1B TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 675.1 lumens
Efficiency: N/A
Efficacy: 93.8 lumens/watt
Spacing Criteria (0/90/45): 0.35 / 0.35 / 0.34
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 7.2
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1256528

CATALOG NUMBER: P3AS05R209040DE010 E3D1B

Luminous Intensity Polar Plot



TEST NUMBER: P1256528

CATALOG NUMBER: P3AS05R209040DE010 E3D1B

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	115	114	112	110	113	111	110	108	107	106	105		104	103	102		100
2	112	109	106	104	110	107	105	103	104	102	101		101	100	98		99
3	109	105	102	99	107	104	101	98	101	99	97		99	97	95		97
4	106	101	98	95	105	100	97	95	99	96	94		97	94	93		95
5	104	98	95	92	102	98	94	92	96	93	91		95	92	90		93
6	101	96	92	89	100	95	92	89	94	91	89		93	90	88		92
7	99	93	90	87	98	93	89	87	92	89	86		91	88	86		90
8	97	91	87	85	96	91	87	85	90	87	85		89	86	84		88
9	95	89	85	83	94	89	85	83	88	85	83		87	84	82		87
10	93	87	84	81	92	87	83	81	86	83	81		86	83	81		85

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	1023931
5°	862093
10°	538467
15°	201318
20°	69096
25°	28792
30°	13572
35°	6077
40°	2863
45°	1489
50°	546
55°	115
60°	132
65°	156
70°	0
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 1489 cd/sqm

TEST NUMBER: P1256528

CATALOG NUMBER: P3AS05R209040DE010 E3D1B

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	325.7	48.2
10°-20°	268.3	39.7
20°-30°	61.0	9.0
30°-40°	15.5	2.3
40°-50°	3.9	0.6
50°-60°	0.5	0.1
60°-70°	0.2	0.0
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	654.9	97.0
0°-40°	670.4	99.3
0°-60°	674.9	100.0
0°-90°	675.1	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	675.1	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	4670	
5°	3916	326
15°	887	268
25°	119	61
35°	23	16
45°	5	4
55°	0	1
65°	0	0
75°	0	0
85°	0	0
90°	0	

TEST NUMBER: P1256528

CATALOG NUMBER: P3AS05R209040DE010 E3D1B

CANDELA DISTRIBUTION (FULL):

0°	
0°	4669.5
1°	4629.9
2°	4513.2
3°	4345.9
4°	4140.6
5°	3916.5
6°	3666.8
7°	3391.3
8°	3069.9
9°	2751.3
10°	2418.3
11°	2063.8
12°	1709.9
13°	1410.1
14°	1123.5
15°	886.8
16°	699.9
17°	552.1
18°	443.6
19°	360.8
20°	296.1
21°	247.6
22°	206.6
23°	171.8
24°	143.3
25°	119.0
27.5°	77.9
30°	53.6
32.5°	33.0
35°	22.7
37.5°	14.5
40°	10.0
42.5°	6.9
45°	4.8
47.5°	3.2
50°	1.6
52.5°	0.8
55°	0.3
57.5°	0.3
60°	0.3
62.5°	0.3
65°	0.3
67.5°	0.0
70°	0.0
72.5°	0.0

TEST NUMBER: P1256528

CATALOG NUMBER: P3AS05R209040DE010 E3D1B

CANDELA DISTRIBUTION (continued):

	0°
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)