

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1257178

Luminaire Tested: P3AS09R659040DE010 E3DLD1WH

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1257178
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-42)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS09R659040DE010 E3DLD1WH
Description: 3in Adjustable LED luminaire with, R65 optic, 4000K CCT AND, 90CRI , E3DLD1WH TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 620.0 lumens
Efficiency: N/A
Efficacy: 55.9 lumens/watt
Spacing Criteria (0/90/45): 0.94 / 0.94 / 1
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 11.1
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1257178

CATALOG NUMBER: P3AS09R659040DE010 E3DLD1WH

Luminous Intensity Polar Plot



TEST NUMBER: P1257178

CATALOG NUMBER: P3AS09R659040DE010 E3DLD1WH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	112	109	106	103	110	107	104	101	102	100	98		99	97	95		95
2	105	99	94	90	103	97	93	89	94	90	87		91	88	85		88
3	99	91	85	80	96	89	84	79	87	82	78		84	80	77		82
4	92	83	77	72	90	82	76	71	80	75	70		78	73	70		76
5	87	77	70	65	85	76	69	65	74	68	64		72	67	63		71
6	82	71	64	59	80	70	64	59	69	63	58		67	62	58		66
7	77	66	59	54	75	65	59	54	64	58	54		63	57	53		61
8	72	61	55	50	71	61	54	50	60	54	49		59	53	49		58
9	68	57	51	46	67	57	50	46	56	50	46		55	49	46		54
10	65	54	47	43	64	53	47	43	52	47	43		52	46	42		51

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	110342
5°	108848
10°	105186
15°	99206
20°	91498
25°	83061
30°	73581
35°	62613
40°	49808
45°	35166
50°	20400
55°	11125
60°	10350
65°	9391
70°	8591
75°	7964
80°	6945
85°	6038

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 35166 cd/sqm

TEST NUMBER: P1257178

CATALOG NUMBER: P3AS09R659040DE010 E3DLD1WH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	46.5	7.5
10°-20°	122.3	19.7
20°-30°	157.1	25.3
30°-40°	145.4	23.4
40°-50°	87.7	14.2
50°-60°	29.9	4.8
60°-70°	18.0	2.9
70°-80°	10.2	1.6
80°-90°	2.9	0.5
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	325.9	52.6
0°-40°	471.2	76.0
0°-60°	588.9	95.0
0°-90°	620.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	620.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	503	
5°	494	47
15°	437	122
25°	343	157
35°	234	145
45°	113	88
55°	29	30
65°	18	18
75°	9	10
85°	2	3
90°	0	

TEST NUMBER: P1257178

CATALOG NUMBER: P3AS09R659040DE010 E3DLD1WH

CANDELA DISTRIBUTION (FULL):

0°	
0°	503.2
2.5°	500.8
5°	494.5
7.5°	485.0
10°	472.4
12.5°	456.7
15°	437.0
17.5°	415.8
20°	392.1
22.5°	367.7
25°	343.3
27.5°	317.3
30°	290.6
32.5°	263.8
35°	233.9
37.5°	204.7
40°	174.0
42.5°	143.3
45°	113.4
47.5°	85.8
50°	59.8
52.5°	37.8
55°	29.1
57.5°	26.0
60°	23.6
62.5°	20.5
65°	18.1
67.5°	15.7
70°	13.4
72.5°	11.8
75°	9.4
77.5°	7.9
80°	5.5
82.5°	3.9
85°	2.4
87.5°	1.6
90°	0.0

(END OF REPORT)