

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1257207

Luminaire Tested: P3AS09R709040DE010 E3DLP1WH

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1257207
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-47)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS09R709040DE010 E3DLP1WH
Description: 3in Adjustable LED luminaire with, R70 optic, 4000K CCT AND, 90CRI , E3DLP1WH TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 793.0 lumens
Efficiency: N/A
Efficacy: 71.4 lumens/watt
Spacing Criteria (0/90/45): 0.97 / 0.97 / 0.98
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 11.1
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1257207

CATALOG NUMBER: P3AS09R709040DE010 E3DLP1WH

Luminous Intensity Polar Plot



TEST NUMBER: P1257207

CATALOG NUMBER: P3AS09R709040DE010 E3DLP1WH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	110	107	104	110	107	105	103	103	101	100		100	98	97		96
2	106	101	96	93	104	99	95	92	96	92	90		93	90	88		90
3	100	93	88	83	98	92	87	82	89	85	81		86	83	80		84
4	94	86	80	75	93	85	79	75	83	78	74		81	76	73		79
5	89	80	73	69	87	79	73	68	77	72	68		75	71	67		74
6	84	74	68	63	82	73	67	63	72	66	62		70	65	62		69
7	79	69	62	58	78	68	62	58	67	61	57		66	61	57		65
8	75	65	58	53	74	64	58	53	63	57	53		62	57	53		61
9	71	60	54	50	70	60	54	50	59	53	49		58	53	49		57
10	67	57	50	46	66	56	50	46	55	50	46		55	49	46		54

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	153518
5°	151684
10°	147292
15°	141045
20°	132125
25°	120031
30°	103687
35°	82637
40°	60198
45°	39570
50°	18524
55°	5735
60°	5526
65°	5292
70°	5065
75°	5338
80°	4925
85°	4026

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 39570 cd/sqm

TEST NUMBER: P1257207

CATALOG NUMBER: P3AS09R709040DE010 E3DLP1WH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	64.9	8.2
10°-20°	173.9	21.9
20°-30°	226.0	28.5
30°-40°	191.8	24.2
40°-50°	98.9	12.5
50°-60°	19.1	2.4
60°-70°	10.3	1.3
70°-80°	6.3	0.8
80°-90°	1.8	0.2
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	464.8	58.6
0°-40°	656.6	82.8
0°-60°	774.5	97.7
0°-90°	793.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	793.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	700	
5°	689	65
15°	621	174
25°	496	226
35°	309	192
45°	128	99
55°	15	19
65°	10	10
75°	6	6
85°	2	2
90°	0	

TEST NUMBER: P1257207

CATALOG NUMBER: P3AS09R709040DE010 E3DLP1WH

CANDELA DISTRIBUTION (FULL):

0°	
0°	700.1
2.5°	697.7
5°	689.1
7.5°	676.5
10°	661.5
12.5°	642.6
15°	621.3
17.5°	595.4
20°	566.2
22.5°	533.1
25°	496.1
27.5°	454.4
30°	409.5
32.5°	359.9
35°	308.7
37.5°	258.3
40°	210.3
42.5°	165.4
45°	127.6
47.5°	93.7
50°	54.3
52.5°	23.6
55°	15.0
57.5°	14.2
60°	12.6
62.5°	11.8
65°	10.2
67.5°	9.5
70°	7.9
72.5°	7.1
75°	6.3
77.5°	4.7
80°	3.9
82.5°	2.4
85°	1.6
87.5°	0.8
90°	0.0

(END OF REPORT)