

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1257573

Luminaire Tested: P3AS13R659040DE010 E3D1WH

Issue Date: 1/29/2026

Test Information

Test Method: LM-79-2019
Report Number: P1257573
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2501-338-16)
Test Lab: INNOVATION CENTER
Issue Date: 1/29/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS13R659040DE010 E3D1WH
Description: 3in Adjustable LED luminaire with, R65 optic, 4000K CCT AND, 90CRI , E3D1WH TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 1247.0 lumens
Efficiency: N/A
Efficacy: 85.4 lumens/watt
Spacing Criteria (0/90/45): 0.92 / 0.92 / 0.88
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 14.6
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1257573

CATALOG NUMBER: P3AS13R659040DE010 E3D1WH

Luminous Intensity Polar Plot



TEST NUMBER: P1257573

CATALOG NUMBER: P3AS13R659040DE010 E3D1WH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	114	111	109	106	111	109	107	105	105	103	102		101	100	99		98
2	108	104	100	96	106	102	98	95	99	96	93		96	93	91		93
3	103	97	92	88	101	95	91	88	93	89	86		90	87	85		88
4	98	91	85	81	96	90	85	81	87	83	80		85	82	79		84
5	93	85	79	75	92	84	79	75	82	78	74		81	77	74		79
6	89	80	74	70	87	79	74	70	78	73	69		76	72	69		75
7	84	75	70	65	83	75	69	65	73	69	65		72	68	65		71
8	80	71	65	61	79	71	65	61	69	64	61		68	64	61		67
9	77	67	61	58	76	67	61	57	66	61	57		65	60	57		64
10	73	64	58	54	72	63	58	54	62	57	54		62	57	54		61

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	334140
5°	310257
10°	300039
15°	289150
20°	267307
25°	243546
30°	188181
35°	109085
40°	43281
45°	18452
50°	4367
55°	573
60°	439
65°	259
70°	321
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 18452 cd/sqm

TEST NUMBER: P1257573

CATALOG NUMBER: P3AS13R659040DE010 E3D1WH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	132.9	10.7
10°-20°	354.9	28.5
20°-30°	449.2	36.0
30°-40°	255.8	20.5
40°-50°	50.8	4.1
50°-60°	2.6	0.2
60°-70°	0.7	0.1
70°-80°	0.1	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	937.0	75.1
0°-40°	1192.8	95.7
0°-60°	1246.3	99.9
0°-90°	1247.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1247.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1524	
5°	1410	133
15°	1274	355
25°	1007	449
35°	408	256
45°	60	51
55°	2	3
65°	0	1
75°	0	0
85°	0	0
90°	0	

TEST NUMBER: P1257573

CATALOG NUMBER: P3AS13R659040DE010 E3D1WH

CANDELA DISTRIBUTION (FULL):

0°	
0°	1523.8
1°	1512.5
2°	1487.9
3°	1459.2
4°	1431.0
5°	1409.5
6°	1393.6
7°	1380.8
8°	1369.5
9°	1358.3
10°	1347.5
11°	1335.7
12°	1323.4
13°	1308.5
14°	1292.6
15°	1273.7
16°	1251.1
17°	1226.5
18°	1199.9
19°	1171.7
20°	1145.5
21°	1118.9
22°	1094.8
23°	1069.7
24°	1040.5
25°	1006.6
26°	966.2
27°	917.5
28°	862.6
29°	804.2
30°	743.2
31°	676.1
32°	609.4
32.5°	575.1
33°	541.8
34°	474.1
35°	407.5
36°	346.0
37°	285.0
37.5°	253.7
38°	228.6
39°	185.0
40°	151.2
42.5°	93.3
45°	59.5



TEST NUMBER: P1257573

CATALOG NUMBER: P3AS13R659040DE010 E3D1WH

CANDELA DISTRIBUTION (continued):

	0°
47.5°	34.9
50°	12.8
52.5°	2.6
55°	1.5
57.5°	1.0
60°	1.0
62.5°	1.0
65°	0.5
67.5°	0.5
70°	0.5
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)