

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1257600

Luminaire Tested: P3AS13R709040DE010 E3D1LI

Issue Date: 1/29/2026

Test Information

Test Method: LM-79-2019
Report Number: P1257600
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2501-338-17)
Test Lab: INNOVATION CENTER
Issue Date: 1/29/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS13R709040DE010 E3D1LI
Description: 3in Adjustable LED luminaire with, R70 optic, 4000K CCT AND, 90CRI , E3D1LI TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 1247.0 lumens
Efficiency: N/A
Efficacy: 85.4 lumens/watt
Spacing Criteria (0/90/45): 1.02 / 1.02 / 1.06
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 14.6
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1257600

CATALOG NUMBER: P3AS13R709040DE010 E3D1LI

Luminous Intensity Polar Plot



TEST NUMBER: P1257600

CATALOG NUMBER: P3AS13R709040DE010 E3D1LI

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	110	108	105	111	108	106	104	104	102	100		100	99	97		97
2	107	102	98	94	105	100	96	93	97	94	91		94	91	89		91
3	101	94	89	85	99	93	88	84	90	86	83		88	84	81		86
4	95	87	81	77	94	86	81	77	84	79	76		82	78	75		80
5	90	81	75	70	88	80	74	70	78	73	69		77	72	69		75
6	85	75	69	64	83	75	69	64	73	68	64		72	67	63		70
7	80	70	64	59	79	70	63	59	68	63	59		67	62	58		66
8	76	66	59	55	75	65	59	55	64	58	54		63	58	54		62
9	72	61	55	51	71	61	55	51	60	54	50		59	54	50		58
10	68	58	51	47	67	57	51	47	56	51	47		55	50	47		55

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	242481
5°	228637
10°	216785
15°	212896
20°	205211
25°	193439
30°	192055
35°	167254
40°	108203
45°	51137
50°	7164
55°	573
60°	439
65°	519
70°	321
75°	424
80°	631
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 51137 cd/sqm

TEST NUMBER: P1257600

CATALOG NUMBER: P3AS13R709040DE010 E3D1LI

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	97.0	7.8
10°-20°	263.4	21.1
20°-30°	372.6	29.9
30°-40°	374.4	30.0
40°-50°	134.6	10.8
50°-60°	3.6	0.3
60°-70°	0.8	0.1
70°-80°	0.5	0.0
80°-90°	0.1	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	732.9	58.8
0°-40°	1107.3	88.8
0°-60°	1245.6	99.9
0°-90°	1247.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1247.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1106	
5°	1039	97
15°	938	263
25°	800	373
35°	625	374
45°	165	135
55°	2	4
65°	1	1
75°	0	1
85°	0	0
90°	0	

TEST NUMBER: P1257600

CATALOG NUMBER: P3AS13R709040DE010 E3D1LI

CANDELA DISTRIBUTION (FULL):

0°	
0°	1105.8
1°	1102.7
2°	1093.0
3°	1077.6
4°	1058.1
5°	1038.7
6°	1020.2
7°	1005.9
8°	993.1
9°	982.8
10°	973.6
11°	965.9
12°	958.8
13°	951.6
14°	944.9
15°	937.8
16°	929.1
17°	919.8
18°	908.6
19°	894.7
20°	879.4
21°	862.5
22°	845.6
23°	829.2
24°	813.3
25°	799.5
26°	789.8
27°	782.1
28°	775.9
29°	768.8
30°	758.5
31°	743.7
32°	722.7
32.5°	710.9
33°	695.0
34°	663.8
35°	624.8
36°	581.8
37°	533.2
37.5°	510.6
38°	479.9
39°	425.1
40°	378.0
42.5°	261.7
45°	164.9



TEST NUMBER: P1257600

CATALOG NUMBER: P3AS13R709040DE010 E3D1LI

CANDELA DISTRIBUTION (continued):

	0°
47.5°	88.6
50°	21.0
52.5°	2.6
55°	1.5
57.5°	1.5
60°	1.0
62.5°	1.0
65°	1.0
67.5°	0.5
70°	0.5
72.5°	0.5
75°	0.5
77.5°	0.5
80°	0.5
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)