

Scaled data based on original data using  
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-  
State Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1257642

Luminaire Tested: P3AS17R129040DE010 E3DLP1H

Issue Date: 1/30/2026

**Test Information**

Test Method: LM-79-2019  
Report Number: P1257642  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-1)  
Test Lab: INNOVATION CENTER  
Issue Date: 1/30/2026  
Manufacturer: COOPER LIGHTING SOLUTIONS  
Product Line: IRiS  
Catalog Number: P3AS17R129040DE010 E3DLP1H  
Description: 3in Adjustable LED luminaire with, R12 optic, 4000K CCT AND, 90CRI , E3DLP1H TRIM  
Light Source: -  
Ballast/Driver: -

**Summary**


Lumens per Lamp: N/A  
Luminaire Lumens: 705.0 lumens  
Efficiency: N/A  
Efficacy: 30.8 lumens/watt  
Spacing Criteria (0/90/45): 0.52 / 0.52 / 0.61  
Luminous Opening: Circular (Dia: 0.25' x H: 0')  
CIE Type: Direct

Input Watts (W): 22.9  
Input Voltage (V): NR  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 24 FT

TEST NUMBER: P1257642

CATALOG NUMBER: P3AS17R129040DE010 E3DLP1H

### Luminous Intensity Polar Plot



TEST NUMBER: P1257642

CATALOG NUMBER: P3AS17R129040DE010 E3DLP1H

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

|     |     |     |     |     |     |     |     |     |     |     |     |  |     |     |     |  |     |
|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|--|-----|-----|-----|--|-----|
| RF  | 20  |     |     |     | 20  |     |     |     | 20  |     |     |  | 20  |     |     |  | 20  |
| RC  | 80  |     |     |     | 70  |     |     |     | 50  |     |     |  | 30  |     |     |  | 10  |
| RW  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 50  | 30  | 10  |  | 50  | 30  | 10  |  | 50  |
| RCR |     |     |     |     |     |     |     |     |     |     |     |  |     |     |     |  |     |
| 0   | 119 | 119 | 119 | 119 | 116 | 116 | 116 | 116 | 111 | 111 | 111 |  | 106 | 106 | 106 |  | 102 |
| 1   | 113 | 110 | 108 | 106 | 111 | 108 | 106 | 104 | 104 | 102 | 101 |  | 100 | 99  | 98  |  | 97  |
| 2   | 108 | 103 | 98  | 95  | 105 | 101 | 97  | 94  | 98  | 95  | 92  |  | 95  | 92  | 90  |  | 92  |
| 3   | 102 | 96  | 91  | 87  | 100 | 94  | 90  | 86  | 92  | 88  | 85  |  | 89  | 86  | 83  |  | 87  |
| 4   | 97  | 90  | 84  | 80  | 95  | 88  | 83  | 79  | 86  | 82  | 78  |  | 84  | 81  | 78  |  | 82  |
| 5   | 93  | 84  | 78  | 74  | 91  | 83  | 78  | 74  | 81  | 77  | 73  |  | 80  | 76  | 72  |  | 78  |
| 6   | 88  | 79  | 73  | 69  | 87  | 79  | 73  | 69  | 77  | 72  | 69  |  | 76  | 71  | 68  |  | 74  |
| 7   | 84  | 75  | 69  | 65  | 83  | 74  | 69  | 65  | 73  | 68  | 64  |  | 72  | 67  | 64  |  | 71  |
| 8   | 80  | 71  | 65  | 61  | 79  | 71  | 65  | 61  | 69  | 64  | 61  |  | 68  | 64  | 61  |  | 67  |
| 9   | 77  | 68  | 62  | 58  | 76  | 67  | 62  | 58  | 66  | 61  | 58  |  | 65  | 61  | 57  |  | 64  |
| 10  | 74  | 64  | 59  | 55  | 73  | 64  | 59  | 55  | 63  | 58  | 55  |  | 62  | 58  | 55  |  | 62  |

**AVERAGE LUMINANCE (cd/sqm):**

|     |        |
|-----|--------|
|     | 0°     |
| 0°  | 304011 |
| 5°  | 280981 |
| 10° | 224333 |
| 15° | 169445 |
| 20° | 129045 |
| 25° | 98328  |
| 30° | 70441  |
| 35° | 45963  |
| 40° | 28196  |
| 45° | 17056  |
| 50° | 11326  |
| 55° | 8755   |
| 60° | 7543   |
| 65° | 6538   |
| 70° | 5898   |
| 75° | 5846   |
| 80° | 4293   |
| 85° | 2768   |

**MAXIMUM LUMINANCE 45°-90°:**

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 17056 cd/sqm

TEST NUMBER: P1257642

CATALOG NUMBER: P3AS17R129040DE010 E3DLP1H

**ZONAL LUMENS:**

| Zone      | Lumens | % Fixture |
|-----------|--------|-----------|
| 0°-10°    | 113.1  | 16.0      |
| 10°-20°   | 208.6  | 29.6      |
| 20°-30°   | 185.7  | 26.3      |
| 30°-40°   | 109.9  | 15.6      |
| 40°-50°   | 45.1   | 6.4       |
| 50°-60°   | 21.2   | 3.0       |
| 60°-70°   | 12.9   | 1.8       |
| 70°-80°   | 6.8    | 1.0       |
| 80°-90°   | 1.7    | 0.2       |
| 90°-100°  | 0.0    | 0.0       |
| 100°-110° | 0.0    | 0.0       |
| 110°-120° | 0.0    | 0.0       |
| 120°-130° | 0.0    | 0.0       |
| 130°-140° | 0.0    | 0.0       |
| 140°-150° | 0.0    | 0.0       |
| 150°-160° | 0.0    | 0.0       |
| 160°-170° | 0.0    | 0.0       |
| 170°-180° | 0.0    | 0.0       |
| <hr/>     |        |           |
| 0°-30°    | 507.4  | 72.0      |
| 0°-40°    | 617.4  | 87.6      |
| 0°-60°    | 683.7  | 97.0      |
| 0°-90°    | 705.0  | 100.0     |
| 90°-120°  | 0.0    | 0.0       |
| 90°-150°  | 0.0    | 0.0       |
| 90°-180°  | 0.0    | 0.0       |
| 0°-180°   | 705.0  | 100.0     |

**CANDELA DISTRIBUTION:**

|     | 0°   | Flux |
|-----|------|------|
| 0°  | 1386 |      |
| 5°  | 1276 | 113  |
| 15° | 746  | 209  |
| 25° | 406  | 186  |
| 35° | 172  | 110  |
| 45° | 55   | 45   |
| 55° | 23   | 21   |
| 65° | 13   | 13   |
| 75° | 7    | 7    |
| 85° | 1    | 2    |
| 90° | 0    |      |

TEST NUMBER: P1257642

CATALOG NUMBER: P3AS17R129040DE010 E3DLP1H

**CANDELA DISTRIBUTION (FULL):**

| 0°    |        |
|-------|--------|
| 0°    | 1386.4 |
| 1°    | 1383.0 |
| 2°    | 1372.7 |
| 3°    | 1352.1 |
| 4°    | 1317.7 |
| 5°    | 1276.5 |
| 6°    | 1231.9 |
| 7°    | 1179.2 |
| 8°    | 1124.2 |
| 9°    | 1068.1 |
| 10°   | 1007.5 |
| 12.5° | 868.9  |
| 15°   | 746.4  |
| 17.5° | 641.1  |
| 20°   | 553.0  |
| 22.5° | 475.1  |
| 25°   | 406.4  |
| 27.5° | 340.0  |
| 30°   | 278.2  |
| 32.5° | 222.1  |
| 35°   | 171.7  |
| 37.5° | 131.7  |
| 40°   | 98.5   |
| 42.5° | 73.3   |
| 45°   | 55.0   |
| 47.5° | 42.4   |
| 50°   | 33.2   |
| 52.5° | 27.5   |
| 55°   | 22.9   |
| 57.5° | 19.5   |
| 60°   | 17.2   |
| 62.5° | 14.9   |
| 65°   | 12.6   |
| 67.5° | 11.4   |
| 70°   | 9.2    |
| 72.5° | 8.0    |
| 75°   | 6.9    |
| 77.5° | 4.6    |
| 80°   | 3.4    |
| 82.5° | 2.3    |
| 85°   | 1.1    |
| 87.5° | 1.1    |
| 90°   | 0.0    |

(END OF REPORT)